

Omni-ID Fit 400P

Compact ceramic UHF RFID tag optimized for non-metallic and plastic substrates. Compatible with heat shrink, potting and injection moulding finishing processes for covert embedding in plastic assets and tool handles.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range – EU	866–868 MHz
Frequency Range – US	902–928 MHz
IC Type (Chip)	EM 4124
EPC Memory	96 bits
User Memory	0 bits
Unique TID	64 bits
Read Range – Fixed Reader	Up to 4 m / 13.1 ft
Read Range – Handheld Reader	Up to 2 m / 6.5 ft
Material Compatibility	Plastic and non-metallic substrates

PHYSICAL SPECIFICATION

Size	17.6 × 7.1 × 4.1 mm / 0.70 × 0.28 × 0.16 in
Material	Ceramic
Weight	2.6 g
Attachment	Permanent liquid adhesive (not included) or film adhesive (option)

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-40°C to +75°C
Application Temperature	+18°C to +35°C
IP Rating	IP68
Shock & Vibration	MIL-STD-810 G
Certifications	CE, RoHS

FEATURE HIGHLIGHTS

- EM 4124 – EPC Class 1 Gen2v2, EU/US dual frequency
- Read range: 4 m fixed / 2 m handheld – optimized for plastic/non-metal
- IP68, MIL-STD-810 G – ceramic 17.6×7.1×4.1 mm, covert tag

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag