

# Xerafy CARGO-OUTDOOR

Xerafy CARGO-OUTDOOR is an industrial RFID tag with read range Up to 39.37 ft (12 m), IP68 protection.



## RFID SPECIFICATION

|                      |                                              |
|----------------------|----------------------------------------------|
| Protocol             | EPC global Class 1 Gen 2                     |
| Operating Frequency  | 902-928 MHz (US); 865-868 MHz (EU)           |
| Chip                 | Impinj M750                                  |
| Memory               | 96 bits EPC; 96 bits TID 32 bits user memory |
| Write Cycles         | 10,000 times                                 |
| Data Retention       | 10 years                                     |
| Read Range On Metal  | Up to 39.37 ft (12 m)                        |
| Read Range Off Metal | Up to 19.69 ft (6 m)                         |
| Polarization         | Linear                                       |
| Radiation Pattern    | on metal                                     |

## PHYSICAL SPECIFICATION

|                     |                                         |
|---------------------|-----------------------------------------|
| Material            | Industry grade polymer, Stainless steel |
| Dimensions (mm)     | 100 x 26 x 8.90                         |
| Dimensions (in)     | 3.94 x 1.02 x 0.30                      |
| Weight              | 0.62 oz (17.80 g)                       |
| Rivet Hole Diameter | 0.14 in (3.50 mm)                       |

ENVIRONMENTAL RESISTANCE

|                       |                                           |
|-----------------------|-------------------------------------------|
| Operating Temperature | -40°C to +85°C -40°F to +185°F            |
| Survival Temperature  | -40°C to +85°C (48 hours) -40°F to +185°F |
| IP Rating             | IP68                                      |
| Compression Strength  | 29 psi (200 kPa)                          |
| Shock                 | 3 ft (1 m) to concrete/granite            |
| Vibration             | MIL-STD-810G                              |
| Warranty              | 1 year                                    |

APPLICATIONS

|              |                                                                                  |
|--------------|----------------------------------------------------------------------------------|
| Applications | RTI inventory, Transportation and logistics, Yard management, Construction tools |
|--------------|----------------------------------------------------------------------------------|

FEATURE HIGHLIGHTS

- Up to 39.37 ft (12 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

|               |                       |
|---------------|-----------------------|
| Category      | UHF RFID On-Metal Tag |
| Product Group | RFID Label / Tag      |