

Xerafy Container Trak

Xerafy Container Trak is an industrial RFID tag with read range Up to 131.23 ft (40 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 Impinj M830
Memory	128 bits EPC; 96 bits TID
Write Cycles	10,000 times
Data Retention	10 years
Read Range On Metal	Up to 131.23 ft (40 m)
Read Range Off Metal	Up to 82.02 ft (25 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	139 x 42.20 x 12
Dimensions (in)	5.46 x 1.65 x 0.47
Weight	1.76 oz (50 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C (48 hours) -40°F to +185°F Container OUTDOOR
IP Rating	IP68
Compression Strength	29 psi (200 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Last-Mile logistics, Supply chain & inventory, management, Returnable transport packaging, (RTP), Yard management
--------------	---

FEATURE HIGHLIGHTS

- Up to 131.23 ft (40 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag