

Xerafy METAL-SKIN-DELTA

Xerafy METAL-SKIN-DELTA is an industrial RFID tag with read range Up to 11.48 ft (3.50 m) on metal Up to 8.20 ft (2.50 m) on plastic, IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	Impinj M830
Memory	128 bits EPC; 96 bits TID
Write Cycles	10,000 times
Data Retention	10 years
Read Range (Fixed)	Up to 11.48 ft (3.50 m) on metal Up to 8.20 ft (2.50 m) on plastic
Read Range (Handheld)	Up to 6.56 ft (2 m) on metal Up to 4.92 ft (1.50 m) on plastic
Polarization	Linear

PHYSICAL SPECIFICATION

Material	White thermal transfer
Dimensions (mm)	70 x 30 x 0.4
Dimensions (in)	2.76 x 1.18 x 0.02
Weight	2.20 lbs (0.90 kg)
Reel Core	76.2mm/3(in)
Packing Information	500pcs/roll

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Vibration	MIL-STD-810G
Storage Humidity	50±15%RH
Printer Compatibility	Zebra ZT410, ZT411R,
Warranty	1 year

APPLICATIONS

Applications	MRO parts and components, Automated warehouse, Electronic devices, IT assets, Data centers, Hospital equipment
--------------	--

FEATURE HIGHLIGHTS

- Up to 11.48 ft (3.50 m) on metal Up to 8.20 ft (2.50 m) on plastic
- IP68
- 40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag