

Xerafy METAL-SKIN-TITANIUM-25-HF

Xerafy METAL-SKIN-TITANIUM-25-HF is an industrial RFID tag with read range Up to 0.16 ft (5 cm), IP68 protection.



RFID SPECIFICATION

Protocol	ISO14443A
Operating Frequency	13.56 MHz (HF)
Chip	NTAG213
Memory	7 bytes UID; 144 bytes user memory
Write Cycles	100,000 times
Data Retention	10 years
Read Range (Fixed)	Up to 0.16 ft (5 cm)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	White thermal transfer face stock
Dimensions (mm)	ø 25 x 0.45
Dimensions (in)	ø 0.98 x 0.02

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Vibration	MIL-STD-810G
Storage Humidity	50±15%RH
Printer Compatibility	SATO CL4NX, Zebra
Warranty	1 year

APPLICATIONS

Applications	IT asset management, Warehouse management, Automotive components tracking, Equipment&device tracking
--------------	--

FEATURE HIGHLIGHTS

- Up to 0.16 ft (5 cm)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag