

Xerafy MICRO-INDUSTRIAL

Xerafy MICRO-INDUSTRIAL is an industrial RFID tag with read range Up to 49.21 ft (15 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902–928 MHz (US); 865–868 MHz (EU)
Chip	NXP UCODE 9xm
Memory	128/496 bits EPC; 96 bits TID; 752/384 bits user memory
Write Cycles	100,000 cycles
Data Retention	20 years
Read Range (Fixed)	Up to 49.21 ft (15 m)
Read Range (Handheld)	Up to 32.81 ft (10 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Industry grade polymer, 316L Stainless steel
Dimensions (mm)	55 × 36.20 × 7.50
Dimensions (in)	2.16 × 1.43 × 0.30
Weight	0.92 oz (26 g)
Packing Information	92 pcs /one box

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
Survival Temperature	-40°C to +250°C
High Temperature Cycle	250°C
IP Rating	IP68
Compression Strength	181 psi (1250 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	High temperature production, Work in process, Automotive assembly, RTI management
--------------	---

FEATURE HIGHLIGHTS

- Up to 49.21 ft (15 m)
- IP68
- 40°C to +85°C

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag