

Xerafy MICRO-POWER

Xerafy MICRO-POWER is an industrial RFID tag with read range Up to 13.12 ft (4 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 Impinj M750
Memory	96 bits EPC; 96 bits TID 32 bits user memory
Write Cycles	10,000 times
Data Retention	10 years
Read Range (Fixed)	Up to 13.12 ft (4 m)
Read Range (Handheld)	Up to 9.84 ft (3 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	32 x 10.80 x 6
Dimensions (in)	1.25 x 0.43 x 0.24
Weight	0.11 oz (3 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +150°C (4 hours) -40°F to +302°F
IP Rating	IP68
Compression Strength	181 psi (1,250 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Power tool tracking, Automotive Post-Paint processes, Construction tools, Audio-Video equipment, Rental fleet management, RTI management
--------------	--

FEATURE HIGHLIGHTS

- Up to 13.12 ft (4 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag