

Xerafy PICO-MINI-100

Xerafy PICO-MINI-100 is an industrial RFID tag with read range PICO Mini 100: Up to 1.64 ft (0.50 m) PICO Mini 150: Up to 9.84 ft (3 m) PICO Mini 300: Up to 13.12 ft (4 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC Class1 Gen2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 NXP UCODE 8
Memory	128 bits EPC, 96 bits TID
Write Cycles	100,000 Times
Data Retention	20 years
Read Range (Fixed)	PICO Mini 100: Up to 1.64 ft (0.50 m) PICO Mini 150: Up to 9.84 ft (3 m) PICO Mini 300: Up to 13.12 ft (4 m)
Read Range (Handheld)	PICO Mini 100: Up to 0.98 ft (0.30 m) PICO Mini 150: Up to 4.92 ft (1.50 m) PICO Mini 300: Up to 6.56 ft (2 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	FR4 (PCB)
Dimensions (mm)	1
Color	Black

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G; s, water
Warranty	1 year

APPLICATIONS

Applications	output power,, Hand tools for manufacturing,, aerospace, railways, nuclear,, military, Oil & Gas, Weapon management, Data centers
--------------	---

FEATURE HIGHLIGHTS

- PICO Mini 100: Up to 1.64 ft (0.50 m) PICO Mini 150: Up to 9.84 ft (3 m) PICO Mini 300: Up t...
- IP68
- 40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag