

Xerafy XPLATE

Xerafy XPLATE is an industrial RFID tag with read range Up to 32.81 ft (10 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 Impinj M750
Memory	96 bits EPC; 96 bits TID 32 bits user memory
Write Cycles	10,000 times
Data Retention	10 years
Read Range On Metal	Up to 32.81 ft (10 m)
Read Range Off Metal	Up to 19.69 ft (6 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Industry grade polymer, Aluminum or stainless steel plate
Dimensions (mm)	85 x 59.30 x 15.40,
Dimensions (in)	3.35 x 2.31 x 0.61,
Color	Dark gray
Weight	0.42 oz (11.80 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C (168 hours) -40°F to +185°F
Peak Temperature	100°C (212°F, 100 hours)
Chemical Resistance	4
IP Rating	IP68
Compression Strength	181 psi (1250 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on
--------------	--

FEATURE HIGHLIGHTS

- Up to 32.81 ft (10 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag