

Alien ALR-F800 Enterprise RFID Reader

The Alien ALR-F800 is a self-optimizing, enterprise-grade UHF RFID reader featuring real-time RF antenna optimization, the Alien GateScape web interface, and simultaneous PoE & 12VDC power options. Its compact form-factor with VESA mounting and IP53/Plenum rating makes it ideal for demanding deployments.



RFID SPECIFICATIONS

Model Number	ALR-F800 (All Models and Country Variants)
Supported RFID Tag Protocols	EPC Gen 2; ISO 18000-6c
Reader Protocols	Alien Reader Protocol, LLRP
Reader Power (with PoE)	≥31.5 dBm
Dense reader management	Dense Reader Mode, auto event triggering and event management

PLATFORM

Architecture	ARM9 677MHz processor, Linux, 512 MBytes DDR3 RAM, 2 GBytes Flash
Software SDK	Java, .NET, Ruby APIs

CONNECTIVITY

Communications	LAN TCP/IP (RJ-45), RS-232 (DB-9 F), USB Host, USB Console
LAN Protocols	TCP/IP, NTP, DNS, DHCP, SNMP
Antennas	4 reverse polarity TNC monostatic ports; circular or linear polarization; near and far field compatible
General Purpose I/O	Optically isolated. 0-24VDC rail. 4 inputs. 8 outputs (1500 mA capacity).

POWER

Power	Power over Ethernet or robust universal AC-DC power converter; 100-240 VAC, 50/60 Hz
-------	--

SIZE AND WEIGHT

Dimensions	(L) 20.2 cm x (W) 19.1 cm x (D) 2.8 cm (7.5" x 7.9" x 1.1")
Weight	0.85 kg (1.88 lb)

ENVIRONMENT

Operational Temperature	-20 °C to +50 °C
Environmental Ratings	IP53 and Plenum rated UL-2043
LED Indicators	Power, CPU, Read, Sniff, Ant 0-3

COMPLIANCE

RoHS	EU 2002/95/EC compliant
------	-------------------------

FEATURE HIGHLIGHTS

- Features GateScape Web Interface
- Flexible connectivity via LAN, USB, Serial
- Real-time RF antenna optimization
- Ease of field upgradeability
- PoE & 12VDC simultaneous power options
- Compact form-factor, standard VESA M4 mounting threads
- 8 Output / 4 Input / 12 VDC out GPIO
- Wi-Fi & Bluetooth capable via USB adapter

PRODUCT GROUP

Category	RFID Reader
Product Group	Fixed UHF RFID Reader