

Hopeland Sharp 340 RFID Reader

The Hopeland Sharp 340 is a standard expandable UHF RFID reader powered by the Impinj INDY R2000 chipset and Linux 2.6. It supports 4-port output, offline work for 40,000 tags, 2 GB RAM / 16 GB ROM, and rich connectivity including WiFi, Bluetooth, 4G, USB, RJ45, RS232, I/O, HDMI, and optional PoE.



HARDWARE, OS AND FIRMWARE

Processor	ARM9, 400MHz
Memory	Flash 128MB; DRAM 32 MB
Operating System	Linux 2.6
Firmware Upgrade	Demo software
API Support	C#, Android - Java

PHYSICAL CHARACTERISTICS

Dimensions	241 mm x 132 mm x 36 mm
Weight	1.2 kg
Housing Material	Die-cast aluminum
Visual Status Indicators	Power/Status, Ant 1-4/8

RFID CHARACTERISTICS

Air Protocols	ISO/IEC 18000-6B, 6C / EPC C1Gen2 (C2GEN2 optional)
Frequency	USA: 902-928 MHz (FCC part 15); EU: 865-868 MHz (ETSI EN 302208)
Reading Range	0-20 m
Output Power	0 dBm-35 dBm (+/-1 dBm) adjustable
Channel bandwidth	< 200 KHz
Anti-collision	Support multi-tag / intensive inventory
Work Mode	Fixed / hop frequency optional

CONNECTIVITY

Communications	RJ45, RS-485, OTG, Wiegand
General Purpose I/O	4 inputs (DC 0-24V), 4 outputs (DC max 30V, 2A; AC max 125V, 0.3A), optically isolated
Power supply	DC 24V/2.5A (DC 9V ~ 30V, 60W) or PoE (IEEE 802.3 af/at/bt)
Antenna Ports	4 Reverse Polarity TNC ports; circular or linear polarization; near and far field compatible

ENVIRONMENTAL

Operating Temp.	-20 to +70 C
Storage Temp.	-40 to +85 C
Humidity	5-90% non-condensing (+25 C)
Sealing	IP53

FEATURE HIGHLIGHTS

- Powered by Impinj R2000 chipset for maximum tag detection performance
- 4-port output with reverse-polarity TNC antenna ports
- Linux 2.6 operating system with 2 GB RAM and 16 GB ROM
- Offline operation for up to 40,000 tags
- RJ45, RS-485, OTG, Wiegand, USB, WiFi, Bluetooth, 4G, and HDMI connectivity
- Industrial, installation-friendly I/O connector
- RSSI, antenna detection, online update, RSSI filter, and speed filter support

PRODUCT GROUP

Category	RFID Reader
Product Group	Fixed UHF RFID Reader