

Nordic ID AR82

Nordic ID AR82 is a fixed 16-port UHF RFID reader with an integrated Linux-based computer and highly isolated antenna ports that prevent cross-readings. With reading speeds up to 1000 tags/s, it is ideal for shelf reading and large-scale inventory management.



UHF RFID

Supported standard	ISO 18000-63 (EPC Class 1 Gen 2)
Frequency band	ETSI 865.6–867.6 MHz or FCC/IC 902–928 MHz
Regulatory	CE ETSI EN 302 208, CE ETSI EN 301 489, FCC part 15.247 IC RSS210, Safety IEC 60950-1
Max receive sensitivity	-81 dBm
Typical reading speed	Up to 1000 tags/s
Conducted power	30 dBm (1 W)
External antenna port	16 pcs. 50 Ω / SMA Female
Isolation between external antenna ports	35 dBm / typical

PLATFORM

CPU	1.2GHz 64-bit Quad-Core Cortex-A53 processor
Operating system	Debian based embedded Linux
Memory	1 GB RAM / 4 GB flash

USER INTERFACE

SIM	Mini-SIM
Indicators	4 pcs (programmable) leds

CONNECTIVITY

USB	USB host, type A / USB device, type B
GPIO	4 inputs, opto isolated, max. 24V / 4 outputs, opto isolated, max. 50mA
Wireless WAN (optional)	3G HSPA (B1, B2, B5, B6, B8 and B19) / 2G GPRS / EDGE
LAN	Ethernet 10/100 Mbit
Wireless LAN (optional)	IEEE 802.11 a/b/g/n, dual band WLAN 2.4 / 5 GHz

POWER

External Power Supply	PoE 802.3af or AC/DC adapter: 100-240 VAC / 24 VDC, 1.25A
Operating Power	12W PoE, 20 W DC

SIZE AND WEIGHT

Dimensions	(L) 210 x (W) 121 x (H) 31 mm
Weight	700 g / 24.7 oz

ENVIRONMENT

Environmental sealing	IP20, for indoor use only
Operating Temperature	-20 °C to 55 °C
Storage Temperature	-40 °C to 85 °C
Mounting	Detachable mounting bracket with VESA 75

SOFTWARE INTERFACE

Data management	Nordic ID Radea
Firmware update	Via Web management UI and RESTful service
API support	NUR API for RFID and RESTful service
Other protocols	LLRP

FEATURE HIGHLIGHTS

- Smart fixed area reader for automated UHF RFID data collection
- Enables real-time visibility of tagged items
- Integrated Linux based computer for versatile SW development options
- Cutting edge UHF RFID reading sensitivity and reading speed
- Versatile communication options
- Improved isolation between antenna ports to avoid cross readings

PRODUCT GROUP

Category	RFID Reader
Product Group	Fixed UHF RFID Reader