

## SATO CT4-LX RFID Printer

The SATO CT4-LX is a compact 4-inch smart desktop thermal printer that brings industrial-grade features — including auto UHF/HF/NFC RFID encoding, a 4.3-inch full-color touchscreen, user-replaceable print head and platen roller, and SATO AEP on-printer intelligence — into a lightweight chassis. It supports linerless printing, dual-band Wi-Fi, Bluetooth 4.1, and encodes approximately 2,500–7,000 RFID tags/labels per day.



### PRINT SPECIFICATIONS

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Print Method | Direct Thermal / Thermal Transfer                                               |
| Resolution   | 8 dots/mm (203 dpi), 12 dots/mm (305 dpi)                                       |
| Print Speed  | 203 dpi: 8 ips (203 mm/sec); 305 dpi: 6 ips (152 mm/sec); Linerless mode: 4 ips |
| Print Width  | 104 mm (4.09 in)                                                                |
| Print Mode   | Continuous, Tear-off, Cutter, Dispenser, Linerless                              |
| Display      | 4.3-inch full-color touch screen                                                |

### RFID SPECIFICATIONS

|                              |                                                       |
|------------------------------|-------------------------------------------------------|
| Air Interface Protocol (UHF) | ISO/IEC 18000-6 Type C (EPC Gen2 / ISO/IEC 18000-63)  |
| Air Interface Protocol (HF)  | ISO/IEC 15693 (extended-range HF logistics)           |
| Air Interface Protocol (NFC) | ISO/IEC 14443 (NFC short-range)                       |
| Operating Frequency (UHF)    | 860 – 960 MHz                                         |
| Operating Frequency (HF/NFC) | 13.56 MHz                                             |
| RFID Positioning             | Auto RFID positioning — encodes UHF / HF / NFC inlays |
| SATO RF Analyze (SRA)        | Automatic antenna/inlay optimization                  |
| Dual Antenna                 | Supports exact encoding to small-sized inlays         |

MEDIA SPECIFICATIONS

|                |                                                              |
|----------------|--------------------------------------------------------------|
| Media Type     | Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket, Linerless |
| Label Width    | Min. 25 mm (0.98 in) – Max. 118 mm (4.65 in)                 |
| Media Roll OD  | Max. 115 mm (4.53 in)                                        |
| Media Core ID  | 76 mm (3.0 in)                                               |
| Ribbon Width   | 45 – 111 mm (1.77 – 4.37 in)                                 |
| Ribbon Length  | Max. 100 m (328 ft)                                          |
| Ribbon Core ID | 12.7 mm (0.5 in)                                             |

CONNECTIVITY

|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| Data Interface (Standard) | USB 2.0 (Type A & Type B), Ethernet (DHCPv4/DHCPv6), NFC pairing |
| Data Interface (Optional) | Wi-Fi (dual-band), Bluetooth 4.1, RS-232C                        |

SYSTEM

|            |                                                             |
|------------|-------------------------------------------------------------|
| Memory     | 4 GB Flash / 1 GB RAM                                       |
| Emulation  | SBPL, SEPL, SZPL, SDPL, SIPL, STCL (auto-detect switching)  |
| Additional | Direct PDF Printing, AEP (Application Enabled Printing)     |
| Fonts      | 40 Scalable Fonts; 47 print languages, 31 display languages |

PHYSICAL SPECIFICATIONS

|                             |                                                                        |
|-----------------------------|------------------------------------------------------------------------|
| Dimensions (W x D x H)      | 178 x 238 x 214 mm (7.0 x 9.4 x 8.4 in)                                |
| Weight                      | DT model: approx. 3.3 kg (7.3 lbs); TT model: approx. 3.4 kg (7.5 lbs) |
| User-Replaceable Components | Print head, Platen roller                                              |

ELECTRICAL SPECIFICATIONS

|                             |                                            |
|-----------------------------|--------------------------------------------|
| Power Supply                | AC 100–240 V, 50/60 Hz                     |
| Power Consumption (Peak)    | 155 VA / 95 W (AC100V, 30% printing ratio) |
| Power Consumption (Standby) | 18 VA / 8 W (AC100V)                       |

ENVIRONMENTAL SPECIFICATIONS

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Operating Temperature | 0 – 40 °C (32 – 104 °F); Linerless mode: 5 – 35 °C (41 – 95 °F) |
| Operating Humidity    | 30 – 80% RH (non-condensing)                                    |
| Storage Temperature   | -10 – 60 °C (14 – 140 °F)                                       |
| Storage Humidity      | 15 – 90% RH (non-condensing)                                    |

FEATURE HIGHLIGHTS

- Auto RFID positioning for UHF (860–960 MHz), HF (ISO/IEC 15693), and NFC (ISO/IEC 14443) inlay encoding
- Dual antenna design for precise encoding of small-sized inlays
- SATO RF Analyze (SRA) for automatic RFID optimization
- 4.3-inch full-color touch screen with 31 display languages
- User-replaceable print head and platen roller to minimize downtime
- Patented label waste prevention technology
- Linerless printing mode support
- Compact and lightweight: 178 x 238 x 214 mm, ~3.4 kg
- 4 GB Flash / 1 GB RAM with 40 scalable fonts
- AEP (Application Enabled Printing) for standalone custom applications

PRODUCT GROUP

|               |                      |
|---------------|----------------------|
| Category      | Desktop RFID Printer |
| Product Group | Desktop RFID Printer |