

Zebra ZD500R UHF RFID Printer

The ZD500R extends Zebra's broad range of RFID printers by adding UHF RFID printing and encoding to Zebra's line of industry-leading thermal desktop printers. Designed for applications where space is at a premium, the compact ZD500R offers simple, one-touch printing and encoding, straightforward loading, and automatic RFID calibration, making it ideal for retail in-store exception tagging and similar applications where technical support staff is not always available.



RFID FEATURES

Protocol	Supports tags compatible with UHF EPC Gen 2 V1.2 / ISO 18000-6C
Minimum Pitch	Prints and encodes tags with a minimum pitch of 16 mm (0.6")
Adaptive Encoding	Adaptive Encoding Technology simplifies RFID setup and eliminates complex RFID placement guidelines
Monitoring	RFID job monitoring tools track RFID performance
ZPL Compatibility	RFID ZPL commands provide compatibility with existing Zebra RFID printers
MCS	Support for industry standard multi-vendor chip-based serialisation (MCS)
Block Permalocking	Supports block permalocking of user memory compatible with ATA Spec 2000
RFID Module	Integrated ThingMagic RFID Reader/Encoder

PRINTER SPECIFICATIONS

Print Methods	Thermal Transfer or Direct Thermal
Resolution	8 dots per mm (203 dpi); 12 dots per mm (300 dpi) optional
Memory	128 MB SDRAM; 256 MB Flash
Maximum Print Width	104 mm (4.09")
Maximum Print Length	990 mm (39.0")
Maximum Print Speed	152 mm (6") per second (203 dpi); 102 mm (4") per second (300 dpi)
Media Sensors	Multi-position gap and moveable black-line media sensors
Software Platform	Link-OS enabled
Firmware	ZPL II; Web View; Alert; ZBI

COMMUNICATION AND INTERFACE CAPABILITIES

Serial	RS-232 auto-sensing Serial interface, DB-9 (standard)
USB	USB V2.0, bi-directional (standard)
Parallel	Centronics Parallel (standard)
Ethernet	10/100 internal (standard)
Wireless	802.11 a/b/g/n and Bluetooth 3.0 (optional)

MEDIA CHARACTERISTICS

Label and Liner Width	19 mm – 108 mm (0.75" – 4.25")
Label and Liner Length	Min. 6.35 mm (0.25") tear-off; Min. 12.7 mm (0.5") with label sensor; Max. 990 mm (39")
Media Roll Size	Max. OD: 127 mm (5"); Core ID: 12.7 mm, 25 mm, 35 mm, 37.1 mm or 76 mm
Media Thickness	0.08 – 0.305 mm (0.003" – 0.012")
Media Types	Roll-fed or fan-fed, die-cut or continuous, tag stock, continuous receipt paper, wristbands

RIBBON CHARACTERISTICS

Outside Diameter	35 mm (1.36")
Standard Length	74 m (244"); Ratio: 1:1 media to ribbon
Width	33.8 mm – 109.2 mm (1.33" – 4.3")
Core Inner Diameter	12.7 mm (0.5")

PHYSICAL CHARACTERISTICS

Width	193 mm (7.6")
Height	191 mm (7.5")
Depth	254 mm (10.0")
Weight	2.2 kg (4.9 lbs)

OPERATING CHARACTERISTICS

Operating Temperature	4.4 °C to 41 °C (40 °F to 105 °F)
Storage Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Operating Humidity	5% to 95% non-condensing
Electrical	Auto-detectable 100–240 VAC, 50–60 Hz

FEATURE HIGHLIGHTS

- UHF EPC Gen 2 V1.2 / ISO 18000-6C RFID printing and encoding
- Integrated ThingMagic RFID Reader/Encoder
- Link-OS enabled with Cloud Connect and Print Touch (NFC)
- Quad connectivity: USB, Parallel, Serial, and Ethernet standard
- Optional 802.11 a/b/g/n Wi-Fi and Bluetooth 3.0
- Direct Thermal and Thermal Transfer print methods
- OpenACCESS for easy media loading
- ENERGY STAR qualified

PRODUCT GROUP

Category	Desktop RFID Printer
Product Group	Desktop RFID Printer