

Zebra ZD621R RFID Printer

The 4-inch ZD621R desktop RAIN/RFID printer/encoder is nearly 32% more powerful than the ZD500R. It delivers outstanding print performance, industry-leading reliability, unparalleled intelligence and security, a 4.3-inch full-color LCD touch display, and unmatched remote management capabilities, with Zebra's RE40 RFID module and Adaptive Encoding Technology.



RFID FEATURES

Protocol	Supports tags compatible with UHF EPC Gen 2 V2, ISO/IEC 18000-63 and RAIN RFID protocols
Minimum Pitch	Prints and encodes tags with a minimum pitch of 0.6"/16 mm
Adaptive Encoding	Adaptive Encoding Technology simplifies RFID setup and eliminates complex RFID placement guidelines
Monitoring	RFID job monitoring tools track RFID performance
Global Certification	Globally certified in more than 70 countries for RFID
RFID Log	RFID log records all RFID data with timestamps, ensuring complete traceability
MCS	Support for industry-standard, multi-vendor chip-based serialization (MCS)
RFID Module	Integrated Zebra RE40 RFID Reader/Encoder

PRINTER SPECIFICATIONS

Operating System	Link-OS printer operating system
Resolution	203 dpi/8 dots per mm; 300 dpi/12 dots per mm (optional)
Memory	512 MB Flash; 256 MB DDR3 SDRAM
Maximum Print Width	4.09 in./104 mm (203 dpi); 4.16 in./105 mm (300 dpi)
Maximum Print Speed	8 in./203 mm per second (203 dpi); 6 in./152 mm per second (300 dpi)
Display	4.3" full color touch LCD (480 x 272)
Firmware	ZPL II; EPL 2; XML; ZBI; PDF Direct

STANDARD FEATURES

Print Methods	Thermal Transfer
Connectivity	Ethernet, USB 2.0, USB Host (standard); RS-232 Serial, dual radio 802.11ac Wi-Fi + Bluetooth 4.2 (optional)
Mobile Setup	Printer setup mobile app for Android & iOS via Bluetooth Low Energy 5
Clock	Real Time Clock (RTC)
Energy	ENERGY STAR certified
Warranty	Two-year standard warranty

MEDIA AND RIBBON CHARACTERISTICS

Media Width	0.585 in./15 mm to 4.65 in./118 mm
Label Length	Min. 0.25 in./6.35 mm; Max. 39.0 in./991 mm
Media Roll Size	Max. OD: 5.00 in./127 mm; Core ID: 0.5 in./12.7 mm and 1.0 in./25.4 mm standard
Media Thickness	0.0024 in./0.06 mm min.; 0.0075 in./0.1905 mm max.
Ribbon Length	300 m (984 ft.) standard; 74 m (243 ft.)
Ribbon Width	1.3 in./33 mm – 4.3 in./109.2 mm
Ribbon Core I.D.	1 in./25.4 mm (300 m ribbon); 0.5 in./12.7 mm (74 m ribbon)

PHYSICAL CHARACTERISTICS

Dimensions	10.5 in. L x 8.0 in. W x 7.5 in. H / 267 mm L x 202 mm W x 192 mm H
Weight	5.5 lb. / 2.5 kg

OPERATING CHARACTERISTICS

Operating Temperature	40 °F to 105 °F / 4.4 °C to 41 °C
Storage Temperature	-40 °F to 140 °F / -40 °C to 60 °C
Operating Humidity	10% to 90% non-condensing
Electrical	Auto-detectable 100–240 VAC, 50–60 Hz; ENERGY STAR certified

FEATURE HIGHLIGHTS

- UHF EPC Gen 2 V2 / ISO/IEC 18000-63 / RAIN RFID protocol support
- Integrated Zebra RE40 RFID Reader/Encoder
- Globally certified in 70+ countries for RFID
- 4.3" full-color touch LCD with color-coded status and setup wizards
- Link-OS printer operating system with Print DNA software suite
- Adaptive Encoding Technology — no complex RFID placement guidelines
- RFID log with timestamps for full traceability
- 512 MB Flash / 256 MB DDR3 SDRAM — 32% more powerful than ZD500R
- Field-installable wireless dual radio: 802.11ac Wi-Fi + Bluetooth Classic 4.2
- Optional battery for portable operation
- ENERGY STAR certified, two-year standard warranty

PRODUCT GROUP

Category	Desktop RFID Printer
Product Group	Desktop RFID Printer