

Xerafy Cargo Trak II

Xerafy Cargo Trak II is an industrial RFID tag with read range Up to 39.37 ft (12 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	Impinj M750
Memory	96 bits EPC; 96 bits TID 32 bits user memory
Write Cycles	10,000 times
Data Retention	10 years
Read Range On Metal	Up to 39.37 ft (12 m)
Read Range Off Metal	Up to 19.69 ft (6 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Industry grade polymer, Stainless steel
Dimensions (mm)	100 x 26 x 8.90
Dimensions (in)	3.94 x 1.02 x 0.30
Weight	0.62 oz (17.80 g)
Rivet Hole Diameter	0.14 in (3.50 mm)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C (48 hours) -40°F to +185°F
IP Rating	IP68
Compression Strength	29 psi (200 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	RTI inventory, Transportation and logistics, Yard management, Construction tools
--------------	--

FEATURE HIGHLIGHTS

- Up to 39.37 ft (12 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag