

Xerafy METAL-SKIN-PLATINUM-60-MAX

Xerafy METAL-SKIN-PLATINUM-60-MAX is an industrial RFID tag with IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US)
Chip	NXP UCODE 8
Memory	128 bits EPC; 96 bits TID
Write Cycles	100,000 times
Data Retention	20 years
Polarization	Linear

PHYSICAL SPECIFICATION

Material	White thermal transfer face stock
Dimensions (mm)	60 x 25 x 1
Dimensions (in)	2.36 x 0.98 x 0.04
Weight	1.76 lbs (0.80 kg)
Packing Information	500pcs/roll

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Vibration	MIL-STD-810G
Printer Compatibility	SATO CL4NX,
Warranty	1 year

APPLICATIONS

Applications	Reusable packaging and containers, Automated warehouse, MRO parts and components, WIP inventory
--------------	---

FEATURE HIGHLIGHTS

- IP68
- -40°C to +85°C -40°F to +185°F
- NXP UCODE 8

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag