


Xerafy Nano X II

Xerafy Nano X II is an industrial RFID tag with read range Up to 32.81 ft (10 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	NXP UCODE 9xm
Memory	128/496 bits EPC, 96 bits TID, 752/384 bits user memory
Write Cycles	100,000 times
Data Retention	20 years
Read Range (Fixed)	Up to 32.81 ft (10 m)
Read Range (Handheld)	Up to 24.61 ft (7.50 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	31.70 x 12.80 x 4.97
Dimensions (in)	1.25 x 0.51 x 0.20
Weight	0.18 oz (5 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +150°C (168 hours) -40°F to +302°F
IP Rating	IP68
Compression Strength	167 psi (1,150 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	MRO tool tracking, Manufacturing WIP, IT asset management
--------------	---

FEATURE HIGHLIGHTS

- Up to 32.81 ft (10 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag