

Xerafy NFC-RTI-OUTDOOR

Xerafy NFC-RTI-OUTDOOR is an industrial RFID tag with read range HF3 Up to 0.03 ft (1 cm); UHF3 Up to 29.53 ft (9 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	13.56 MHz (HF) IC type (HF chip)1 NXP NTAG213; 902-928 MHz (US); 865-868 MHz (EU) IC type (UHF chip)1 Impinj R6-P
Memory	(HF)2 7 bytes UID 144 bytes user memory; (UHF)2 128/96 bits EPC 96 bits TID; 32/64 bits user memory
Read Range	HF3 Up to 0.03 ft (1 cm); UHF3 Up to 29.53 ft (9 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Anti-UV industry grade polymer
Dimensions (mm)	73.30 x 22.80 x 8.65
Dimensions (in)	2.88 x 0.90 x 0.34
Weight	0.39 oz (11 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	26 psi (180 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G

Warranty	1 year
----------	--------

APPLICATIONS

Applications

144 bytes user memory, IC type (UHF chip)1 Impinj R6-P, Legacy tracking systems, Oil and Gas assets, RTI management, Production logistics

FEATURE HIGHLIGHTS

- HF3 Up to 0.03 ft (1 cm); UHF3 Up to 29.53 ft (9 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	NFC / UHF RFID Tag
Product Group	RFID Label / Tag