

Xerafy Pico On Plus

Xerafy Pico On Plus is an industrial RFID tag with read range Up to 19.69 ft (6 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 Impinj M830
Memory	128 bits EPC, 96 bits TID
Write Cycles	10,000 times
Data Retention	10 years
Read Range (Fixed)	Up to 19.69 ft (6 m)
Read Range (Handheld)	Up to 14.44 ft (4.40 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Ceramic
Dimensions (mm)	12.80 x 7.08 x 3.08
Dimensions (in)	0.50 x 0.28 x 0.12
Weight	0.05 oz (1.40 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +150°C (168 hours) -40°F to +302°F
Peak Temperature	200°C (392°F)
IP Rating	IP68
Compression Strength	170 psi (1,176 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Hand tools for manufacturing,, aerospace, railways, nuclear,, military, Oil & Gas, Weapon management, Oilfield equipment, Data centers
--------------	--

FEATURE HIGHLIGHTS

- Up to 19.69 ft (6 m)
- IP68
- 40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag