

altis teknoloji

pursuing perfection with you

Xerafy SLIM-TRAK

Xerafy SLIM-TRAK is an industrial RFID tag with read range
Up to 6.56 ft (2 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	Alien Higgs 9
Memory	96 bits EPC; 96 bits TID 688 bits user memory
Read Range On Metal	Up to 6.56 ft (2 m)
Read Range Off Metal	Up to 4.92 ft (1.50 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	High temperature polymer
Dimensions (mm)	56.50 x 5.95 x 1.30
Dimensions (in)	2.22 x 0.23 x 0.05
Weight	0.04 oz (1 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +150°C -40°F to +302°F
IP Rating	IP68
Compression Strength	106 psi (731 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	MRO tool tracking, IT asset management, Military asset & weapon tracking
--------------	--

FEATURE HIGHLIGHTS

- Up to 6.56 ft (2 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag