

Xerafy TEX-55X12-SILICONE

Xerafy TEX-55X12-SILICONE is an industrial RFID tag with IP68 protection.

XERAFY

RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	NXP UCODE 9
Memory	96 bits EPC; 96 bits TID
Write Cycles	100,000 times
Data Retention	20 years
Read Range Off Metal	Up to 19.69 ft (6 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Silicone
Dimensions (mm)	55 x 12 x 2.50
Dimensions (in)	2.17 x 0.47 x 0.10
Color	Gray
Weight	0.07 oz (1.99 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	71.07 psi
Shock	1 m to concrete/granite
Vibration	MIL-STD-810G
Storage Humidity	20% - 60% RH
Warranty	200 washing cycles or 3 years

APPLICATIONS

Applications	The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on, Medical scrubs, Hospital linens, Hotel linens, Uniforms, Rental costumes
--------------	--

FEATURE HIGHLIGHTS

- IP68
- -40°C to +85°C -40°F to +185°F
- NXP UCODE 9

PRODUCT GROUP

Category	RFID Laundry Tag
Product Group	RFID Label / Tag