

Xerafy XENSE-TEMP

Xerafy XENSE-TEMP is an industrial RFID tag with read range Up to 6.56 ft (2 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	Asygn AS3211
Memory	192 bits EPC; 48 bits TID 32 bits user memory Customizable sensing features Temperature; humidity; strain; ambient light; pressure; magnetic field (hall effect); electrical continuity
Read Range On Metal	Up to 6.56 ft (2 m)
Read Range Off Metal	Up to 9.84 ft (3 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Industry grade polymer, Copper
Dimensions (mm)	100 x 26 x 8.90
Dimensions (in)	3.94 x 1.02 x 0.35
Weight	0.68 oz (19.40 g)
Rivet Hole Diameter	0.137 in +/-0.008

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	29 psi (200 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

FEATURE HIGHLIGHTS

- Up to 6.56 ft (2 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag