

Zebra ZQ511/ZQ521 Mobile RFID Printer

The ZQ511 and ZQ521 RFID mobile printers pair best-in-class mobile printing with a military-grade design for the toughest indoor and outdoor environments. They print and encode UHF RFID labels on-demand (3 in. ZQ511 / 4 in. ZQ521), withstand 6.6 ft. drops to concrete, carry an IP54 rating, and are powered by a 3250 mAh PowerPrecision+ battery with optional 6500 mAh extended battery.



RFID FEATURES

Protocol	Supports tags compatible with UHF EPC Gen 2 V2, ISO/IEC 18000-63 and RAIN RFID protocols
Adaptive Encoding	Adaptive Encoding Technology simplifies RFID setup and eliminates complex RFID placement guidelines
Minimum Pitch	Prints and encodes tags with a minimum pitch of 16 mm
MCS	Support for industry standard multi-vendor chip-based serialization (MCS)
Block Permalocking	Supports block permalocking of user memory compatible with ATA Spec 2000
RFID Module	Integrated RFID Reader/Encoder

PRINTER SPECIFICATIONS

Operating System	Link-OS printer operating system
Resolution	203 dpi (8 dots per mm)
Memory	256 MB RAM, 512 MB Flash
Maximum Print Width	ZQ511: 2.83 in./72 mm; ZQ521: 4.09 in./104 mm
Maximum Print Speed	Up to 5 in./127 mm per second (Draft Mode enabled)
Print Method	Direct thermal
Processor	528 MHz ARM processor
Battery	3250 mAh PowerPrecision+ removable, rechargeable Li-Ion

STANDARD FEATURES

OS Connectivity	Android, Apple iOS, Windows Mobile connectivity
WLAN	802.11ac
Bluetooth	Bluetooth 4.1 EDR + LE
USB	USB On-The-Go ports
Display	Simple easy-to-read LCD with large icons for battery and wireless status
IP Rating	IP54 rated for protection against solid and liquid ingress
Drop Rating	MIL-STD 810G certified; multiple drops from 6.6 ft./2 m to concrete
Print Orientation	Supports vertical and horizontal printing; can be used in any orientation

PHYSICAL CHARACTERISTICS

ZQ511 Dimensions	5.9 in. L x 4.7 in. W x 2.4 in. H / 150 mm L x 120 mm W x 62 mm H
ZQ511 Weight	1.39 lbs / 0.63 kg
ZQ521 Dimensions	6.2 in. L x 6.1 in. W x 2.6 in. H / 158 mm L x 155 mm W x 67 mm H
ZQ521 Weight	1.73 lbs / 0.79 kg

MEDIA CHARACTERISTICS

Media Width	ZQ511: 35 – 80 mm; ZQ521: 50.8 – 113 mm
Maximum Media Roll Size	ZQ511: 51 mm; ZQ521: 57 mm
Media Types	Black-mark RFID Label, Receipt, Tag

OPERATING CHARACTERISTICS

Operating Temperature	-20 °C to 55 °C (-4 °F to 131 °F)
Operating Humidity	10% to 90% non-condensing
Charging Temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage Temperature	-30 °C to 66 °C (-22 °F to 150 °F)

FEATURE HIGHLIGHTS

- UHF EPC Gen 2 V2 / ISO/IEC 18000-63 / RAIN RFID on-demand mobile printing
- MIL-STD 810G certified; multiple drops from 6.6 ft./2 m to concrete
- IP54 dust and liquid ingress protection
- 3250 mAh PowerPrecision+ Li-Ion battery; optional 6500 mAh extended battery
- 802.11ac Wi-Fi + Bluetooth 4.1 Classic and BLE dual radio
- Power Smart Print Technology for optimized battery consumption
- Link-OS operating system with Print DNA suite
- ZQ511: 2.83 in./72 mm max print width; ZQ521: 4.09 in./104 mm max print width
- 528 MHz ARM processor; 256 MB RAM / 512 MB Flash
- Two-year standard warranty

PRODUCT GROUP

Category	Mobile RFID Printer
Product Group	Mobile RFID Printer