

Zebra ZQ630 Mobile RFID Printer

The ZQ630 RFID mobile printer is the only RFID mobile printer in the market, allowing workers to print and encode RFID labels on the spot. A 6800 mAh PowerPrecision+ battery powers the longest shifts, an instant wake-up feature on Wi-Fi or Bluetooth ensures zero downtime, and a large color display with 5-way navigation provides full printer status at a glance.



RFID FEATURES

Protocol	Supports tags compatible with UHF EPC Gen 2 V2, ISO/IEC 18000-63 and RAIN RFID protocols
Adaptive Encoding	Adaptive Encoding Technology simplifies RFID setup and eliminates complex RFID placement guidelines
Minimum Pitch	Prints and encodes tags with a minimum pitch of 16 mm
MCS	Support for industry standard multi-vendor chip-based serialization (MCS)
Block Permalocking	Supports block permalocking of user memory compatible with ATA Spec 2000
RFID Module	Integrated RFID Reader/Encoder

PRINTER SPECIFICATIONS

Operating System	Link-OS
Resolution	203 dpi / 8 dots per mm
Memory	256 MB RAM; 512 MB Flash
Maximum Print Width	4.1 in./104 mm
Maximum Print Speed	Up to 4.5 in./115 mm per second
Print Length	Min. 0.5 in./12.7 mm; Max. 32 in./813 mm
Battery	6800 mAh (nominal) 49.4 Wh removable, rechargeable PowerPrecision+ Li-Ion

STANDARD FEATURES

OS Connectivity	Apple iOS, Android and Windows Mobile connectivity
Print Method	Direct thermal printing of barcodes, text and graphics
Programming Languages	CPCL, EPL and ZPL programming languages
Display	Large color display (288 x 240 pixels) with 5-way navigation buttons
Media Sensing	Black mark sensing; label present sensor for issuing labels one at a time
IP Rating	IP43 dust- and water-resistance (IP54 with soft case)
Drop Tolerance	Multiple drops from 6 ft./1.83 m to concrete
Processor	400 MHz 32-bit ARM processor

COMMUNICATION AND INTERFACE CAPABILITIES

WLAN	802.11ac with WPA/WPA2, 802.1x; simultaneous Bluetooth 4.2 dual radio
Bluetooth	Bluetooth 4.2 Classic and BLE; Made for iPod/iPhone/iPad certified
Ethernet	10/100 Ethernet support via charging cradle
USB	USB 2.0 full-speed interface (12 Mbps); Mini-B connector
Serial	14-pin RS-232C port up to 115.2 Kbps

PHYSICAL CHARACTERISTICS

Dimensions	7.35 in. L x 6.5 in. W x 3.25 in. H / 187 mm L x 165 mm W x 82.5 mm H
Weight with Battery	2.45 lbs / 1.1 kg

MEDIA CHARACTERISTICS

Media Width	2.0 in./51 mm – 4.4 in./112 mm (lined)
Maximum Media Roll Size	2.6 in./66 mm O.D. on a 0.75 in./19 mm or 1.375 in./34.9 mm inner core
Media Types	Die-cut labels and tags, receipt paper, RFID, black bar

OPERATING CHARACTERISTICS

Operating Temperature	-20 °C to 50 °C (-4 °F to 122 °F)
Operating Humidity	10% to 90% non-condensing
Storage Temperature	-25 °C to 65 °C (-13 °F to 149 °F)

FEATURE HIGHLIGHTS

- Industry's only RFID mobile printer at 4-inch print width
- UHF EPC Gen 2 V2 / ISO/IEC 18000-63 / RAIN RFID on-demand encoding
- 6800 mAh PowerPrecision+ Li-Ion battery — longest shift coverage
- Instant wake-up on Wi-Fi or Bluetooth
- 802.11ac Wi-Fi + Bluetooth 4.2 Classic and BLE dual radio with 802.11r fast roaming
- Large color display (288 x 240 px), 5-way navigation, WML-customizable
- IP43 standard (IP54 with soft case); drops to 6 ft./1.83 m
- 256 MB RAM / 512 MB Flash; Link-OS with Print DNA suite
- Backward compatible with QLn Series accessories

PRODUCT GROUP

Category	Mobile RFID Printer
Product Group	Mobile RFID Printer