

DesignEye — Run it on any laptop

Clone, configure, start. About 15 minutes, most of it Docker downloading images.

0 Install these first

Docker Desktop
docker.com/products/docker-desktop

Git
git-scm.com

The model file
ask Ali (~99 MB, not on GitHub)

1 Clone the repository

```
git clone https://github.com/<your-username>/designeye.git
```

```
cd designeye
```

2 Add the model file

The trained model is 99 MB, so GitHub does not carry it. Ali will send stage3_ui_best_val.pth. Put it here exactly:

```
backend/app/ml/weights/stage3_ui_best_val.pth
```

Without this the app starts but every upload fails.

3 Create your settings file

Copy the template, then generate a login secret:

```
cp .env.example .env
```

```
python -c "import secrets;print(secrets.token_urlsafe(48))"
```

Paste that output as JWT_SECRET= inside .env. Leave everything else as it is — the defaults run fully offline with no accounts or API keys. On Windows use copy .env.example .env instead of cp.

4 Start everything

```
docker compose up -d --build
```

First run takes 5–10 minutes: it downloads Python, Node, MongoDB and Redis, and installs PyTorch. Later runs take seconds.

5 Create the demo account

```
docker compose exec api python -m app.seed --reset
```

6 Open it and sign in

Web app	http://localhost:3000
Email	demo@designeye.app
Password	Demo@1234
API docs	http://localhost:8000/docs

Check it actually works

Everything healthy?	open http://localhost:8000/health — model_loaded must be true
Run the tests	<code>docker compose exec api python -m pytest -q</code>

If something goes wrong

Problem	Fix
model_loaded is false	The .pth file is missing or in the wrong folder. Re-check step 2.
Port already in use	Something else is on 3000, 8000 or 27017. Close it, or edit the ports in docker-compose.yml.
redis is false	Normal. DEV_MODE runs analysis inline, so Redis is not needed.
Changed code, nothing happened	Code is baked into the image. Restart is not enough — rebuild: <code>docker compose build api worker frontend</code> , then <code>up -d</code> .
Want to start over	<code>docker compose down -v</code> wipes the database, then repeat steps 4 and 5.

Understanding the code: start with docs/CODE_WALKTHROUGH.md — it is written to be read with the code open beside it. docs/DEVIATIONS.md explains why anything differs from the SDS. • DesignEye, Final Year Project, Group S26CS003, University of Central Punjab.