

1. Define a UserCreate model with name: str, email: str, age: int. Create a POST /users route that accepts it and returns it back.

POST /users Create User

Parameters

Cancel

Reset

Name	Description
response_model	response_model
any	
(query)	

Request body required

application/json

Edit Value | Schema

```
{  "name": "alina",  "email": "abc@gmail.com",  "age": 19}
```

Execute

Clear

Responses

Curl

```
curl -X 'POST' \  'http://127.0.0.1:8000/users' \  -H 'accept: application/json' \  -H 'Content-Type: application/json' \  -d '{  "name": "alina",  "email": "abc@gmail.com",  "age": 19}'
```

Request URL

```
http://127.0.0.1:8000/users
```

Server response

Code	Details
200	Response body <pre>{ "id": 1, "name": "alina", "email": "abc@gmail.com", "age": 19}</pre> Download Response headers <pre>content-length: 56 content-type: application/json date: Wed, 08 Jul 2025 11:17:00 GMT server: uvicorn</pre>

Responses

Code	Description	Links
------	-------------	-------

2. Add a Field() constraint to email requiring it to match a basic email pattern, and age must be between 18 and 120.

Edit Value | Schema

```
{
  "name": "Alina",
  "email": "alinagmail",
  "age": 180
}
```

Execute

Clear

Responses

Curl

```
curl -X 'POST' \
  'http://127.0.0.1:8000/users' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "name": "Alina",
    "email": "alinagmail",
    "age": 180
  }'
```

Request URL

<http://127.0.0.1:8000/users>

Server response

Code	Details
------	---------

422	Error: Unprocessable Content
-----	------------------------------

Response body

```
{
  "detail": [
    {
      "type": "string_pattern_mismatch",
      "loc": [
        "body",
        "email"
      ],
      "msg": "String should match pattern '^@[\\s]+@[\\s]+\\.?[\\s]+$'",
      "input": "alinagmail",
      "ctx": {
        "pattern": "^@[\\s]+@[\\s]+\\.?[\\s]+$"
      }
    },
    {
      "type": "less_than_equal",
      "loc": [
        "body",
        "age"
      ],
      "msg": "Input should be less than or equal to 120",
      "input": 180,
      "ctx": {
        "le": 120
      }
    }
  ]
}
```

Download

3. Create a UserRead model that adds an id: int field. Use response_model=UserRead on the route so the response always includes an id.

```
{
  "name": "Alina",
  "email": "alina@gmail.com",
  "age": 18
}
```

[Execute](#) [Clear](#)

Responses

Curl

```
curl -X 'POST' \
  'http://127.0.0.1:8000/users' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "name": "Alina",
    "email": "alina@gmail.com",
    "age": 18
  }'
```

Request URL

```
http://127.0.0.1:8000/users
```

Server response

Code	Details
200	Response body <pre>{ "name": "Alina", "email": "alina@gmail.com", "age": 18, "id": 1 }</pre> Response headers <pre>content-length: 58 content-type: application/json date: Wed, 08 Jul 2025 12:55:49 GMT server: uvicorn</pre>

Responses

Code	Description	Links
200	Successful Response	No links

Media type

application/json

[Continue & reset headers](#)

4. Create a nested model: Address with city and country, and embed it in a UserCreate model.

Request body required

application/json

Edit Value | Schema

```
{
  "name": "alina",
  "email": "abc@gmail.com",
  "age": 18,
  "address": {
    "city": "Lahore",
    "country": "Pakistan"
  }
}
```

Execute

Clear

Responses

Curl

```
curl -X 'POST' \
  'http://127.0.0.1:8000/users' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "name": "alina",
    "email": "abc@gmail.com",
    "age": 18,
    "address": {
      "city": "Lahore",
      "country": "Pakistan"
    }
  }'
```

Request URL

```
http://127.0.0.1:8000/users
```

Server response

Code Details

200

Response body

```
{
  "id": 1,
  "name": "alina",
  "email": "abc@gmail.com",
  "age": 18,
  "address": {
    "city": "Lahore",
    "country": "Pakistan"
  }
}
```



Download

Response headers

```
content-length: 185
content-type: application/json
date: Wed, 08 Jul 2026 11:20:22 GMT
server: uvicorn
```

Responses

5. Add a `@field_validator` to reject any name that contains numbers.

0/docs#/default/create_user_users_post

```
{
  "name": "Alinal234",
  "email": "alina@mail.com",
  "age": 19,
  "address": {
    "city": "Lahore",
    "country": "Pakistan"
  }
}
```

Execute Clear

Responses

Curl

```
curl -X 'POST' \
  'http://127.0.0.1:8000/users' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "name": "Alinal234",
    "email": "alina@mail.com",
    "age": 19,
    "address": {
      "city": "Lahore",
      "country": "Pakistan"
    }
  }'
```

Request URL

http://127.0.0.1:8000/users

Server response

Code	Details
422	Error: Unprocessable Content Response body <pre>{ "detail": [{ "type": "value_error", "loc": ["body", "name"], "msg": "Value error, Name must not contain numbers", "input": "Alinal234", "ctx": { "error": {} } }] }</pre> Response headers <pre>content-length: 147 content-type: application/json date: Wed, 08 Jul 2026 13:03:45 GMT server: uvicorn</pre>

6. Create both ItemCreate and ItemRead schemas for a product (name, price, in_stock). The read schema adds created_at. Use response_model to ensure created_at always appears in responses.

No parameters

Request body required

application/json

Edit Value | Schema

```
{
  "name": "ASUS",
  "price": 100000,
  "in_stock": true
}
```

Execute

Clear

Responses

Curl

```
curl -X 'POST' \
  'http://127.0.0.1:8000/items' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "name": "ASUS",
    "price": 100000,
    "in_stock": true
  }'
```

Request URL

http://127.0.0.1:8000/items

Server response

Code Details

200

Response body

```
{
  "name": "ASUS",
  "price": 100000,
  "in_stock": true,
  "created_at": "2026-07-08T17:33:16.736820"
}
```



Download

Response headers

```
content-length: 90
content-type: application/json
date: Wed, 08 Jul 2026 12:33:16 GMT
server: uvicorn
```

Responses

Code Description

Links