

Question 1: Create a FastAPI app with a GET / route that returns {"message": "Hello, Artificizen"}.

127.0.0.1:8000/docs#/default/question1_get

FastAPI 0.1.0 OAS 3.1

default

GET / Question1

Parameters

No parameters

Execute Clear

Responses

Curl

```
curl -X 'GET' \
  'http://127.0.0.1:8000/' \
  -H 'accept: application/json'
```

Request URL

http://127.0.0.1:8000/

Server response

Code	Details
200	Response body <pre>{ "message": "Hello, Artificizen" }</pre> Response headers <pre>content-length: 32 content-type: application/json date: Tue, 07 Jul 2026 13:53:38 GMT server: uvicorn</pre>

Responses

Code	Description	Links
200	Successful Response	No links

Media type: application/json

Controls: Accept header

Question 2: Add a GET /users/{user_id} route that returns the user ID as an integer. Test what happens when you pass a string.

default

GET / Question1

GET /users/{user_id} Get User Id

Parameters

Name Description

user_id * required integer (path) 5

Execute Clear

Responses

Curl

```
curl -X 'GET' \
  'http://127.0.0.1:8000/users/5' \
  -H 'accept: application/json'
```

Request URL

http://127.0.0.1:8000/users/5

Server response

Code	Details
200	Response body <pre>{ "user_id": 5 }</pre> Response headers <pre>content-length: 13 content-type: application/json date: Tue, 07 Jul 2026 14:07:16 GMT server: uvicorn</pre>

Responses

Code	Description	Links
------	-------------	-------

Question 3: Add a GET /items route with optional query parameters skip (default 0) and limit (default 10) that return a fake paginated list.

pcs#/default/get_items_items_get

GET /items Get Items

Parameters

Cancel

Name	Description
skip	
integer (query)	2
limit	
integer (query)	5

Execute

Clear

Responses

Curl

curl -X 'GET' \ 'http://127.0.0.1:8000/items?skip=2&limit=5' \ -H 'accept: application/json'

Request URL

http://127.0.0.1:8000/items?skip=2&limit=5

Server response

Code	Details
200	Response body ["Keyboard", "Monitor", "Phone", "Camera", "Printer"] Response headers content-length: 49 content-type: application/json date: Tue, 07 Jul 2026 14:14:17 GMT server: uvicorn Download

Responses

Code	Description	Links
200	Successful Response	No links

Question 4: Raise an HTTPException with status 404 and a custom message when a user ID greater than 100 is requested.

127.0.0.1:8000/docs#/default/get_user_id_users_user_id_get

GET /users/{user_id} Get User Id

Parameters

Cancel

Name	Description
user_id ^{required}	
integer	105
(path)	

Execute Clear

Responses

Curl

```
curl -X 'GET' \
'http://127.0.0.1:8000/users/105' \
-H 'accept: application/json'
```

Request URL

```
http://127.0.0.1:8000/users/105
```

Server response

CodeDetails

404Error: Not Found

Response body

```
{
  "detail": "User not found"
}
```

Download

Response headers

```
content-length: 27
content-type: application/json
date: Tue, 07 Jul 2026 14:21:56 GMT
server: uvicorn
```

Responses

CodeDescriptionLinks

200Successful ResponseNo links

Media type

application/json

Controls Accept header

Example Value | Schema

Question 5: Add a POST /ping route that returns status code 201 with {"status": "created"}.

127.0.0.1:8000/docs#/default/ping_ping_post

POST /ping Ping

Parameters

Cancel

No parameters

Execute Clear

Responses

Curl

```
curl -X 'POST' \
'http://127.0.0.1:8000/ping' \
-H 'accept: application/json' \
-d ''
```

Request URL

```
http://127.0.0.1:8000/ping
```

Server response

CodeDetails

201

Response body

```
{
  "Status": "created"
}
```

Download

Response headers

```
content-length: 20
content-type: application/json
date: Tue, 07 Jul 2026 14:29:06 GMT
server: uvicorn
```

Responses

CodeDescriptionLinks

201Successful ResponseNo links

Media type

application/json

Controls Accept header

Example Value | Schema

"string"