| ID | File | Line | Real/Decoy | Algorithm | Category | Status | Replacement | What it tests | Scanner result (match, miss, mislabel) | Notes (What kind of test) |
|---|---|---|---|---|---|---|---|---|---|---|
| GT01 | ground_truth_demo | 9 | Real | RSA (2048) | asymmetric | vulnerable | ML-KEM / ML-DSA | Basic RSA 2048 use | Match | Base |
| GT02 | ground_truth_demo | 10 | Real | RSA (1024) | asymmetric | vulnerable | ML-KEM / ML-DSA | Basic RSA 1024 use | Match | Base |
| GT03 | ground_truth_demo | 11 | Real | ECDSA (P-256) | asymmetric | vulnerable | ML-DSA | Basic ECDSA (P-256) use | Match | Base |
| GT04 | ground_truth_demo | 12 | Real | Ed25519 | asymmetric | vulnerable | ML-DSA | Basic Ed25519 use | Match | Base |
| GT05 | ground_truth_demo | 13 | Real | ECDSA | asymmetric | vulnerable | ML-DSA | If it catches both assets on the same line | Match | Base |
| GT06 | ground_truth_demo | 13 | Real | SHA-256 | hash | safe | None needed | Basic SHA-256 use | Match | Base |
| GT07 | ground_truth_demo | 16 | Real | AES-GCM | symmetric | safe | None needed | Basic AES-GCM use | Match | Base |
| GT08 | ground_truth_demo | 17 | Real | AES-CBC | symmetric | transitional | AES-GCM | Basic AES-CBC use | Match | Base |
| GT09 | ground_truth_demo | 18 | Real | 3DES | symmetric | weak | AES-256-GCM | Basic 3DES use | Match | Base |
| GT10 | ground_truth_demo | 21 | Real | MD5 | hash | weak | SHA-256 / SHA-3 | Basic MD5 use | Match | Base |
| GT11 | ground_truth_demo | 22 | Real | SHA-1 | hash | weak | SHA-256 / SHA-3 | Basic SHA-1 use | Match | Base |
| GT12 | ground_truth_demo | 23 | Real | SHA-256 | hash | safe | None needed | Basic SHA-256 use | Match | Base |
| GT13 | ground_truth_demo | 24 | Real | SHA-512 | hash | safe | None needed | Basic SHA-512 use | Match | Base |
| GT14 | ground_truth_demo | 27 | Real | X25519MLKEM768 | key exchange | safe | None needed | When the asset is a hybrid PAQ group, does it catch all the assets | Match | Base |
| GT15 | ground_truth_demo | 27 | Real | X25519 | key exchange | vulnerable | Hybrid ML-KEM group | Hybrid PQC group, does it catch all 3 assets | Match | Base |
| GT16 | ground_truth_demo | 27 | Real | prime256v1 | key exchange | vulnerable | Hybrid ML-KEM group | Hybrid PQC group, does it catch all 3 assets | Match | Base |
| AST01 | ast_demo | 7 | Real | RSA | asymmetric | vulnerable | ML-KEM / ML-DSA | Aliased import (RSA as r) | Match | Base |
| AST02 | ast_demo | 8 | Real | MD5 | hash | weak | SHA-256 / SHA-3 | Aliased import (hashlib as h) | Match | Base |
| AST03 | ast_demo | 9 | Real | SHA-1 | hash | weak | SHA-256 / SHA-3 | Direct import (from hashlib import sha1) | Match | Base |
| AST04 | ast_demo | 10-13 | Real | AES-CBC | symmetric | transitional | AES-GCM | Multi-line call | Match | Base |
| AST-D1 | ast_demo | 6 | Decoy | None | N/A | N/A | N/A | Comment-only line mentioning RSA | Match | Base |
| GAP01 | gap_test | 9 | Real | RSA (3072) | asymmetric | vulnerable | ML-KEM / ML-DSA | | Match | Base |
| GAP02 | gap_test | 10 | Real | DSA | asymmetric | vulnerable | ML-DSA | | Match | Base |
| GAP03 | gap_test | 11 | Real | MD5 | hash | weak | SHA-256 / SHA-3 | | Match | Base |
| GAP04 | gap_test | 12 | Real | SHA3-256 | hash | safe | None needed | | Match | Base |
| GAP05 | gap_test | 13 | Real | BLAKE2b | hash | safe | None needed | | Match | Base |
| GAP06 | gap_test | 14 | Real | Fernet | symmetric | transitional | AES-256-GCM | Basic Fernet use | Match | Base |
| GAP07 | gap_test | 15 | Real | ChaCha20 | symmetric | safe | None needed | Basic ChaCha20 use | Match | Base |
| GAP08 | gap_test | 16 | Real | Blowfish | symmetric | weak | AES-256-GCM | Basic Blowfish use | Match | Base |
| GAP09 | gap_test | 16 | Real | ECB mode | symmetric | weak | AES-GCM | | Match | Base |
| GAP10 | gap_test | 17 | Real | AES-CBC | symmetric | transitional | AES-GCM | | Match | Base |
| GAP11 | gap_test | 18 | Real | TLS 1.0 (legacy) | protocol | weak | TLS 1.3 | Basic TLS 1.0 (legacy) use | Match | Base |
| S1a | blind_structure.py | 16 | Real | SHA-256 | hash | safe | None needed | Call in an if condition | TBD | Blind |
| S1b | blind_structure.py | 23 | Real | SHA-256 | hash | safe | None needed | Call in an if body | TBD | Blind |
| S2a | blind_structure.py | 29 | Real | MD5 | hash | weak | SHA-256 / SHA-3 | Call in a while condition | TBD | Blind |
| S2b | blind_structure.py | 34 | Real | AES-GCM | symmetric | safe | None needed | Call in a while body | TBD | Blind |
| S3a | blind_structure.py | 39 | Real | RSA | asymmetric | vulnerable | ML-KEM / ML-DSA | Call in a try body | TBD | Blind |
| S3b | blind_structure.py | 47 | Real | RSA | asymmetric | vulnerable | ML-KEM / ML-DSA | Call in an except body | TBD | Blind, Would it still count if an exception wasn't raise |
| S4 | blind_structure.py | 51 | Real | RSA | asymmetric | vulnerable | ML-KEM / ML-DSA | Call inside a plain function | TBD | Blind |
| D1 | blind_decoys.py | 4 | Decoy | None | N/A | N/A | N/A | Trailing comment on a real statement | TBD | Blind |
| D2a | blind_decoys.py | 8 | Decoy | None | N/A | N/A | N/A | Stray string statement mentioning an algorithm | TBD | Blind |
| D2b | blind_decoys.py | 12 | Decoy | None | N/A | N/A | N/A | Real docstring mentioning an algorithm | TBD | Blind. New row |
| D3 | blind_decoys.py | 15 | Decoy | None | N/A | N/A | N/A | Function named after an algorithm | TBD | Blind |
| D4a | blind_decoys.py | 21 | Decoy | None | N/A | N/A | N/A | Print string, level 1 (sentence) | TBD | Blind |
| D4b | blind_decoys.py | 24 | Decoy | None | N/A | N/A | N/A | Print string, level 2 (call name) | TBD | Blind |
| D4c | blind_decoys.py | 27 | Decoy | None | N/A | N/A | N/A | Print string, level 3 (call with arguments) | TBD | Blind |
| D4d | blind_decoys.py | 30 | Decoy | None | N/A | N/A | N/A | Print string, level 4 (real TLS group string) | TBD | Blind. Confirm with team |
| D5a1 | blind_decoys.py | 35 | Decoy | None | N/A | N/A | N/A | Method definition named sha1 | TBD | Blind |
| D5b1 | blind_decoys.py | 39 | Decoy | None | N/A | N/A | N/A | Method definition named generate_private_key | TBD | Blind |
| D5c1 | blind_decoys.py | 43 | Decoy | None | N/A | N/A | N/A | Method definition named sign | TBD | Blind |
| D5d1 | blind_decoys.py | 47 | Decoy | None | N/A | N/A | N/A | Method definition named sha256 | TBD | Blind |
| D5a2 | blind_decoys.py | 54 | Decoy | None | N/A | N/A | N/A | Call on your own object (myPassword.sha1()) | TBD | Blind |
| D5a3 | blind_decoys.py | 58 | Decoy | None | N/A | N/A | N/A | Call on an object named hashlib, no real import | TBD | Blind. Name collision |
| D5b2 | blind_decoys.py | 62 | Decoy | None | N/A | N/A | N/A | Call on an object named rsa, no real import | TBD | Blind. Name collision |
| D5c2 | blind_decoys.py | 66 | Decoy | None | N/A | N/A | N/A | Call on an object named ecdsa_key | TBD | Blind |
| D5d2 | blind_decoys.py | 69 | Decoy | None | N/A | N/A | N/A | hashlib.sha256() on a fake object, assigned to sha256_digest | TBD | Blind. Looks identical to a real call |
| D6 | blind_decoys.py | 72 | Decoy | None | N/A | N/A | N/A | Variable named ec | TBD | Blind |
| A1 | blind_algorithms.py | TBD | Real | AES-ECB | symmetric | weak | AES-GCM | Cipher plus mode | TBD | Blind |
| A2a | blind_algorithms.py | TBD | Real | HMAC | confirm | confirm | confirm | HMAC | TBD | Blind |
| A2b | blind_algorithms.py | TBD | Real | SHA-256 | hash | safe | None needed | Hash passed into HMAC | TBD | Blind |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| A3 | blind_algorithms.py | TBD | Real | Diffie-Hellman | key exchange | vulnerable | ML-KEM | Shor's algorithm target | TBD | Blind |
| A4 | blind_algorithms.py | TBD | Real | DES | symmetric | weak | AES-256-GCM | Plain DES | TBD | Blind |
| A5 | blind_algorithms.py | TBD | Real | RC4 | symmetric | weak | AES-256-GCM | Named in the proposal | TBD | Blind |
| A6 | blind_algorithms.py | TBD | Real | bcrypt | confirm | confirm | confirm | Password hashing | TBD | Blind. Category and status need deciding from team |
| A7 | blind_algorithms.py | TBD | Real | Argon2 | confirm | confirm | confirm | Algorithm name absent at the call (ph.hash) | TBD | Blind. Category and status need deciding from team |
| A8 | blind_algorithms.py | TBD | Real | scrypt | confirm | confirm | confirm | Password hashing | TBD | Blind. Category and status need deciding from team |