

به نام پیگانه معبود بخشنده مهربان

مبانی یادگیری ماشین

Machine Learning Foundations

گروه هوش مصنوعی، دانشکده مهندسی کامپیوتر، دانشگاه اصفهان

ترم اول سال تحصیلی ۰۲-۰۳

ارائه دهنده : پیمان ادیبی

شبکه های عصبی جلو سو

Feedforward Neural Networks

دسته بند شبکه عصبی

Neural Network for classification

Vector function with tunable parameters θ

$$\mathbf{f}(\cdot; \theta) : \mathbb{R}^N \rightarrow (0, 1)^K$$

Sample s in dataset S :


- input: $\mathbf{x}^s \in \mathbb{R}^N$
- expected output: $y^s \in [0, K - 1]$

Output is a conditional probability distribution:

$$\mathbf{f}(\mathbf{x}^s; \theta)_c = P(Y = c | X = \mathbf{x}^s)$$

نورون مصنوعی

Artificial Neuron




$$z(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + b$$

$$f(\mathbf{x}) = g(\mathbf{w}^T \mathbf{x} + b)$$

- $\mathbf{x}, f(\mathbf{x})$ input and output
- $z(\mathbf{x})$ pre-activation
- \mathbf{w}, b weights and bias
- g activation function

لایه ای از نورون های مصنوعی

Layer of Neurons




$$\mathbf{f}(\mathbf{x}) = g(\mathbf{z}(\mathbf{x})) = g(\mathbf{W}\mathbf{x} + \mathbf{b})$$

- \mathbf{W}, \mathbf{b} now matrix and vector

شبکه ای با یک لایه مخفی


One Hidden Layer Network




- $\mathbf{z}^h(\mathbf{x}) = \mathbf{W}^h \mathbf{x} + \mathbf{b}^h$
- $\mathbf{h}(\mathbf{x}) = g(\mathbf{z}^h(\mathbf{x})) = g(\mathbf{W}^h \mathbf{x} + \mathbf{b}^h)$
- $\mathbf{z}^o(\mathbf{x}) = \mathbf{W}^o \mathbf{h}(\mathbf{x}) + \mathbf{b}^o$
- $\mathbf{f}(\mathbf{x}) = \text{softmax}(\mathbf{z}^o) = \text{softmax}(\mathbf{W}^o \mathbf{h}(\mathbf{x}) + \mathbf{b}^o)$

شبکه ای با یک لایه مخفی

One Hidden Layer Network




Alternate representation




توابع فعاليت متداول

Element-wise activation functions




$$\text{sigm}(x) = \frac{1}{1 + e^{-x}}$$

$$\text{sigm}'(x) = \text{sigm}(x)(1 - \text{sigm}(x))$$



$$\tanh(x) = \frac{e^{2x} - 1}{e^{2x} + 1}$$

$$\tanh'(x) = 1 - \tanh(x)^2$$



$$\text{relu}(x) = \max(0, x)$$

$$\text{relu}'(x) = 1_{x>0}$$

- blue: activation function
- green: derivative

تابع بیشینه نرم

Softmax function

$$\text{softmax}(\mathbf{x}) = \frac{1}{\sum_{i=1}^n e^{x_i}} \cdot \begin{bmatrix} e^{x_1} \\ e^{x_2} \\ \vdots \\ e^{x_n} \end{bmatrix}$$

$$\frac{\partial \text{softmax}(\mathbf{x})_i}{\partial x_j} = \begin{cases} \text{softmax}(\mathbf{x})_i \cdot (1 - \text{softmax}(\mathbf{x})_i) & i = j \\ -\text{softmax}(\mathbf{x})_i \cdot \text{softmax}(\mathbf{x})_j & i \neq j \end{cases}$$

- vector of values in (0, 1) that add up to 1
- $p(Y = c | X = \mathbf{x}) = \text{softmax}(\mathbf{z}(\mathbf{x}))_c$
- the pre-activation vector $\mathbf{z}(\mathbf{x})$ is often called "the logits"

آموزش شبکه

Training the network

Find parameters $\theta = (\mathbf{W}^h; \mathbf{b}^h; \mathbf{W}^o; \mathbf{b}^o)$ that minimize the negative log likelihood (or [cross entropy](#))

The loss function for a given sample $s \in S$:

$$l(\mathbf{f}(\mathbf{x}^s; \theta), y^s) = nll(\mathbf{x}^s, y^s; \theta) = -\log \mathbf{f}(\mathbf{x}^s; \theta)_{y^s}$$

example $y^s = 3$

$$l(\mathbf{f}(\mathbf{x}^s; \theta), y^s) = l \left(\begin{bmatrix} f_0 \\ \dots \\ f_3 \\ \dots \\ f_{K-1} \end{bmatrix}, \begin{bmatrix} 0 \\ \dots \\ 1 \\ \dots \\ 0 \end{bmatrix} \right) = -\log f_3$$

آموزش شبکه

Training the network

Find parameters $\theta = (\mathbf{W}^h; \mathbf{b}^h; \mathbf{W}^o; \mathbf{b}^o)$ that minimize the negative log likelihood (or [cross entropy](#))

The loss function for a given sample $s \in S$:

$$l(\mathbf{f}(\mathbf{x}^s; \theta), y^s) = nll(\mathbf{x}^s, y^s; \theta) = -\log \mathbf{f}(\mathbf{x}^s; \theta)_{y^s}$$

The cost function is the negative likelihood of the model computed on the full training set (for i.i.d. samples):

$$L_S(\theta) = -\frac{1}{|S|} \sum_{s \in S} \log \mathbf{f}(\mathbf{x}^s; \theta)_{y^s} + \lambda \Omega(\theta)$$

$\lambda \Omega(\theta) = \lambda(\|\mathbf{W}^h\|^2 + \|\mathbf{W}^o\|^2)$ is an optional regularization term.

نزول در امتداد گرادیان تصادفی

Stochastic Gradient Descent

Initialize θ randomly

For E epochs perform:

- Randomly select a small batch of samples ($B \subset S$)
 - Compute gradients: $\Delta = \nabla_{\theta} L_B(\theta)$
 - Update parameters: $\theta \leftarrow \theta - \eta \Delta$
 - $\eta > 0$ is called the learning rate
- Repeat until the epoch is completed (all of S is covered)

Stop when reaching criterion:

- nll stops decreasing when computed on validation set

نزول در امتداد گرادیان تصادفی

Computing Gradients

Output Weights: $\frac{\partial l(\mathbf{f}(\mathbf{x}), y)}{\partial W_{i,j}^o}$

Output bias: $\frac{\partial l(\mathbf{f}(\mathbf{x}), y)}{\partial b_i^o}$


Hidden Weights: $\frac{\partial l(\mathbf{f}(\mathbf{x}), y)}{\partial W_{i,j}^h}$

Hidden bias: $\frac{\partial l(\mathbf{f}(\mathbf{x}), y)}{\partial b_i^h}$

- The network is a composition of differentiable modules
- We can apply the "chain rule"

نزول در امتداد گرادیان تصادفی

Chain rule



$$z = u(\mathbf{v}(\mathbf{x}))$$


chain-rule

$$\frac{\partial z}{\partial x_i} = \sum_j \frac{\partial z}{\partial v_j} \frac{\partial v_j}{\partial x_i} = \nabla u \cdot \frac{\partial \mathbf{v}}{\partial x_i}$$

| | | |
|--------------|--|-----------------------------------|
| v_j | $\frac{\partial v_j}{\partial x_i}$ | $\frac{\partial z}{\partial v_j}$ |
| \mathbf{v} | $\frac{\partial \mathbf{v}}{\partial x_i}$ | ∇u |

الگوریتم پس انتشار خطا

Backpropagation



Compute partial derivatives of the loss

- $\frac{\partial l(\mathbf{f}(\mathbf{x}), y)}{\partial \mathbf{f}(\mathbf{x})_i} = \frac{\partial -\log \mathbf{f}(\mathbf{x})_y}{\partial \mathbf{f}(\mathbf{x})_i} = \frac{-1_{y=i}}{\mathbf{f}(\mathbf{x})_y} = \frac{\partial l}{\partial \mathbf{f}(\mathbf{x})_i}$
- $\frac{\partial l}{\partial \mathbf{z}^o(\mathbf{x})_i} = ?$

الگوریتم پس انتشار خطا

$$\frac{\partial l}{\partial \mathbf{z}^o(\mathbf{x})_i} = \sum_j \frac{\partial l}{\partial \mathbf{f}(\mathbf{x})_j} \frac{\partial \mathbf{f}(\mathbf{x})_j}{\partial \mathbf{z}^o(\mathbf{x})_i}$$

Chain rule!

$$\frac{\partial l}{\partial \mathbf{f}(\mathbf{x})_i} = \frac{-1_{y=i}}{\mathbf{f}(\mathbf{x})_y}$$

$$= \sum_j \frac{-1_{y=j}}{\mathbf{f}(\mathbf{x})_y} \frac{\partial \text{softmax}(\mathbf{z}^o(\mathbf{x}))_j}{\partial \mathbf{z}^o(\mathbf{x})_i}$$

$$\mathbf{f}(\mathbf{x}) = \text{softmax}(\mathbf{z}^o(\mathbf{x}))$$


$$= -\frac{1}{\mathbf{f}(\mathbf{x})_y} \frac{\partial \text{softmax}(\mathbf{z}^o(\mathbf{x}))_y}{\partial \mathbf{z}^o(\mathbf{x})_i}$$

$$= \begin{cases} -\frac{1}{\mathbf{f}(\mathbf{x})_y} \text{softmax}(\mathbf{z}^o(\mathbf{x}))_y (1 - \text{softmax}(\mathbf{z}^o(\mathbf{x}))_y) & \text{if } i = y \\ \frac{1}{\mathbf{f}(\mathbf{x})_y} \text{softmax}(\mathbf{z}^o(\mathbf{x}))_y \text{softmax}(\mathbf{z}^o(\mathbf{x}))_i & \text{if } i \neq y \end{cases}$$

$$= \begin{cases} -1 + \mathbf{f}(\mathbf{x})_y & \text{if } i = y \\ \mathbf{f}(\mathbf{x})_i & \text{if } i \neq y \end{cases}$$


$$\nabla_{\mathbf{z}^o(\mathbf{x})} l(\mathbf{f}(\mathbf{x}), y) = \mathbf{f}(\mathbf{x}) - \mathbf{e}(y)$$

$\mathbf{e}(y)$: one-hot encoding of y



الگوریتم پس انتشار خطا

Backpropagation




Gradients

- $\nabla_{\mathbf{z}^o(\mathbf{x})} l = \mathbf{f}(\mathbf{x}) - \mathbf{e}(y)$
- $\nabla_{\mathbf{b}^o} l = \mathbf{f}(\mathbf{x}) - \mathbf{e}(y)$

because $\mathbf{z}^o(\mathbf{x}) = \mathbf{W}^o \mathbf{h}(\mathbf{x}) + \mathbf{b}^o$ and then $\frac{\partial \mathbf{z}^o(\mathbf{x})_i}{\partial \mathbf{b}_j^o} = 1_{i=j}$

الگوریتم پس انتشار خطا

Backpropagation



Partial derivatives related to \mathbf{W}^o

- $$\frac{\partial l}{\partial W_{i,j}^o} = \sum_k \frac{\partial l}{\partial \mathbf{z}^o(\mathbf{x})_k} \frac{\partial \mathbf{z}^o(\mathbf{x})_k}{\partial W_{i,j}^o}$$
- $$\nabla_{\mathbf{W}^o} l = (\mathbf{f}(\mathbf{x}) - \mathbf{e}(y)) \cdot \mathbf{h}(\mathbf{x})^\top$$

الگوریتم پس انتشار خطا

Backprop gradients

Compute activation gradients

- $\nabla_{z^o(\mathbf{x})} l = \mathbf{f}(\mathbf{x}) - \mathbf{e}(y)$

Compute layer params gradients

- $\nabla_{\mathbf{W}^o} l = \nabla_{z^o(\mathbf{x})} l \cdot \mathbf{h}(\mathbf{x})^\top$
- $\nabla_{\mathbf{b}^o} l = \nabla_{z^o(\mathbf{x})} l$

Compute prev layer activation gradients

- $\nabla_{\mathbf{h}(\mathbf{x})} l = \mathbf{W}^{o\top} \nabla_{z^o(\mathbf{x})} l$
- $\nabla_{z^h(\mathbf{x})} l = \nabla_{\mathbf{h}(\mathbf{x})} l \odot \sigma'(z^h(\mathbf{x}))$

شبکه های عصبی:

توابع اتلاف، مقداردهی اولیه، ترفندهای

یادگیری

توابع اتلاف

Discrete output (classification)

- Binary classification: $y \in [0, 1]$
 - $Y|X = \mathbf{x} \sim \text{Bernoulli}(b = f(\mathbf{x}; \theta))$
 - output function: $\text{logistic}(x) = \frac{1}{1+e^{-x}}$
 - loss function: binary cross-entropy
- Multiclass classification: $y \in [0, K - 1]$
 - $Y|X = \mathbf{x} \sim \text{Multinoulli}(\mathbf{p} = \mathbf{f}(\mathbf{x}; \theta))$
 - output function: softmax
 - loss function: categorical cross-entropy

توابع اتلاف

Continuous output (regression)

- Continuous output: $\mathbf{y} \in \mathbb{R}^n$
 - $Y|X = \mathbf{x} \sim \mathcal{N}(\mu = \mathbf{f}(\mathbf{x}; \theta), \sigma^2 \mathbf{I})$
 - output function: Identity
 - loss function: square loss
- Heteroschedastic if $\mathbf{f}(\mathbf{x}; \theta)$ predicts both μ and σ^2
- Mixture Density Network (multimodal output)
 - $Y|X = \mathbf{x} \sim GMM_{\mathbf{x}}$
 - $\mathbf{f}(\mathbf{x}; \theta)$ predicts all the parameters: the means, covariance matrices and mixture weights

مقداردهی اولیه، نرمال سازی

Initialization and normalization

- Input data should be normalized to have approx. same range:
 - standardization or quantile normalization
- Initializing W^h and W^o :
 - Zero is a saddle point: no gradient, no learning
 - Constant init: hidden units collapse by symmetry
 - Solution: random init, ex: $w \sim \mathcal{N}(0, 0.01)$
 - Better inits: Xavier Glorot and Kaming He & orthogonal
- Biases can (should) be initialized to zero

نرخ یادگیری

SGD learning rate

- Very sensitive:
 - Too high \rightarrow early plateau or even divergence
 - Too low \rightarrow slow convergence
 - Try a large value first: $\eta = 0.1$ or even $\eta = 1$
 - Divide by 10 and retry in case of divergence
- Large constant LR prevents final convergence
 - multiply η_t by $\beta < 1$ after each update
 - or monitor validation loss and divide η_t by 2 or 10 when no progress
 - See [ReduceLROnPlateau](#) in Keras

گشتاور و شتاب دهنده SGD Momentum

Accumulate gradients across successive updates:

$$m_t = \gamma m_{t-1} + \eta \nabla_{\theta} L_{B_t}(\theta_{t-1})$$
$$\theta_t = \theta_{t-1} - m_t$$

γ is typically set to 0.9


Larger updates in directions where the gradient sign is constant to accelerate in low curvature areas

Nesterov accelerated gradient

$$m_t = \gamma m_{t-1} + \eta \nabla_{\theta} L_{B_t}(\theta_{t-1} - \gamma m_{t-1})$$
$$\theta_t = \theta_{t-1} - m_t$$


Better at handling changes in gradient direction.

گشتاور - مثال




[Why Momentum Really Works](#)

گشتاور - مثال




[Why Momentum Really Works](#)

گشتاور - مثال



[Why Momentum Really Works](#)

گشتاور - مثال



Why Momentum Really Works

انواع بهینه سازها

Alternative optimizers

- SGD (with Nesterov momentum)
 - Simple to implement
 - Very sensitive to initial value of η
 - Need learning rate scheduling
- Adam: adaptive learning rate scale for each param
 - Global η set to $3e-4$ often works well enough
 - Good default choice of optimizer (often)
- But well-tuned SGD with LR scheduling can generalize better than Adam (with naive l2 reg)...
- Promising stochastic second order methods: [K-FAC](#) and [Shampoo](#) can be used to accelerate training of very large models.

بهینه سازها در اطراف یک نقطه زین اسبی

