

# Package ‘gfpop’

February 12, 2019

**Type** Package

**Title** Graph-constrained Functional Pruning Optimal Partitioning

**Version** 0.1.2

**Author** Vincent Runge

**Maintainer** Vincent Runge <vincent.runge@univ-evry.fr>

**Description** Penalized parametric changepoint detection by functional pruning dynamic programming algorithm. The successive means can be constrained using a graph structure with edge of type null, up, down, std, absInf or absSup. To each edge we can use an additional nonnegative parameter allowing us to force a minimal gap between two successive means. The user can also constraint the inferred means to lie between some minimal and maximal values. Data is modeled by a quadratic cost with possible use of a robust loss, biweight and Huber. In a next version of this package, other parametric losses will be available (L1, Poisson, binomial).

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Imports** Rcpp (>= 0.12.18)

**LinkingTo** Rcpp

**RoxygenNote** 6.1.0

**Suggests** knitr,  
rmarkdown

**VignetteBuilder** knitr

## R topics documented:

dataGenerator . . . . .	2
edge . . . . .	2
gfpop . . . . .	3
graph . . . . .	4
sdDiff . . . . .	4
StartEnd . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

---

dataGenerator	<i>Gaussian data Generator</i>
---------------	--------------------------------

---

**Description**

Generating data with given model = changepoint relative position + means + standard deviation

**Usage**

```
dataGenerator(n, changepoints, means, sigma = 1)
```

**Arguments**

n	number of data to generate
changepoints	vector of position of the changepoint in (0,1] (last element is always 1).
means	vector of means for the consecutive segments (same length as changepoints)
sigma	a positive number = the standard deviation of the data

**Value**

a vector of size n generated by the chosen model

**Examples**

```
dataGenerator(100, c(0.3, 0.6, 1), c(1, 2, 3))
```

---

edge	<i>Edge generation</i>
------	------------------------

---

**Description**

Edge creation for graph

**Usage**

```
edge(state1, state2, type = "null", penalty = 0, parameter = 0)
```

**Arguments**

state1	a nonnegative integer defining the starting state of the edge
state2	a nonnegative integer defining the ending state of the edge
type	a string equal to "null", "std", "up", "down", "absInf" or "absSup"
penalty	a nonnegative number. The penalty associated to this state transition
parameter	a nonnegative number to constraint the size of the gap in the change of state

**Value**

a dataframe with five components equal to the five parameters

**Examples**

```
edge(0, 1, "up", 10, 1)
```

---

gfpop	<i>Graph-constrained functional pruning optimal partitioning</i>
-------	--

---

**Description**

Graph-constrained functional pruning optimal partitionning

**Usage**

```
gfpop(vectData = c(0), vectWeight = c(0), mygraph, type = "gauss",
      K = Inf, a = 0, min = -Inf, max = Inf)
```

**Arguments**

vectData	vector of data to segment
vectWeight	vector of weights (positive numbers) same size as vectData
mygraph	dataframe of class graph to constraint the changepoint dynamic programming algorithm
type	a string defining the type of cost to use. "gauss", "poisson" or "binomial"
K	a positive number. Threshold for the Biweight robust loss
a	a positive number. Slope for the Huber robust loss
min	minimal bound for the infered means
max	maximal bound for the infered means

**Value**

a gfpop object = (changepoints, states, forced, means). 'changepoints' is the vector of changepoints (we give the last element of each segment). 'states' is the vector giving the state of each segment 'forced' is the vector specifying whether the constraints of the graph are active (=1) or not (=0) 'means' is the vector of successive means of each segment

---

graph	<i>Graph generation</i>
-------	-------------------------

---

**Description**

Graph creation

**Usage**

```
graph(..., penalty = 0, type = "empty")
```

**Arguments**

- ... This is a list of edges defined by functions edge and StartEnd
- penalty a nonnegative number equals to the common penalty to use for all edges
- type a string equal to "std", "isotonic", "updown", "infsup". to build a predefined classic graph

**Value**

a dataframe with edges in rows (columns are named "state1", "state2", "type", "penalty", "parameter") with additional "graph" class.

**Examples**

```
UpDownGraph <- graph(penalty = 10, type = "updown")
MyGraph <- graph(edge(0,0), edge(1,1), edge(0,1,"up",10), edge(1,0,"down",0), StartEnd(0,0))
```

---

sdDiff	<i>sdDiff</i>
--------	---------------

---

**Description**

Estimation of the standard deviation

**Usage**

```
sdDiff(x, method = "HALL")
```

**Arguments**

- x vector of datapoint
- method Three available methods: "HALL", "MAD" and "SD"

**Value**

a value equal to the estimated standard deviation

**Examples**

```
data <- dataGenerator(100, c(0.3, 0.6, 1), c(1, 2, 3), 2)
sdDiff(data)
```

---

**StartEnd***Constraint starting and ending states to a graph*

---

**Description**

Adding constraints on the starting and ending states to a graph

**Usage**

```
StartEnd(start = -1, end = -1)
```

**Arguments**

start	a nonnegative integer. The first vertex in the changepoint inference
end	a nonnegative integer. The end vertex in the changepoint inference

**Value**

a dataframe with five components (as for edge) with only state1 and type = start or end defined.

**Examples**

```
StartEnd(start = 0, end = 1)
```

# Index

dataGenerator, [2](#)

edge, [2](#)

gfpop, [3](#)

graph, [4](#)

sdDiff, [4](#)

StartEnd, [5](#)