Запустим help и man, чтобы узнать как проверить доступность сервера.

```
┌──(kali㉿kali)-[~]
└─$ ping --help
ping: invalid option -- '-'

Usage
  ping [options] <destination>

Options:
  <destination>      DNS name or IP address
  -3                 RTT precision (do not round up the result time)
  -a                 use audible ping
  -A                 use adaptive ping
  -B                 sticky source address
  -c <count>         stop after <count> replies
  -C                 call connect() syscall on socket creation
  -D                 print timestamps
  -d                 use SO_DEBUG socket option
  -e <identifier>    define identifier for ping session, default is random for
                     SOCK_RAW and kernel defined for SOCK_DGRAM
                     Imply using SOCK_RAW (for IPv4 only for identifier 0)
  -f                 flood ping
  -h                 print help and exit
  -H                 force reverse DNS name resolution (useful for numeric
                     destinations or for -f), override -n
  -I <interface>     either interface name or address
  -i <interval>      seconds between sending each packet
  -L                 suppress loopback of multicast packets
  -l <preload>       send <preload> number of packages while waiting replies
```

```
PING(8)                                iputils                                PING(8)

NAME
       ping - send ICMP ECHO_REQUEST to network hosts

SYNOPSIS

       ping [-aAbBdCDfhHLnOqrRUvV346] [-c count] [-e identifier] [-F flowlabel] [-i interval] [-I interface] [-l preload] [-m mark] [-M pmtudisc_option]
            [-N nodeinfo_option] [-w deadline] [-W timeout] [-p pattern] [-Q tos] [-s packetsize] [-S sndbuf] [-t ttl] [-T timestamp option] [hop ... ]
            {destination}

DESCRIPTION
       ping uses the ICMP protocol's mandatory ECHO_REQUEST datagram to elicit an ICMP ECHO_RESPONSE from a host or gateway. ECHO_REQUEST datagrams
       (“pings”) have an IP and ICMP header, followed by a struct timeval and then an arbitrary number of “pad” bytes used to fill out the packet.

       ping works with both IPv4 and IPv6. Using only one of them explicitly can be enforced by specifying -4 or -6.

       ping can also send IPv6 Node Information Queries (RFC4620). Intermediate hops may not be allowed, because IPv6 source routing was deprecated
       (RFC5095).

OPTIONS
       -3
           RTT precision (do not round up the result time).

       -4
           Use IPv4 only.

       -6
           Use IPv6 only.

       -a
           Audible ping.

       -A
           Adaptive ping. Interpacket interval adapts to round-trip time, so that effectively not more than one (or more, if preload is set) unanswered
           probe is present in the network. The default interval is 2 ms, for more info see option -i. On networks with low RTT this mode is essentially
 Manual page ping(8) line 1 (press h for help or q to quit)
```

Для проверки доступности сервера можно отправить несколько пакетов. Например отправим пакеты на google.com, чтобы понять подключены ли мы к интернету.

```
┌──(kali㉿kali)-[~]
└─$ ping -c 4 google.com
PING google.com (209.85.233.139) 56(84) bytes of data.
64 bytes from lr-in-f139.1e100.net (209.85.233.139): icmp_seq=1 ttl=104 time=68.0 ms
64 bytes from lr-in-f139.1e100.net (209.85.233.139): icmp_seq=2 ttl=104 time=66.3 ms
64 bytes from lr-in-f139.1e100.net (209.85.233.139): icmp_seq=3 ttl=104 time=65.9 ms
64 bytes from lr-in-f139.1e100.net (209.85.233.139): icmp_seq=4 ttl=104 time=66.2 ms

--- google.com ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3009ms
rtt min/avg/max/mdev = 65.897/66.608/68.044/0.842 ms
```

Пакеты доходят, а значит к интернету мы подключены. При этом надо учитывать, что у нас относительно сильные колебания, так что возможно маршрутизатор перегружен.

Теперь запустим help и man для useradd.

```
┌──(kali㉿kali)-[~]
└─$ useradd --help
Usage: useradd [options] LOGIN
       useradd -D
       useradd -D [options]

Options:
      --badname                 do not check for bad names (DEPRECATED)
  -b, --base-dir BASE_DIR       base directory for the home directory of the
                                new account
      --btrfs-subvolume-home    use BTRFS subvolume for home directory
  -c, --comment COMMENT         GECOS field of the new account
  -d, --home-dir HOME_DIR       home directory of the new account
  -D, --defaults                print or change default useradd configuration
  -e, --expiredate EXPIRE_DATE  expiration date of the new account
  -f, --inactive INACTIVE       password inactivity period of the new account
  -F, --add-subids-for-system   add entries to sub[ud]id even when adding a system user
  -g, --gid GROUP               name or ID of the primary group of the new
                                account
  -G, --groups GROUPS           list of supplementary groups of the new
                                account
  -h, --help                    display this help message and exit
  -k, --skel SKEL_DIR           use this alternative skeleton directory
  -K, --key KEY=VALUE           override /etc/login.defs defaults
  -m, --create-home             create the user's home directory
  -M, --no-create-home          do not create the user's home directory
  -N, --no-user-group           do not create a group with the same name as
                                the user
  -o, --non-unique              allow to create users with duplicate
                                (non-unique) UID
  -p, --password PASSWORD       encrypted password of the new account
  -r, --system                  create a system account
  -R, --root CHROOT_DIR         directory to chroot into
  -P, --prefix PREFIX_DIR       prefix directory where are located the /etc/* files
```

```
USERADD(8)                          System Management Commands                          USERADD(8)

NAME
       useradd - create a new user or update default new user information

SYNOPSIS

       useradd [options] LOGIN

       useradd -D

       useradd -D [options]

DESCRIPTION
       useradd is a low level utility for adding users. On Debian, administrators should usually use adduser(8) instead.

       When invoked without the -D option, the useradd command creates a new user account using the values specified on the command line plus the
       default values from the system. Depending on command line options, the useradd command will update system files and may also create the new
       user's home directory and copy initial files.

       By default, a group will also be created for the new user (see -g, -N, -U, and USERGROUPS_ENAB).

OPTIONS
       The options which apply to the useradd command are:

       --badname
           Allow names that do not conform to standards.

       -b, --base-dir BASE_DIR
           The default base directory for the system if -d HOME_DIR is not specified.  BASE_DIR is concatenated with the account name to define the home
           directory.

           If this option is not specified, useradd will use the base directory specified by the HOME variable in /etc/default/useradd, or /home by
           default.

       -c, --comment COMMENT
 Manual page useradd(8) line 1 (press h for help or q to quit)
```

Создадим нового пользователя.

```
┌──(kali㉿kali)-[~]
└─$ sudo useradd user111

┌──(kali㉿kali)-[~]
└─$
```

Теперь посмотрим help и man для chmod.

```
┌──(kali㉿kali)-[~]
└─$ chmod --help
Usage: chmod [OPTION]... MODE[,MODE]... FILE...
  or:  chmod [OPTION]... OCTAL-MODE FILE...
  or:  chmod [OPTION]... --reference=RFILE FILE...
Change the mode of each FILE to MODE.
With --reference, change the mode of each FILE to that of RFILE.

  -c, --changes          like verbose but report only when a change is made
  -f, --silent, --quiet  suppress most error messages
  -v, --verbose          output a diagnostic for every file processed
      --dereference      affect the referent of each symbolic link,
                           rather than the symbolic link itself
  -h, --no-dereference   affect each symbolic link, rather than the referent
      --no-preserve-root  do not treat '/' specially (the default)
      --preserve-root    fail to operate recursively on '/'
      --reference=RFILE  use RFILE's mode instead of specifying MODE values.
                         RFILE is always dereferenced if a symbolic link.
  -R, --recursive        change files and directories recursively

The following options modify how a hierarchy is traversed when the -R
option is also specified.  If more than one is specified, only the final
one takes effect. -H is the default.

  -H                     if a command line argument is a symbolic link
                         to a directory, traverse it
  -L                     traverse every symbolic link to a directory
                         encountered
  -P                     do not traverse any symbolic links

      --help        display this help and exit
      --version     output version information and exit

Each MODE is of the form '[ugoa]*([-+=]([rwxXst]*|[ugo]))+|[-+=][0-7]+'.
```

```
CHMOD(1)                                User Commands                                CHMOD(1)

NAME
       chmod - change file mode bits

SYNOPSIS
       chmod [OPTION]... MODE[,MODE]... FILE...
       chmod [OPTION]... OCTAL-MODE FILE...
       chmod [OPTION]... --reference=RFILE FILE...

DESCRIPTION
       This  manual page documents the GNU version of chmod.  chmod changes the file mode bits of each given file according to mode, which can be either
       a symbolic representation of changes to make, or an octal number representing the bit pattern for the new mode bits.

       The format of a symbolic mode is [ugoa...][[-+=][perms...]...], where perms is either zero or more letters from the set rwxXst, or a single  let-
       ter from the set ugo.  Multiple symbolic modes can be given, separated by commas.

       A  combination  of the letters ugoa controls which users' access to the file will be changed: the user who owns it (u), other users in the file's
       group (g), other users not in the file's group (o), or all users (a).  If none of these are given, the effect is as if (a) were given,  but  bits
       that are set in the umask are not affected.

       The  operator  +  causes  the selected file mode bits to be added to the existing file mode bits of each file; - causes them to be removed; and =
       causes them to be added and causes unmentioned bits to be removed except that a directory's unmentioned set user and group ID bits  are  not  af-
       fected.

       The  letters  rwxXst  select  file mode bits for the affected users: read (r), write (w), execute (or search for directories) (x), execute/search
       only if the file is a directory or already has execute permission for some user (X), set user or group ID on execution (s),  restricted  deletion
       flag  or sticky bit (t).  Instead of one or more of these letters, you can specify exactly one of the letters ugo: the permissions granted to the
       user who owns the file (u), the permissions granted to other users who are members of the file's group (g), and the permissions granted to  users
       that are in neither of the two preceding categories (o).

       A  numeric  mode is from one to four octal digits (0-7), derived by adding up the bits with values 4, 2, and 1.  Omitted digits are assumed to be
       leading zeros.  The first digit selects the set user ID (4) and set group ID (2) and restricted deletion or sticky (1)  attributes.  The  second
       digit  selects permissions for the user who owns the file: read (4), write (2), and execute (1); the third selects permissions for other users in
       the file's group, with the same values; and the fourth for other users not in the file's group, with the same values.

 Manual page chmod(1) line 1 (press h for help or q to quit)
```

Создадим новую директорию, посмотрим права на нее, а после изменим их.

```
┌──(kali㉿kali)-[~]
└─$ mkdir new_papka
```

```
┌──(kali㉿kali)-[~]
└─$ ls -l
total 59336
drwxr-xr-x 2 kali kali     4096 Jun 23 07:10 Desktop
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Documents
drwxr-xr-x 5 kali kali     4096 Jul  3 12:12 Downloads
-rw-rw-r-- 1 kali kali       65 Jul  3 08:12 hash.txt
drwxr-xr-x 9 root root     4096 Jun 22 13:25 impacket
-rw-rw-r-- 1 kali kali 60558933 Jun 21 05:51 lsass.DMP
-rw-rw-r-- 1 kali kali     3261 Jul 17 11:24 man.html
-rw-rw-r-- 1 kali kali    69272 Jul 17 11:24 man.print.1
-rw-rw-r-- 1 kali kali    69269 Jul 17 11:24 man.print.2
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Music
drwxrwxr-x 4 kali kali     4096 Jul  3 11:17 neofetch
drwxrwxr-x 2 kali kali     4096 Jul 17 12:00 new_papka
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Pictures
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Public
drwxrwxr-x 7 kali kali     4096 Jun 21 05:59 pypykatz
drwxrwxr-x 5 kali kali     4096 Jun 23 00:18 temp
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Templates
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Videos
```

```
┌──(kali㉿kali)-[~]
└─$ chmod 755 new_papka

┌──(kali㉿kali)-[~]
└─$ ls -l
total 59336
drwxr-xr-x 2 kali kali     4096 Jun 23 07:10 Desktop
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Documents
drwxr-xr-x 5 kali kali     4096 Jul  3 12:12 Downloads
-rw-rw-r-- 1 kali kali       65 Jul  3 08:12 hash.txt
drwxr-xr-x 9 root root     4096 Jun 22 13:25 impacket
-rw-rw-r-- 1 kali kali 60558933 Jun 21 05:51 lsass.DMP
-rw-rw-r-- 1 kali kali     3261 Jul 17 11:24 man.html
-rw-rw-r-- 1 kali kali    69272 Jul 17 11:24 man.print.1
-rw-rw-r-- 1 kali kali    69269 Jul 17 11:24 man.print.2
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Music
drwxrwxr-x 4 kali kali     4096 Jul  3 11:17 neofetch
drwxr-xr-x 2 kali kali     4096 Jul 17 12:00 new_papka
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Pictures
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Public
drwxrwxr-x 7 kali kali     4096 Jun 21 05:59 pypykatz
drwxrwxr-x 5 kali kali     4096 Jun 23 00:18 temp
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Templates
drwxr-xr-x 2 kali kali     4096 Jun 15 07:05 Videos

┌──(kali㉿kali)-[~]
└─$
```

Далее запустим help и man для команды tar.

```
┌──(kali㉿kali)-[~]
└─$ tar --help
Usage: tar [OPTION ... ] [FILE] ...
GNU 'tar' saves many files together into a single tape or disk archive, and can
restore individual files from the archive.

Examples:
  tar -cf archive.tar foo bar  # Create archive.tar from files foo and bar.
  tar -tvf archive.tar         # List all files in archive.tar verbosely.
  tar -xf archive.tar          # Extract all files from archive.tar.

 Main operation mode:
  -A, --catenate, --concatenate   append tar files to an archive
  -c, --create                    create a new archive
      --delete                    delete from the archive (not on mag tapes!)
  -d, --diff, --compare           find differences between archive and file system
  -r, --append                    append files to the end of an archive
      --test-label                test the archive volume label and exit
  -t, --list                      list the contents of an archive
  -u, --update                    only append files newer than copy in archive
  -x, --extract, --get            extract files from an archive

 Operation modifiers:

'
```

```
TAR(1)                          GNU TAR Manual                          TAR(1)

NAME
       tar - an archiving utility

SYNOPSIS
   Traditional usage
       tar {A|c|d|r|t|u|x}[GnSkUWOmpsMBiajJzZhPlRvwo] [ARG ... ]

   UNIX-style usage
       tar -A [OPTIONS] -f ARCHIVE ARCHIVE ...

       tar -c [-f ARCHIVE] [OPTIONS] [FILE ... ]

       tar -d [-f ARCHIVE] [OPTIONS] [FILE ... ]

       tar -r [-f ARCHIVE] [OPTIONS] [FILE ... ]

       tar -t [-f ARCHIVE] [OPTIONS] [MEMBER ... ]

       tar -u [-f ARCHIVE] [OPTIONS] [FILE ... ]

       tar -x [-f ARCHIVE] [OPTIONS] [MEMBER ... ]

   GNU-style usage
       tar {--catenate|--concatenate} [OPTIONS] --file ARCHIVE ARCHIVE ...

       tar --create [--file ARCHIVE] [OPTIONS] [FILE ... ]

       tar {--diff|--compare} [--file ARCHIVE] [OPTIONS] [FILE ... ]

       tar --delete [--file ARCHIVE] [OPTIONS] [MEMBER ... ]

       tar --append [--file ARCHIVE] [OPTIONS] [FILE ... ]
```

Создадим архив.

```
┌──(kali㉿kali)-[~]
└─$ tar -cvf archive_test.tar new_papka
new_papka/

┌──(kali㉿kali)-[~]
└─$ ls
archive_test.tar  Documents  hash.txt  lsass.DM
Desktop           Downloads  impacket  man.html

┌──(kali㉿kali)-[~]
└─$
```

Теперь извлечем файл из архива.

```
┌──(kali㉿kali)-[~]
└─$ tar -xvf archive_test.tar
new_papka/

┌──(kali㉿kali)-[~]
```

По сути help и man могут быть использованы в любой ситуации, когда условный работник или пользователь не знают как работать с какой-то утилитой, будь то ip, ifconfig, nmap или ls.