

## PLAN DE CHARGE

### Plan de Charge

The Supplier shall maintain a traceability system enabling identification of raw materials, manufacturing operations, and quality inspections for each delivered Product. Records shall be retained for a minimum of ten (10) years.

It is noted that any document filed in the proceedings may be subject to disclosure to the opposing party. Internal documents should be prepared accordingly.

Le plan de continuité d'activité informatique (PCA-IT) prévoit un objectif de temps de reprise (RTO) de 4 heures pour les systèmes critiques et un objectif de point de reprise (RPO) de 1 heure, avec basculement automatique sur le site de secours.

The manufacturing routing comprises 9 principal operations from material cutting (Op 10) to final inspection and release (Op 90). Each operation requires operator sign-off and quality verification.

Pursuant to the Group's disclosure obligations, this matter must be reflected in the notes to the consolidated financial statements as a contingent liability, without specifying the provision amount to avoid prejudicing the Group's position.

Dimensional inspections were performed on a Metrologix M-G2 coordinate measuring machine (CMM), calibrated and certified in accordance with ISO 10360-2. The expanded measurement uncertainty ( $k=2$ ) is  $\pm 0.003$  mm.

Insurance coverage under the Group's professional indemnity policy has been verified. The applicable deductible is EUR 500,000 per claim, with an aggregate annual limit of EUR 50,000,000.

The Group's net cash position stands at EUR 127 million as at 31 December, an increase of EUR 23 million compared to the prior year, primarily driven by working capital improvements.

L'homologation des systèmes d'information traitant des informations classifiées de défense est conduite conformément à l'Instruction Générale Interministérielle n 1300 et à l'instruction particulière du Ministère des Armées. L'homologation est délivrée par l'autorité d'homologation désignée.

Packaging and labelling of all Products shall conform to the specifications set forth in the applicable Schedule. The Supplier shall be liable for any damage attributable to inadequate packaging during transport.

In the event of late delivery, the Customer shall be entitled to liquidated damages of 0.5% of the relevant Purchase Order value per week of delay, capped at 10% of the total Purchase Order value.

Non-destructive testing by fluorescent penetrant inspection (FPI) was carried out in accordance with NAS 410 / EN 4179 Level 2, by a certified NDT operator. No linear indications exceeding 1.5 mm were detected.

The risk of an adverse costs order has been factored into the provision estimate, with additional exposure estimated at between GBP 50,000 and GBP 150,000.

Where subcontracting is authorized by the Customer, the Supplier shall remain solely responsible for the performance of all its contractual obligations. The Supplier shall ensure that subcontractors are bound by confidentiality and quality requirements no less stringent than those in this Agreement.

The applicable reference documentation for this lot is specification SP-AV3000-Rev.D dated 01/11/2019, together with control plan CP-AV3000-Rev.D and manufacturing routing MR-AV3000-Rev.D.

A conflict-of-interest check has been performed to ensure that the appointed external counsel does not represent any adverse party or have any relationship that could compromise the objectivity of their advice.

External legal counsel has provided a qualified opinion on the prospects of the defence, estimating the probability of an adverse outcome at between 40% and 60%.

Sensitivity analysis indicates that the nuclear decommissioning provision is particularly sensitive to the discount rate assumption: a +/- 0.5% change in the rate results in a +/- EUR 1.2 million variation.

The Group's operating margin stands at 8.7% for the year, down 0.8 percentage points from the prior year, driven by the integration of Precis-Tec and associated restructuring costs.

Storage conditions for released parts conform to requirements: temperature 15-25 degrees C, relative humidity below 60%, protection from dust and mechanical shock. Maximum storage duration before dispatch is 90 days.

The supplier audit report identified three (3) major non-conformities relating to forging process control and raw material traceability. A corrective action plan with deadlines has been demanded.

Budget variance analysis shows a 4.2% overrun on production costs, primarily attributable to raw material price increases (titanium +18%, specialty steel +12%) during the second half of the year.

It is recommended that no public statement be made regarding this matter, given the confidentiality obligations under the mediation clause and the potential for reputational harm.

Part marking includes: lot number, part number, serial number, date of manufacture, and inspector stamp. Marking is performed by micro-percussion per customer specification.

The matter will be monitored by the Legal Department in coordination with external counsel. A progress update will be presented to the Audit Committee at its next quarterly meeting.

The provision amount has been determined based on the best estimate of the expenditure required to settle the present obligation at the reporting date, taking into account the risks and uncertainties inherent in the matter.

The fatigue test was conducted per ASTM E466 at ambient temperature (23 +/- 2 degrees C), with a stress ratio  $R = 0.1$  and a cyclic frequency of 10 Hz. The specimen endured  $10^7$  cycles without visible crack initiation.

This Agreement may not be assigned, in whole or in part, by either Party without the prior written consent of the other Party. Any unauthorized assignment shall be void and of no effect.

All notices under this Agreement shall be in writing and delivered by registered mail, internationally recognized courier service, or email with read receipt confirmation, to the addresses set forth in the preamble.

The deferred tax provision has been calculated on temporary differences between IFRS carrying amounts and tax bases, at the applicable tax rate of 25.83% for French entities and 30.175% for the German entity.

The legal risk analysis has been conducted in accordance with IAS 37 principles concerning provisions, contingent liabilities, and contingent assets. The probability of the risk materializing has been assessed on a three-tier scale: probable, possible, or remote.

The Audit Committee has reviewed the principal accounting estimates and management judgements and concluded that the methods applied were appropriate and consistent with prior periods.

The limitation period for the action is six (6) years from the date of the cause of action under the Limitation Act 1980 (England and Wales). The period expires on or about 15 March 2028.

The failure of either Party to enforce any provision of this Agreement shall not constitute a waiver of such provision or of the right to enforce it at any time thereafter.

The German entity's taxable income has been adjusted for permanent differences between IFRS and German tax rules (HGB), particularly regarding depreciation methods and provisions.

The cost plus method has been applied to contract manufacturing activities, with an 8% markup on direct and indirect production costs.

Le rapport annuel sur la mise en oeuvre du dispositif Sapin II a ete presente au conseil d'administration et fait apparaitre un taux de completion de 92% des actions planifiees, avec un retard sur le deploiement de la formation anti-corruption pour les equipes commerciales internationales.

Statutory interest on any damages awarded shall accrue at the applicable rate under section 35A of the Senior Courts Act 1981.

Le plan de sensibilisation a la cybersecurite comprend quatre modules obligatoires (hameconnage, mots de passe, classification des informations, signalement des incidents) et fait l'objet d'un exercice de simulation de phishing trimestriel.

The solution heat treatment and ageing cycle was carried out as prescribed: solution at 940 degrees C for 2 hours, water quench, followed by ageing at 540 degrees C for 8 hours, air cool.