

visit<R>: Explicit Return Type for visit

Document #: D0655R1
Date: 2018-07-09
Project: Programming Language C++
Library Evolution Group
Reply-to: Michael Park
<mcypark@gmail.com>
Agustín Bergé
<agustinberge@gmail.com>

1 Introduction

This paper proposes to allow visiting `variants` with an explicitly specified return type.

2 Motivation and Scope

Variant visitation requires invocation of all combinations of alternatives to result in the same type, such type is deduced as the visitation return type. It is sometimes desirable to explicitly specify a return type to which all the invocations are implicitly convertible to, as if by *INVOKE*<R> rather than *INVOKE*:

```
struct process {  
    template <typename I>  
    auto operator()(I i) -> O<I> { /* ... */ };  
};  
  
std::variant<I1, I2> input = /* ... */;  
  
// mapping from a `variant` of inputs to a `variant` of results:  
auto output = std::visit<std::variant<O<I1>, O<I2>>>(process{}, input);  
  
// coercing different results to a common type:  
auto result = std::visit<std::common_type_t<O<I1>, O<I2>>>(process{}, input);  
  
// visiting a `variant` for the side-effects, discarding results:  
std::visit<void>(process{}, input);
```

In all of the above cases the return type deduction would have failed, as each invocation yields a different type for each alternative.

3 Impact on the Standard

This proposal is a pure library extension.

4 Proposed Wording

Add to §23.7.2 [variant.syn] of N4750 [1]:

```
// 23.7.7, visitation
template <class Visitor, class... Variants>
    constexpr see below visit(Visitor&&, Variants&&...);
+ template <class R, class Visitor, class... Variants>
+     constexpr R visit(Visitor&&, Variants&&...);
```

Add to §23.7.7 [variant.visit] of N4750 [1]:

```
template <class Visitor, class... Variants>
    constexpr see below visit(Visitor&& vis, Variants&&... vars);
+ template <class R, class Visitor, class... Variants>
+     constexpr R visit(Visitor&& vis, Variants&&... vars);
```

- ¹ Let n be `sizeof...(Variants)`. Let m be a pack of n values of type `size_t`. Such a pack is called valid if $0 \leq m_i < \text{variant_size_v}<\text{remove_reference_t}<\text{Variants}_i>>$ for all $0 \leq i < n$. For each valid pack m , let $e(m)$ denote the expression:

`INVOKE(std::forward<Visitor>(vis), get<m>(std::forward<Variants>(vars))...)` // *see 23.14.3*

for the first form and

`INVOKE<R>(std::forward<Visitor>(vis), get<m>(std::forward<Variants>(vars))...)` // *see 23.14.3*

for the second form.

5 Design Decisions

There is a corner case for which the new overload could clash with the existing overload. A call to `std::visit<Result>` actually performs overload resolution with the following two candidates:

```
template <class Visitor, class... Variants>
constexpr decltype(auto) visit(Visitor&&, Variants&&...);

template <class R, class Visitor, class... Variants>
constexpr R visit(Visitor&&, Variants&&...);
```

The template instantiation via `std::visit<Result>` replaces `Visitor` with `Result` for the first overload, `R` with `Result` for the second, and we end up with the following:

```
template <class... Variants>
constexpr decltype(auto) visit(Result&&, Variants&&...);

template <class Visitor, class... Variants>
constexpr Result visit(Visitor&&, Variants&&...);
```

This results in an ambiguity if `Result&&` happens to be the same type as `Visitor&&`. For example, a call to `std::visit<Vis>(Vis{})`; would be ambiguous since `Result&&` and `Visitor&&` are both `Vis&&`.

In general, we would first need a self-returning visitor, then an invocation to `std::visit` with the same type **and** value category specified for the return type **and** the visitor argument.

We claim that this problem is not worth solving considering the rarity of such a use case and the complexity of a potential solution.

Finally, note that this is not a new problem since `bind` already uses the same pattern to support `bind<R>`:

```
template <class F, class... BoundArgs>
    unspecified bind(F&&, BoundArgs&&...);
template <class R, class F, class... BoundArgs>
    unspecified bind(F&&, BoundArgs&&...);
```

6 Implementation Experience

- `MPark.Variant` implements `visit<R>` as proposed in the `visit-r` branch.
- `Eggs.Variant` has provided an implementation of `visit<R>` as `apply<R>` since 2014, and also handles the corner case mentioned in [Design Decisions](#).

7 Future Work

There are other similar facilities that currently use *INVOKE*, and do not provide an accompanying overload that uses *INVOKE<R>*. Some examples are `std::invoke`, `std::apply`, and `std::async`.

There may be room for a paper with clear guidelines as to if/when such facilities should have an accompanying overload.

References

- [1] 2018. Working Draft, Standard for Programming Language C++. *N4750*. Retrieved from <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2018/n4750.pdf>