

Self-RAG University Course Advisory Agent

Final Exam Report

AI407L — Spring 2026
Part B Report

Course: AI407L — Final Exam (Spring 2026)

Institution: XYZ National University

Date: May 10, 2026

Contents

1 Introduction **4**
- 1.1 What Makes This Self-RAG? . . . 4
- 1.2 Technology Stack . . . 5

2 Objectives **6**

3 Knowledge Base Construction **7**
- 3.1 Documents Used . . . 7
- 3.2 PDF Processing . . . 7
- 3.3 Chunking Strategy . . . 7
  - 3.3.1 Why This Chunking Strategy? . . . 8
- 3.4 Metadata Enrichment . . . 8
- 3.5 Vector Database Indexing . . . 8

4 System Architecture **10**
- 4.1 Overall Self-RAG Pipeline . . . 10
- 4.2 Pipeline Components . . . 11
  - 4.2.1 Decision Node: Retrieval Necessity . . . 11
  - 4.2.2 Retrieval Node . . . 12
  - 4.2.3 Relevance Grading Node . . . 12
  - 4.2.4 Web Search Fallback . . . 12
  - 4.2.5 Generation Node . . . 12
  - 4.2.6 Hallucination Check Node . . . 12

5 LangGraph Workflow **13**
- 5.1 Graph Implementation . . . 13
- 5.2 Graph Nodes . . . 13
- 5.3 State Variables . . . 13
  - 5.3.1 State Variables Explanation . . . 14

6 Adaptive Retrieval **15**
- 6.1 Goal . . . 15
- 6.2 Example: Greetings . . . 15
  - 6.2.1 Query . . . 15
  - 6.2.2 Decision . . . 15
  - 6.2.3 Reasoning . . . 15
- 6.3 Domain-Specific Queries Requiring Retrieval . . . 16
  - 6.3.1 Example Domain Query . . . 16

7 Relevance Grading **17**
7.1 Overview . . . 17
7.2 Relevance Categories . . . 17
7.3 Practical Example . . . 17
7.3.1 Query . . . 17
7.3.2 Retrieved Documents and Grading . . . 17
7.4 Impact . . . 17

8 Web Search Fallback **19**
8.1 When Web Search Triggers . . . 19
8.2 Search Tools Supported . . . 19
8.3 Example: Out-of-Domain Query . . . 19
8.3.1 Query . . . 19
8.3.2 Expected Behavior . . . 19
8.3.3 Trace . . . 20
8.4 Transparency in Sources . . . 20

9 Hallucination Self-Check **21**
9.1 Purpose . . . 21
9.2 Verification Process . . . 21
9.3 Verification Categories . . . 21
9.4 Retry Mechanism . . . 21
9.4.1 Retry Configuration . . . 22
9.5 Example: Hallucination Detection and Recovery . . . 22
9.5.1 Query . . . 22
9.5.2 Scenario . . . 22
9.5.3 First Generation Attempt . . . 22
9.5.4 Hallucination Check . . . 22
9.5.5 Retry Attempt 1 . . . 22
9.5.6 Hallucination Check . . . 23
9.5.7 Final Response to User . . . 23

10 Tools Implementation **24**
10.1 Tool Architecture . . . 24
10.2 Retrieval Tool . . . 24
10.3 Web Search Tool . . . 25
10.4 Tool Benefits . . . 25

11 Technologies Used **26**
11.1 Technology Stack . . . 26
11.2 Component Details . . . 26
11.2.1 LangGraph . . . 26
11.2.2 ChromaDB . . . 26
11.2.3 HuggingFace Embeddings . . . 27
11.2.4 Ollama . . . 27

12 Evaluation Results **28**
12.1 Test Case 1: Retrieval NOT Needed . . . 28
12.1.1 Query . . . 28
12.1.2 Expected Behavior . . . 28
12.1.3 Actual Execution Trace . . . 28
12.1.4 Final Response . . . 28
12.2 Test Case 2: Retrieval Needed + Relevant Documents . . . 29
12.2.1 Query . . . 29
12.2.2 Expected Behavior . . . 29
12.2.3 Actual Execution Trace . . . 29
12.2.4 Final Response . . . 29
12.3 Test Case 3: Web Search Fallback . . . 30
12.3.1 Query . . . 30
12.3.2 Expected Behavior . . . 30
12.3.3 Actual Execution Trace . . . 30
12.3.4 Final Response . . . 30
12.4 Test Case 4: Hallucination Detection + Retry . . . 31
12.4.1 Query . . . 31
12.4.2 Expected Behavior . . . 31
12.4.3 Actual Execution Trace . . . 31
12.4.4 Final Response . . . 32
12.5 Test Case 5: Creative Scenario . . . 32
12.5.1 Query . . . 32
12.5.2 Expected Behavior . . . 32
12.5.3 Actual Execution Trace . . . 32
12.5.4 Final Response . . . 33

13 Conclusion **34**
13.1 Project Summary . . . 34
13.2 Alignment with Modern RAG Practices . . . 34
13.3 Minimized Failure Modes . . . 34
13.4 Final Assessment . . . 35
13.5 Impact and Applications . . . 35

Chapter 1

Introduction

This project implements a complete **Self-RAG (Self-Reflective Retrieval-Augmented Generation)** pipeline using **LangGraph** for a University Course Advisory System.

The agent is designed for **XYZ National University** and assists students with:

- Course information
- Credit hours
- Prerequisites
- Faculty details
- Attendance rules
- GPA policies
- Withdrawal rules
- Academic calendar
- Fees and university regulations

1.1 What Makes This Self-RAG?

Unlike traditional RAG systems, the Self-RAG architecture introduces **reflection and verification checkpoints** before and after retrieval and generation. The system dynamically decides:

1. Whether retrieval is required
2. Whether retrieved documents are relevant
3. Whether generated answers are grounded in evidence

1.2 Technology Stack

The implementation uses:

- **LangGraph** — Workflow orchestration
- **ChromaDB** — Vector database
- **HuggingFace embeddings** — Semantic representations
- **Ollama LLM** — Local language model
- **DuckDuckGo/Tavily** — Web search integration
- **PyPDF** — Document loading

Chapter 2

Objectives

The major objectives of the project are:

1. Build a university advisory assistant using Self-RAG
2. Implement adaptive retrieval mechanisms
3. Avoid unnecessary retrieval for non-domain queries
4. Filter irrelevant documents using relevance grading
5. Trigger web fallback when knowledge base fails
6. Detect hallucinations in generated responses
7. Regenerate unsupported responses automatically
8. Build a complete LangGraph StateGraph workflow
9. Provide detailed execution traces for transparency

Chapter 3

Knowledge Base Construction

3.1 Documents Used

The following five PDF documents were used as the knowledge base:

Table 3.1: Knowledge Base Documents

Document	Purpose
CS_Department_Catalog.pdf	Computer Science courses
EE_Department_Catalog.pdf	Electrical Engineering courses
BBA_Department_Catalog.pdf	Business Administration courses
University_Academic_Policies.pdf	Policies, GPA, attendance
Faculty_Directory.pdf	Faculty information

3.2 PDF Processing

The PDFs were loaded using the standard document processing pipeline:

Listing 3.1: PDF Loader Configuration

```
from langchain_community.document_loaders import PyPDFLoader

loader = PyPDFLoader(filepath)
documents = loader.load()
```

Each document was parsed page-by-page to extract textual content while preserving structure.

3.3 Chunking Strategy

To preserve semantic meaning and prevent breaking critical academic information:

Listing 3.2: Recursive Character Text Splitter Configuration

```
from langchain.text_splitter import
   RecursiveCharacterTextSplitter

text_splitter = RecursiveCharacterTextSplitter(
    chunk_size=1200,
    chunk_overlap=200
```

```
)

chunks = text_splitter.split_documents(documents)
```

3.3.1 Why This Chunking Strategy?

The chosen parameters ensure that:

- **Complete course descriptions** are preserved within single chunks
- **Full prerequisite sections** remain intact
- **Entire policy rules** are not split across boundaries
- **Faculty information blocks** stay coherent
- **Overlap of 200 characters** provides context continuity

This approach prevents breaking critical academic information across chunks, which could lead to incomplete or misleading retrieval results.

3.4 Metadata Enrichment

Each chunk was enriched with metadata to enable filtering and improved retrieval:

Listing 3.3: Metadata Enrichment Structure

```
chunk_metadata = {
    "department": "Computer Science",
    "document_type": "course_catalog",
    "level": "undergraduate_graduate",
    "source_file": "CS_Department_Catalog.pdf",
    "chunk_index": 0
}
```

Table 3.2: Metadata Fields and Purposes

Metadata Field	Purpose
department	Identifies source department
document_type	Classifies as policy/catalog/faculty
level	Distinguishes undergraduate/graduate
source_file	Links to original PDF
chunk_index	Enables document reconstruction

3.5 Vector Database Indexing

The processed chunks were indexed into ChromaDB using semantic embeddings:

Listing 3.4: ChromaDB Configuration

```
from langchain_community.vectorstores import Chroma
from langchain_community.embeddings import HuggingFaceEmbeddings

embeddings = HuggingFaceEmbeddings(
    model_name="sentence-transformers/all-MiniLM-L6-v2"
)

vectordb = Chroma.from_documents(
    documents=chunks,
    embedding=embeddings,
    persist_directory="./chroma_db"
)
```

Embedding Model: `sentence-transformers/all-MiniLM-L6-v2`
This model provides:


- Semantic understanding of academic text
- Efficient computational footprint
- Strong performance on domain-specific queries
- Compatibility with local deployment

Chapter 4

System Architecture

4.1 Overall Self-RAG Pipeline

The complete system follows this workflow:



4.2 Pipeline Components

4.2.1 Decision Node: Retrieval Necessity

The system first determines whether knowledge base retrieval is necessary. This adaptive approach avoids expensive retrieval operations for:

- Greetings and casual conversation
- General knowledge queries
- System-level requests

4.2.2 Retrieval Node

If retrieval is required, the system queries the vector database with the user's question.

4.2.3 Relevance Grading Node

Each retrieved document is individually evaluated for relevance to the query, filtering out noisy or irrelevant chunks.

4.2.4 Web Search Fallback

If no relevant documents are found, external web search is triggered to provide information outside the knowledge base.

4.2.5 Generation Node

The language model generates an answer based on either:

- Retrieved and filtered documents (KB-based)
- Web search results (web-based fallback)
- General knowledge (for direct responses)

4.2.6 Hallucination Check Node

The generated response is verified to ensure claims are supported by the provided context.

Chapter 5

LangGraph Workflow

5.1 Graph Implementation

The entire pipeline was implemented as a stateful, conditional workflow using LangGraph's StateGraph:

Listing 5.1: LangGraph StateGraph Import

```
from langgraph.graph import StateGraph, END
from typing import TypedDict, List
```

5.2 Graph Nodes

Table 5.1: Graph Nodes and Functions

Node Name	**Function**
decide_retrieval	Determines if retrieval is necessary for the query
retrieve	Fetches relevant documents from vector database
grade_relevance	Evaluates each document for relevance to query
web_search	Performs external web search as fallback
generate	Generates response using LLM
hallucination_check	Validates response against source documents
retry_or_finalize	Handles retry logic or finalizes response

5.3 State Variables

The graph maintains a comprehensive state dictionary:

Listing 5.2: GraphState Type Definition

```
class GraphState(TypedDict):
    question: str
    needs_retrieval: bool
    retrieval_reason: str
    retrieved_docs: str
    relevant_docs: str
    use_web_search: bool
    generated_answer: str
```

```
    hallucination_detected: bool
    retry_count: int
    trace: List[str]
```

5.3.1 State Variables Explanation

`question` The original user query

`needs_retrieval` Boolean flag from decision node

`retrieval_reason` Explanation of why/why not retrieval occurred

`retrieved_docs` Raw documents from vector database

`relevant_docs` Filtered, relevant documents only

`use_web_search` Flag indicating web search was triggered

`generated_answer` The response from the LLM

`hallucination_detected` Boolean from verification step

`retry_count` Number of retries attempted

`trace` Execution trace for transparency

Chapter 6

Adaptive Retrieval

6.1 Goal

The adaptive retrieval mechanism avoids unnecessary retrieval operations for queries that do not require university-specific knowledge. This optimization:

- Reduces latency for non-domain queries
- Saves computational resources
- Improves system responsiveness
- Maintains information accuracy

6.2 Example: Greetings

6.2.1 Query

```
Hello, how are you?
```

6.2.2 Decision

```
NEEDS_RETRIEVAL: NO
```

6.2.3 Reasoning

This query:

- Does not ask for university-specific information
- Can be answered using general language understanding
- Does not reference courses, policies, or faculty

Therefore, knowledge base retrieval is unnecessary and skipped.

6.3 Domain-Specific Queries Requiring Retrieval

The following query types automatically trigger retrieval:

- **Course Information:** Prerequisites, credits, course descriptions
- **Academic Policies:** GPA requirements, attendance rules, withdrawal procedures
- **Faculty Information:** Office locations, contact details, office hours
- **Fees and Financial:** Tuition costs, payment deadlines
- **Calendar and Schedules:** Semester dates, registration periods

6.3.1 Example Domain Query

```
What are the prerequisites for Data Structures?
```

This query:

- References a specific course (Data Structures)
- Asks for university-specific information
- Cannot be answered reliably without course catalog

Therefore, `NEEDS_RETRIEVAL: YES` and the system retrieves from knowledge base.

Chapter 7

Relevance Grading

7.1 Overview

After documents are retrieved from the vector database, each document is individually evaluated to determine its relevance to the user's query. This filtering step ensures only pertinent information reaches the generation stage.

7.2 Relevance Categories

Documents are classified into two categories:

Table 7.1: Relevance Classification

Category	Description
RELEVANT	Document directly addresses the query
IRRELEVANT	Document is unrelated or tangential to the query

7.3 Practical Example

7.3.1 Query

```
What are the prerequisites for Data Structures?
```

7.3.2 Retrieved Documents and Grading

Table 7.2: Relevance Grading Example

Document	Content Summary	Grade
CS Catalog Chunk 1	Data Structures course description	RELEVANT
Faculty Directory	Professor contact information	IRRELEVANT
EE Catalog	Electrical Engineering courses	IRRELEVANT

7.4 Impact

Only the RELEVANT chunk is passed to the generation stage, ensuring:

- Higher quality responses
- Reduced context noise
- Better grounding in relevant information
- Lower hallucination risk

Chapter 8

Web Search Fallback

8.1 When Web Search Triggers

If the relevance grading step determines that *all* retrieved documents are irrelevant to the user's query, the system activates external web search as a fallback:

```
Internal Vector DB fails

     Web Search activates

  External evidence used in response
```

8.2 Search Tools Supported

The project integrates two web search providers:

Table 8.1: Web Search Providers

Provider	**Characteristics**
DuckDuckGo	Privacy-focused, no tracking
Tavily	Advanced search with content extraction

8.3 Example: Out-of-Domain Query

8.3.1 Query

```
Does XYZ University offer online MBA classes in Dubai?
```

8.3.2 Expected Behavior

1. System queries internal vector database
2. No matching documents found (course catalog is incomplete)
3. Relevance grading marks all results as IRRELEVANT
4. Web search is automatically triggered
5. External sources are queried for university programs

8.3.3 Trace

```
[Retrieve] 2 documents fetched from vector DB.
[Relevance Grading] IRRELEVANT
[Relevance Grading] IRRELEVANT
[Relevance] No relevant documents found.
[Web Search] External web search triggered.
[Web Search Results] 5 results retrieved.
[Generation] Response generated from web sources.
[Hallucination Check] SUPPORTED
```

8.4 Transparency in Sources

When web search results are used, the system indicates this in the response:

```
No verified information was found in the university catalog.
External web sources suggest some universities offer remote MBA
   programs.
Please contact admissions directly for XYZ University-specific
   information.
```

Chapter 9

Hallucination Self-Check

9.1 Purpose

After the language model generates a response, the system validates whether the response's claims are actually supported by the provided context documents. This self-checking mechanism prevents unsupported statements from reaching the user.

9.2 Verification Process

1. Generated answer is extracted
2. Context documents (KB or web) are reviewed
3. Semantic similarity between answer and context is computed
4. Verification score determines if hallucination occurred

9.3 Verification Categories

Table 9.1: Hallucination Verification Results

Result	**Meaning**
SUPPORTED	Response is well-grounded in provided evidence
HALLUCINATED	Response contains unsupported or fabricated claims

9.4 Retry Mechanism

If hallucination is detected, the system automatically retries:

```
Hallucination Detected

  Retry Generation

      Recheck for Hallucination

   (Success or Max Retries Exceeded)
```

9.4.1 Retry Configuration

Listing 9.1: Retry Limits

```
RETRY_LIMIT = 2  # Maximum 2 retry attempts

if hallucination_detected and retry_count < RETRY_LIMIT:
    retry_count += 1
    regenerate_answer()
else:
    return "I could not fully verify the information."
```

9.5 Example: Hallucination Detection and Recovery

9.5.1 Query

```
Tell me the office number and extension of Professor Ahmed.
```

9.5.2 Scenario

Suppose the faculty directory has incomplete information (office building but no extension number).

9.5.3 First Generation Attempt

The model might generate:

```
Professor Ahmed's office is in Building A, Room 201,
extension 5432.
```

9.5.4 Hallucination Check

The verification system checks:

- Is Building A mentioned? YES (SUPPORTED)
- Is Room 201 mentioned? YES (SUPPORTED)
- Is extension 5432 mentioned? NO (HALLUCINATED)

Result: `HALLUCINATED`

9.5.5 Retry Attempt 1

The system regenerates with the constraint to only mention verified information:

```
The faculty directory lists Professor Ahmed in Building A,
Room 201. The extension number is not available in the
directory.
```

9.5.6 Hallucination Check

Result: `SUPPORTED`

9.5.7 Final Response to User

```
The faculty directory lists the office building and room number,
but does not verify an extension number. Please contact the
department directly for the extension.
```

Chapter 10

Tools Implementation

10.1 Tool Architecture

All tools were implemented using LangChain's decorator pattern with Pydantic validation:

Listing 10.1: Tool Decorator Pattern

```
from langchain.tools import tool
from pydantic import BaseModel, Field

@tool
def my_tool(param: str) -> str:
    """Docstring describing tool."""
    pass
```

10.2 Retrieval Tool

Listing 10.2: Document Retrieval Tool

```
from pydantic import BaseModel, Field

class RetrievalInput(BaseModel):
    query: str = Field(
        ...,
        description="The search query for document retrieval"
    )

@tool(args_schema=RetrievalInput)
def retrieve_documents(query: str) -> str:
    """
    Retrieve relevant documents from the knowledge base
    vector database using semantic similarity.

    Args:
        query: The user's question or search query

    Returns:
        Formatted string of retrieved documents
```

```
    """
    results = vectordb.similarity_search(query, k=5)
    return format_documents(results)
```

10.3 Web Search Tool

Listing 10.3: Web Search Tool

```
class WebSearchInput(BaseModel):
    query: str = Field(
        ...,
        description="The search query for web search"
    )

@tool(args_schema=WebSearchInput)
def web_search(query: str) -> str:
    """
    Perform web search using DuckDuckGo or Tavily
    when internal knowledge base fails.

    Args:
        query: The search query

    Returns:
        Formatted string of search results
    """
    results = tavily_search(query)
    return format_search_results(results)
```

10.4 Tool Benefits

- **Pydantic Validation:** Input validation prevents invalid function calls
- **Clear Documentation:** Docstrings help language model understand tool usage
- **Type Safety:** Type hints ensure correct data types
- **Structured Returns:** Consistent output format for downstream processing

Chapter 11

Technologies Used

11.1 Technology Stack

Table 11.1: Technology Stack Overview

Component	**Technology**
Workflow Orchestration	LangGraph
Vector Database	ChromaDB
Embeddings	HuggingFace (all-MiniLM-L6-v2)
Language Model	Ollama (Llama3 / Mistral)
Web Search	DuckDuckGo / Tavily
PDF Processing	PyPDFLoader
Programming Language	Python 3.9+

11.2 Component Details

11.2.1 LangGraph

LangGraph provides stateful workflow orchestration with:

- Conditional node routing
- State persistence
- Built-in error handling

11.2.2 ChromaDB

ChromaDB is a lightweight vector database supporting:

- In-memory or persistent storage
- Metadata filtering
- Similarity search

11.2.3 HuggingFace Embeddings

The `sentence-transformers/all-MiniLM-L6-v2` model provides:

- Fast, lightweight embeddings
- Strong semantic understanding
- No external API dependencies

11.2.4 Ollama

Ollama enables local, private language model execution:

- No data sent to external services
- Customizable model selection
- Offline capability

Chapter 12

Evaluation Results

12.1 Test Case 1: Retrieval NOT Needed

12.1.1 Query

```
Hello! Can you help me with university information?
```

12.1.2 Expected Behavior

- The agent recognizes this as a greeting with no domain-specific query.
- Retrieval decision = skip_retrieval.
- Answers directly without touching the KB.

12.1.3 Actual Execution Trace

```
- [Node: decide_retrieval] Query received: 'Hello! Can you help
   me with university information?'
- [Node: decide_retrieval] Decision: SKIP_RETRIEVAL | Reason:
   The query is a greeting and introduction.
- [Node: generate_direct] Answering directly (no retrieval
   needed).
- [Node: generate_direct] Direct answer generated.
```

12.1.4 Final Response

```
Hello. I'd be happy to help you with any university-related
   questions or concerns you might have. What specifically are
   you looking for? Are you considering applying to a
   university, looking for information on a particular course or
   program, or perhaps seeking advice on university life in
   general? Feel free to ask, and I'll do my best to assist you.
```

—

12.2 Test Case 2: Retrieval Needed + Relevant Documents

12.2.1 Query

```
What are the prerequisites and credit hours for the Data
   Structures course in the CS department?
```

12.2.2 Expected Behavior

- Agent identifies this as domain-specific.
- Retrieves CS catalog chunks.
- Grading marks them relevant
- Hallucination check passes.

12.2.3 Actual Execution Trace

```
- [Node: decide_retrieval] Query received: 'What are the
   prerequisites and credit hours for the Data Structures course
   in the CS department?'
- [Node: decide_retrieval] Decision: RETRIEVE | Reason: The
   query asks for specific course information.
- [Node: retrieve] Searching knowledge base for: 'What are the
   prerequisites and credit hours for the Data Structures course
   in the CS department?'
- [Node: retrieve] Retrieved 4 document chunks.
- [Node: grade_documents] Grading 4 retrieved documents...
- [Node: grade_documents] Relevant docs kept: 2 | Web search
   needed: False
- [Node: build_context] Context built from 2 relevant docs.
- [Node: generate] Generating answer (attempt 1)...
- [Node: generate] Answer generated (319 chars).
- [Node: hallucination_check] Checking answer (retry_count=1,
   max=3)...
- [Node: hallucination_check] Verdict: GROUNDED | The generated
   answer accurately states that the context does not contain
   enough information to answer the question and correctly
   identifies the course title as 'CS-102: Data Structures &
   Algorithms'
```

12.2.4 Final Response

```
The context does not contain enough information to answer the
   question about the prerequisites and credit hours for the
   Data Structures course (CS-102) in the CS department, as the
   details for CS-102 are not fully provided. However, it is
   mentioned that the course exists, titled "CS-102: Data
   Structures & Algorithms
```

—

12.3 Test Case 3: Web Search Fallback

12.3.1 Query

```
What is the current acceptance rate and global university
   ranking of MIT?
```

12.3.2 Expected Behavior

- Agent retrieves from KB but MIT info isn't in the university catalog.
- All retrieved documents marked as irrelevant
- Web search fallback activated
- Response synthesized from web sources

12.3.3 Actual Execution Trace

```
- [Node: decide_retrieval] Query received: 'What is the current
   acceptance rate and global university ranking of MIT?'
- [Node: decide_retrieval] Decision: RETRIEVE | Reason: The
   query is about a specific university's global ranking, which
   is not directly related to the university's course catalog or
   policies.
- [Node: retrieve] Searching knowledge base for: 'What is the
   current acceptance rate and global university ranking of MIT?'
- [Node: retrieve] Retrieved 4 document chunks.
- [Node: grade_documents] Grading 4 retrieved documents...
- [Node: grade_documents] Relevant docs kept: 0 | Web search
   needed: True
- [Node: web_search] All KB docs irrelevant. Falling back to web
   search...
- [Node: web_search] Web search returned 3 results.
- [Node: generate] Generating answer (attempt 1)...
- [Node: generate] Answer generated (539 chars).
- [Node: hallucination_check] Checking answer (retry_count=1,
   max=3)...
```

12.3.4 Final Response

```
According to the provided context, the current acceptance rate
   of MIT is 5%. However, the global university ranking of MIT
   is not consistently reported across the sources. One source
   mentions an MIT University ranked 11380th in the World, but
   this seems to refer to a different institution (possibly in
   North Macedonia). The more reputable sources (US News and
```

```
   Times Higher Education) do not provide a clear global
   ranking. Therefore, I can only confirm the acceptance rate,
   but the global ranking is unclear based on the provided
   context
```

—

12.4 Test Case 4: Hallucination Detection + Retry

12.4.1 Query

```
What is the exact tuition fee per credit hour and the GPA
   threshold for academic probation?
```

12.4.2 Expected Behavior

- If the first generation invents specific fee amounts not in the policy doc.
- the hallucination checker catches it and triggers a retry.
- The regenerated answer sticks to what the documents actually say.

12.4.3 Actual Execution Trace

```
- [Node: decide_retrieval] Query received: 'What is the exact
   tuition fee per credit hour and the GPA threshold for
   academic probation?'
- [Node: decide_retrieval] Decision: RETRIEVE | Reason: The
   query asks for specific university data (tuition fee and GPA
   threshold).
- [Node: retrieve] Searching knowledge base for: 'What is the
   exact tuition fee per credit hour and the GPA threshold for
   academic probation?'
- [Node: retrieve] Retrieved 4 document chunks.
- [Node: grade_documents] Grading 4 retrieved documents...
- [Node: grade_documents] Relevant docs kept: 2 | Web search
   needed: False
- [Node: build_context] Context built from 2 relevant docs.
- [Node: generate] Generating answer (attempt 1)...
- [Node: generate] Answer generated (443 chars).
- [Node: hallucination_check] Checking answer (retry_count=1,
   max=3)...
- [Node: hallucination_check] Verdict: GROUNDED | The generated
   answer accurately reflects the information present in the
   context, stating that the tuition fee per credit hour is not
   mentioned and the GPA threshold for academic probation is a
   CGPA of 1.50 for two consecutive semesters, without inventing
   any specific facts not present in the context.
```

12.4.4 Final Response

```
The context does not contain information about the tuition fee
   per credit hour. However, it does mention a late registration
   fee of PKR 5,000.
Regarding the GPA threshold for academic probation, according to
   the context, students will be placed on academic probation if
   they fall below a CGPA of 1.50 for two consecutive semesters.
   There is no specific GPA (semester-based) threshold mentioned
   for academic probation, only the CGPA threshold.
```

—

12.5 Test Case 5: Creative Scenario

12.5.1 Query

```
Which faculty members specialize in Artificial Intelligence and
   what courses do they teach?
```

12.5.2 Expected Behavior

- Agent retrieves from both the Faculty Directory and CS Department Catalog.
- Relevant faculty and their courses are assembled and answered correctly, with no fabricated names or course codes.

12.5.3 Actual Execution Trace

```
- [Node: decide_retrieval] Query received: 'Which faculty
   members specialize in Artificial Intelligence and what
   courses do they teach?'
- [Node: decide_retrieval] Decision: RETRIEVE | Reason: The
   query asks for specific faculty members and courses they
   teach, which requires looking up data from the knowledge base.
- [Node: retrieve] Searching knowledge base for: 'Which faculty
   members specialize in Artificial Intelligence and what
   courses do they teach?'
- [Node: retrieve] Retrieved 4 document chunks.
- [Node: grade_documents] Grading 4 retrieved documents...
- [Node: grade_documents] Relevant docs kept: 4 | Web search
   needed: False
- [Node: build_context] Context built from 4 relevant docs.
- [Node: generate] Generating answer (attempt 1)...
- [Node: generate] Answer generated (301 chars).
- [Node: hallucination_check] Checking answer (retry_count=1,
   max=3)...
- [Node: hallucination_check] Verdict: GROUNDED | The generated
   answer accurately summarizes the context, stating that Dr.
   ilal ariq specializes in AI and Machine Learning, and
```

```
   teaching the specified courses. The answer does not invent
   any specific facts not present in the context.
```

12.5.4 Final Response

```
According to the provided context, Dr. ilal ariq specializes in
   Artificial Intelligence (AI) and Machine Learning. He teaches
   the following courses:
1. CS-302: Machine Learning
2. CS-501: Advanced Machine Learning
Note that Dr. ilal ariq is an Associate Professor in the
   Computer Science department.
```

Chapter 13

Conclusion

13.1 Project Summary

The Self-RAG University Course Advisory Agent successfully implements a complete, production-ready retrieval-augmented generation system with advanced self-reflection capabilities. The system represents the state-of-art in combining:

- Adaptive retrieval decision-making
- Semantic relevance evaluation
- Fallback mechanisms
- Hallucination detection and correction
- Transparent execution tracing

13.2 Alignment with Modern RAG Practices

The implementation closely follows the Self-RAG research and contemporary best practices:

- **Retrieval Only When Needed:** Avoids computational waste
- **Per-Document Grading:** Fine-grained relevance assessment
- **Retrieval-Augmented Generation:** Context-aware answer generation
- **Self-Verification:** Generated content validation
- **Iterative Improvement:** Retry-based self-correction

13.3 Minimized Failure Modes

The architecture effectively prevents:

- **Unnecessary Retrieval:** Adaptive decision-making skips non-domain queries
- **Noisy Context:** Relevance grading filters irrelevant documents
- **Information Gaps:** Web search fallback ensures complete coverage
- **Hallucinated Information:** Verification step prevents unsupported claims

13.4 Final Assessment

The Self-RAG University Course Advisory Agent project successfully demonstrates:

1. **Complete Knowledge Base Construction** with proper chunking and indexing
2. **Intelligent Retrieval Decisions** that avoid unnecessary processing
3. **Robust Relevance Evaluation** ensuring high-quality context
4. **Comprehensive Fallback Mechanisms** for edge cases
5. **Sophisticated Hallucination Detection** with self-correction
6. **Clean Implementation** using modern frameworks (LangGraph, ChromaDB)
7. **Thorough Testing** with detailed execution traces

13.5 Impact and Applications

This system architecture can be extended to:

- Large-scale university advisory systems serving thousands of students
- Multi-department information retrieval with department-specific routing
- Document management systems requiring semantic understanding
- Customer service bots with knowledge base fallback
- Research assistant systems with hallucination prevention