

ASSIGNMENT



Name	Alishba Nadeem
Roll Number	BCS-F24-E30
Assignment	Computer Architecture
Teacher Name	Sir Raza
Semester	5 th (Self)
Department	Computer Science

University of Mianwali

NASM Assembly Language Tasks

32-bit NASM Assembly for Windows

Task 1: Put a Number in a Register

```
global _main
extern _printf

section .data

; %d tells printf to display a decimal number.
; 10 creates a new line.
; 0 marks the end of the string.
format db "Value in AL = %d", 10, 0

section .text

_main:
; Put decimal 10 into AL.
; AL is an 8-bit register.
mov al, 10

; printf works with larger values.
; MOVZX copies AL into EAX and fills
; the remaining bits with zeros.
movzx eax, al

; Function parameters are pushed onto
; the stack from right to left.
push eax

; Push the address of the format string.
push format

; Call the printf function.
call _printf

; Two 32-bit values were pushed.
; Each value used 4 bytes.
; Remove 8 bytes from the stack.
add esp, 8

; Return 0 from the program.
xor eax, eax
ret
```

Resulting Output :

```
C:\Users\asbah>cd "C:\Program Files (x86)\CodeBlocks\MinGW\bin"
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q1.asm -o d:\nasm\q1.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q1.obj -o d:\nasm\q1.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q1.exe
Value in AL = 10
```

Task 2: Store a 32-Bit Number

```
global _main
extern _printf

section .data

; %08X displays an 8-digit hexadecimal value.
format db "EAX = 0x%08X", 10, 0

section .text

_main:
; EAX is a 32-bit CPU register.
; Store hexadecimal 12345678 inside it.
mov eax, 0x12345678

; Push the number that printf will display.
push eax

; Push the address of the format string.
push format

; Display the result.
call _printf

; Remove the two parameters from the stack.
add esp, 8

; Return 0.
xor eax, eax
ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q2.asm -o d:\nasm\q2.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q2.obj -o d:\nasm\q2.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q2.exe
EAX = 0x12345678
```

Task 3: Copy Data Between Registers

```

global _main
extern _printf

section .data

format db "AL = %d, BL = %d", 10, 0

section .text

_main:
    ; Store 10 inside AL.
    mov al, 10

    ; Copy AL into BL.
    mov bl, al

    ; Convert BL to a 32-bit value.
    ; Store it temporarily in ECX.
    movzx ecx, bl

    ; Convert AL to a 32-bit value.
    ; Store it in EAX.
    movzx eax, al

    ; printf arguments are pushed
    ; from right to left.
    push ecx
    push eax
    push format
    call _printf

    ; Three values were pushed.
    ; 3 x 4 = 12 bytes.
    add esp, 12

    xor eax, eax
    ret

```

Resulting Output :

```

C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q3.asm -o d:\nasm\q3.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q3.obj -o d:\nasm\q3.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q3.exe
AL = 10, BL = 10

```

Task 4: Add a Number

```
global _main
extern _printf

section .data

format db "10 + 5 = %d", 10, 0

section .text

_main:
    ; Start with 10.
    mov al, 10

    ; Add 5 to AL.
    add al, 5

    ; AL now contains 15.
    ; Convert the 8-bit result to 32 bits.
    movzx eax, al

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q4.asm -o d:\nasm\q4.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q4.obj -o d:\nasm\q4.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q4.exe
10 + 5 = 15
```

Task 5: Add Two Registers

```
global _main
extern _printf

section .data

format db "AL = %d, BL = %d", 10, 0

section .text

_main:
    ; Store 10 in AL.
    mov al, 10

    ; Store 20 in BL.
    mov bl, 20

    ; Add the contents of BL to AL.
    add al, bl

    ; AL now contains 30.
    ; BL still contains 20.
    movzx ecx, bl
    movzx eax, al

    push ecx
    push eax
    push format
    call _printf
    add esp, 12

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q5.asm -o d:\nasm\q5.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q5.obj -o d:\nasm\q5.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q5.exe
AL = 30, BL = 20
```

Task 6: Perform 32-Bit Addition

```
global _main
extern _printf

section .data

format db "EAX = %d, EBX = %d", 10, 0

section .text

_main:
    ; Store 10 inside EAX.
    mov eax, 10

    ; Store 20 inside EBX.
    mov ebx, 20

    ; Add EBX to EAX.
    add eax, ebx

    ; EAX now contains 30.
    ; EBX still contains 20.
    push ebx
    push eax
    push format
    call _printf
    add esp, 12

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q6.asm -o d:\nasm\q6.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q6.obj -o d:\nasm\q6.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q6.exe
EAX = 30, EBX = 20
```

Task 7: Basic Subtraction

```
global _main
extern _printf

section .data

format db "20 - 5 = %d", 10, 0

section .text

_main:
    ; Store 20 inside AL.
    mov al, 20

    ; Subtract 5.
    sub al, 5

    ; AL now contains 15.
    movzx eax, al

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q7.asm -o d:\nasm\q7.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q7.obj -o d:\nasm\q7.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q7.exe
20 - 5 = 15
```

Task 8: Subtract One Register From Another

```
global _main
extern _printf

section .data

format db "30 - 10 = %d", 10, 0

section .text

_main:
    mov eax, 30
    mov ebx, 10

    ; Calculate EAX - EBX.
    sub eax, ebx

    ; EAX now contains 20.
    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q8.asm -o d:\nasm\q8.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q8.obj -o d:\nasm\q8.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q8.exe
30 - 10 = 20
```

Task 9: Increment a Register

```
global _main
extern _printf

section .data

format db "After INC, EAX = %d", 10, 0

section .text

_main:
    ; Start with 9.
    mov eax, 9

    ; INC means increase by one.
    inc eax

    ; EAX now contains 10.
    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q9.asm -o d:\nasm\q9.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q9.obj -o d:\nasm\q9.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q9.exe
After INC, EAX = 10
```

Task 10: Decrement a Register

```
global _main
extern _printf

section .data

format db "After DEC, EBX = %d", 10, 0

section .text

_main:
    ; Start with 10.
    mov ebx, 10

    ; DEC means decrease by one.
    dec ebx

    ; EBX now contains 9.
    push ebx
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q10.asm -o d:\nasm\q10.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q10.obj -o d:\nasm\q10.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q10.exe
After DEC, EBX = 9
```

Task 11: Perform an AND Operation

```
global _main
extern _printf

section .data

format db "Result = 0x%02X", 10, 0

section .text

_main:
    ; AA in binary is:
    ; 10101010
    mov al, 0xAA

    ; 0F in binary is:
    ; 00001111
    and al, 0x0F

    ; Result:
    ; 00001010
    ; This is hexadecimal 0A.
    movzx eax, al

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q11.asm -o d:\nasm\q11.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q11.obj -o d:\nasm\q11.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q11.exe
Result = 0x0A
```

Task 12: Perform an OR Operation

```
global _main
extern _printf

section .data

format db "Result = %d", 10, 0

section .text

_main:
    ; Decimal 5:
    ; 00000101
    mov al, 5

    ; Decimal 8:
    ; 00001000
    or al, 8

    ; Result:
    ; 00001101
    ; Decimal 13.
    movzx eax, al

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q12.asm -o d:\nasm\q12.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q12.obj -o d:\nasm\q12.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q12.exe
Result = 13
```

Task 13: Compare Two Equal Numbers

```

global _main
extern _printf

section .data

equalMessage db "The numbers are equal.", 10, 0
notEqualMessage db "The numbers are not equal.", 10, 0

section .text

_main:
    mov al, 10
    mov bl, 10

    ; CMP internally performs:
    ; AL - BL

    ; The result is not stored.
    ; CPU flags are updated instead.
    cmp al, bl

    ; JE means Jump if Equal.
    ; It checks the Zero Flag.
    je numbers_are_equal

numbers_are_not_equal:
    push notEqualMessage
    call _printf
    add esp, 4
    jmp finished

numbers_are_equal:
    push equalMessage
    call _printf
    add esp, 4

finished:
    xor eax, eax
    ret

```

Resulting Output :

```

C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q13.asm -o d:\nasm\q13.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q13.obj -o d:\nasm\q13.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q13.exe
The numbers are equal.

```

Task 14: Test Two Bit Patterns

```

global _main
extern _printf

section .data

zeroMessage db "No common 1 bits were found.", 10, 0
commonMessage db "Common 1 bits were found.", 10, 0

section .text

_main:
    ; AL = 11110000
    mov al, 0xF0

    ; BL = 00001111
    mov bl, 0x0F

    ; TEST performs a bitwise AND
    ; but does not save the answer.
    ; It only changes CPU flags.
    test al, bl

    ; Jump if the result was zero.
    jz no_common_bits

common_bits:
    push commonMessage
    call _printf
    add esp, 4
    jmp finished

no_common_bits:
    push zeroMessage
    call _printf
    add esp, 4

finished:
    xor eax, eax
    ret

```

Resulting Output :

```

C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q14.asm -o d:\nasm\q14.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q14.obj -o d:\nasm\q14.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q14.exe
No common 1 bits were found.

```

Task 15: Exchange Two Registers

```
global _main
extern _printf

section .data

format db "AL = %d, BL = %d", 10, 0

section .text

_main:
    mov al, 10
    mov bl, 20

    ; Before XCHG:
    ; AL = 10
    ; BL = 20
    xchg al, bl

    ; After XCHG:
    ; AL = 20
    ; BL = 10
    movzx ecx, bl
    movzx eax, al

    push ecx
    push eax
    push format
    call _printf
    add esp, 12

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q15.asm -o d:\nasm\q15.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q15.obj -o d:\nasm\q15.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q15.exe
AL = 20, BL = 10
```

Task 16: Store a Number in Memory

```
global _main
extern _printf

section .data

; Reserve one byte in memory.
; Its starting value is 0.
number db 0
format db "Value in memory = %d", 10, 0

section .text

_main:
    ; Store decimal 42 at the memory
    ; location called number.
    mov byte [number], 42

    ; Read the byte from memory and
    ; convert it to a 32-bit value.
    movzx eax, byte [number]

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q16.asm -o d:\nasm\q16.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q16.obj -o d:\nasm\q16.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q16.exe
Value in memory = 42
```

Task 17: Read Data From Memory

```
global _main
extern _printf

section .data

number db 0
format db "Value loaded into BL = %d", 10, 0

section .text

_main:
    ; Store 42 in memory.
    mov byte [number], 42

    ; Read the byte from memory
    ; and place it inside BL.
    mov bl, [number]

    ; Convert BL to 32 bits for printf.
    movzx eax, bl

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q17.asm -o d:\nasm\q17.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q17.obj -o d:\nasm\q17.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q17.exe
Value loaded into BL = 42
```

Task 18: Add a Register Value to Memory

```
global _main
extern _printf

section .data

; Create one byte containing 10.
number db 10
format db "New memory value = %d", 10, 0

section .text

_main:
    ; Put 5 into BL.
    mov bl, 5

    ; Add BL to the byte stored in memory.
    ;
    ; Memory initially contains 10.
    ; BL contains 5.
    ;
    ; 10 + 5 = 15
    add byte [number], bl

    ; Read the new memory value.
    movzx eax, byte [number]

    push eax
    push format
    call _printf
    add esp, 8

    xor eax, eax
    ret
```

Resulting Output :

```
C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q18.asm -o d:\nasm\q18.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q18.obj -o d:\nasm\q18.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q18.exe
New memory value = 15
```

Task 19: Use the Stack

```

global _main
extern _printf

section .data

format db "EAX = 0x%08X, EBX = 0x%08X", 10, 0

section .text

_main:
    ; Put a value into EAX.
    mov eax, 0x12345678

    ; PUSH places EAX on the stack.
    push eax

    ; POP removes the top value
    ; from the stack and places it
    ; inside EBX.
    pop ebx

    ; Both registers now contain
    ; the same value.
    push ebx
    push eax
    push format
    call _printf
    add esp, 12

    xor eax, eax
    ret

```

Resulting Output :

```

C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q19.asm -o d:\nasm\q19.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q19.obj -o d:\nasm\q19.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q19.exe
EAX = 0x12345678, EBX = 0x12345678

```

Task 20: Mini Complete Program

```

global _main
extern _printf

section .data

; Reserve one byte for the final result.
result db 0

; printf will display three decimal numbers.
format db "AL = %d, BL = %d, Memory = %d", 10, 0

section .text

_main:
; -----
; Step 1
; Put 10 into AL.
; -----
mov al, 10

; -----
; Step 2
; Add 20.
;
; 10 + 20 = 30
; -----
add al, 20

; -----
; Step 3
; Subtract 5.
;
; 30 - 5 = 25
; -----
sub al, 5

; -----
; Step 4
; Store AL in memory.
;
; Memory now contains 25.
; -----
mov [result], al

; -----
; Step 5
; Read the value from memory into BL.
; -----
mov bl, [result]

; -----
; Prepare values for printf.
;
; printf uses 32-bit integer parameters.
; -----

```

```

movzx eax, al
movzx ecx, bl
movzx edx, byte [result]

; -----
; printf arguments must be pushed
; from right to left.
;
; format contains:
;
; AL = %d, BL = %d, Memory = %d
;
; Therefore we push:
;
; Memory
; BL
; AL
; format address
; -----
push edx
push ecx
push eax
push format
call _printf

; -----
; Four 32-bit parameters were pushed.
;
; 4 x 4 bytes = 16 bytes.
;
; Restore ESP.
; -----
add esp, 16

; -----
; Return 0 to Windows.
; -----
xor eax, eax
ret

```

Resulting Output :

```

C:\Program Files (x86)\CodeBlocks\MinGW\bin>nasm -f win32 d:\nasm\q20.asm -o d:\nasm\q20.obj
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q19.obj -o d:\nasm\q20.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>gcc d:\nasm\q20.obj -o d:\nasm\q20.exe
C:\Program Files (x86)\CodeBlocks\MinGW\bin>d:\nasm\q20.exe
AL = 25, BL = 25, Memory = 25

```