Name	Period	
_	•	

1. The simulation below counts the number of coin flips it takes to achieve a specified number of heads in a row. Once the number of heads is achieved, the simulations stops and prints the number of coin clips. Consider the following output for different conditions.

Specified heads	Output
<pre>int numHeads = 4;</pre>	30 flips
int numHeads = 12;	10000 flips

	int	numH	eads	=	12;	10000 fl	lips						
	Comp	lete the	Coun	ntHe	ads cla	ass helow	J						
Complete the CountHeads class below. Public class CountHeads{													
		pul	olic	st	atic	void r	main(Strin	ng	args[]){			
		-						-	<i>y</i> -				
١		}											
}													
												/	6

© Pluska

```
2. Write the following for-loops as while loops

(a)

int y;

for(y = 5; y < 10; y+=2)

{
    System.out.println(y);
}

System.out.println(z);

//4
```

```
3. What is the output for each code segment below,

(a)

int m = 0;
int j = 0;

do{
    j *= -1;
    if(j >= 0) {
        m += 2;
    }
    j+=2;
} yhile (m < 4);

System.out.println(j);

(b)
    int i = 5, j = 0;
    do{
        for(j = 0; j < i; j++) {
            System.out.print("*");
        }
        System.out.println();
        i--;
    }
}while (i > 0);
```

Score _____/20

4. The Magic 8 Ball is a plastic sphere resembling an 8-ball. Inside is a floating die with 20 faces face has an affirmative, negative, or non-committal statement printed in raised letters. These is are read through a window on the ball's bottom in response to a "yes" or "no" question. Finis Magic8Ball class which simulates a Magic 8 Ball. You simulator needs to produce messages first 2 cases only. Once the message is displayed, prompt the user if they would like to play a	nessages sh the <u>for the</u>
the user types "y", the simulation will continue to run.	0
Public class CountHeads{	
<pre>public static void main(String args[]){</pre>	
}	
}	
	/6