# Module Interface Specification for 2D Localizer

Aliyah Jimoh

 $March\ 14,\ 2025$ 

# 1 Revision History

Date	Version	Notes
2025/03/19	1.0	Initial Draft

## 2 Symbols, Abbreviations and Acronyms

See SRS Documentation at https://github.com/Aliyah Jimoh/2D-Localizer/blob/main/docs/SRS/SRS.pdf

[Also add any additional symbols, abbreviations or acronyms —SS]

## Contents

Rev	vision History						
Symbols, Abbreviations and Acronyms							
Inti	roduction						
Not	tation						
Mo	dule Decomposition						
MIS	S of Control Module						
6.1	Module						
6.2	Uses						
	6.2.1 Exported Constants						
	6.2.2 Exported Access Programs						
6.3	Semantics						
	6.3.1 State Variables						
	6.3.4 Access Routine Semantics						
MIS	S of Input Format Module						
7.1	•						
7.2	Uses						
7.3	Syntax						
7.4	•						
	7.4.4 Access Routine Semantics						
MIS	S of Localization Module						
8.1							
0.0	·						
	1						
8 4							
0.1							
	Note   Note   Mo   Mis   6.1   6.2   6.3    Mis   7.1   7.2   7.3    7.4    Mis   Mi	Notation					

		8.4.3 A	ssumptions			 	 	 		 		7
		8.4.4 A	ccess Routine S	emantics		 	 	 		 		7
		8.4.5 L	ocal Functions .			 	 	 	 •	 	•	7
9	MIS	of Accu	ıracy Evaluati	on Modu	le							8
	9.1	Module.				 	 	 		 		8
	9.2	Uses				 	 	 		 		8
	9.3	Syntax.				 	 	 		 		8
		9.3.1 E	xported Consta	nts		 	 	 		 		8
		9.3.2 E	xported Access	Programs		 	 	 		 		8
	9.4	Semantic	s			 	 	 		 		8
		9.4.1 S	tate Variables .			 	 	 		 		8
		9.4.2 E	nvironment Var	iables		 	 	 		 		8
		9.4.3 A	ssumptions			 	 	 		 		8
		9.4.4 A	ccess Routine S	emantics		 	 	 		 		8
		9.4.5 L	ocal Functions .			 	 	 		 		Ć
<b>10</b>		_	out Module									10
												10
												10
	10.3	*										10
			xported Constan									10
			xported Access									10
	10.4		S									10
			tate Variables .									10
		10.4.2 E	nvironment Var	iables		 	 	 		 		10
			ssumptions									10
			ccess Routine S									10
		10.4.5 L	ocal Functions .			 	 	 	 •	 	•	11
11	MIS	of Plot	ting Module									12
	11.1	Module.				 	 	 		 		12
	11.2	Uses				 	 	 		 		12
												12
		11.3.1 E	xported Constan	nts		 	 	 		 		12
		11.3.2 E	xported Access	Programs		 	 	 		 		12
	11.4	Semantic	S			 	 	 		 		12
			tate Variables .									12
			nvironment Var									12
			ssumptions									12
			ccess Routine S									12
			ocal Functions .									

12 Appendix 14

## 3 Introduction

The following document details the Module Interface Specifications for 2D Localizer, a program that implements various sensors to help localize mobile robots on a 2D plane in enclosed environments.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at <a href="https://github.com/AliyahJimoh/2D-Localizer">https://github.com/AliyahJimoh/2D-Localizer</a>.

### 4 Notation

[You should describe your notation. You can use what is below as a starting point. —SS]

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol := is used for a multiple assignment statement and conditional rules follow the form  $(c_1 \Rightarrow r_1|c_2 \Rightarrow r_2|...|c_n \Rightarrow r_n)$ .

The following table summarizes the primitive data types used by 2D Localizer.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	$\mathbb{Z}$	a number without a fractional component in $(-\infty, \infty)$
natural number	N	a number without a fractional component in $[1, \infty)$
real	$\mathbb{R}$	any number in $(-\infty, \infty)$

The specification of 2D Localizer uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, 2D Localizer uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

## 5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding Module	
	Input Format Module
	Output Format Module
	Localization Module
Behaviour-Hiding Module	Control Module
	Plotting Module
	Accuracy Evaluation Module
Software Decision Module	

Table 1: Module Hierarchy

## 6 MIS of Control Module

### 6.1 Module

main

#### 6.2 Uses

- Input Format Module (Section 7)
- Localization Module (Section 8)
- Plotting Module (Section 11)

## 6.2.1 Exported Constants

None

#### 6.2.2 Exported Access Programs

Name	In	Out	Exceptions
main			Runtime
			error

#### 6.3 Semantics

#### 6.3.1 State Variables

None

#### 6.3.2 Environment Variables

• user\_input: stores user-provided input

#### 6.3.3 Assumptions

#### 6.3.4 Access Routine Semantics

main():

• transition: None

• output: The control module is the first to be called

• exception: None

```
Get(user_input) variables from user load_input(user_input)  \# \ verify\_input(All \ inputs \ from \ file)  localize(beacons, T_{mf}, T_{rf}, range_measurements)  \# \ plot(estimated \ poses, \ beacons, \ T_{mf})
```

## 7 MIS of Input Format Module

#### 7.1 Module

 $input\_format$ 

#### 7.2 Uses

None

## 7.3 Syntax

#### 7.3.1 Exported Constants

None

#### 7.3.2 Exported Access Programs

Name	${f In}$	Out	Exceptions
load_input	String	Data	File error (file does not
			exist)
verify_input	-	-	Error invariable

## 7.4 Semantics

#### 7.4.1 State Variables

- $\bullet$  sensor\_data(user\_input):
  - range\_measurements:  $\mathbb{R}^N$
  - camera:  $\mathbb{R}^3$

#### 7.4.2 Environment Variables

None

#### 7.4.3 Assumptions

• The module will call on a yaml file

#### 7.4.4 Access Routine Semantics

load\_input("Filename" + ".yaml"):

• output:

– beacons:  $\mathbb{R}^{N\times 2}$ 

— fiducial\_map:  $\mathbb{R}^3$ 

– fiducial\_robot:  $\mathbb{R}^3$ 

– range\_measurements:  $\mathbb{R}^N$ 

• exception: File not found

verify\_input(data):

• exception: Data format was incorrect

## 8 MIS of Localization Module

#### 8.1 Module

localization

#### 8.2 Uses

• Input Format Module (Section 7)

## 8.3 Syntax

#### 8.3.1 Exported Constants

None

#### 8.3.2 Exported Access Programs

Name	In	Out	Exceptions
localize	User Data	$\mathbb{R}^3$	-

#### 8.4 Semantics

#### 8.4.1 State Variables

initial/current pose

#### 8.4.2 Environment Variables

None

#### 8.4.3 Assumptions

• GTSAM is installed

#### 8.4.4 Access Routine Semantics

localize(beacons, fm\_map, fm\_robot, range\_m):

- output: Estimated pose of the robot
  - estimated\_pose:  $\mathbb{R}^3$
- exception: Format errors

#### 8.4.5 Local Functions

GTSAM functions

## 9 MIS of Accuracy Evaluation Module

#### 9.1 Module

accuracy

#### 9.2 Uses

• Localization Module (Section 8)

## 9.3 Syntax

#### 9.3.1 Exported Constants

None

#### 9.3.2 Exported Access Programs

Name	${ m In}$	Out	Exceptions
compute_fim	$(\mathbb{R}^2,\mathbb{R}^{N imes 2},\mathbb{R}^N)$	$\mathbb{R}^{2 imes2}$	-
$compute\_crlb$	$\mathbb{R}^{2 imes2}$	$\mathbb{R}^{2 imes2}$	-

#### 9.4 Semantics

#### 9.4.1 State Variables

None

#### 9.4.2 Environment Variables

None

#### 9.4.3 Assumptions

• Noise variances are positive

#### 9.4.4 Access Routine Semantics

compute\_fim(estimated\_pose, beacons, range\_variances):

• output: A  $2 \times 2$  Fisher Information Matrix (FIM), computed as:

$$\mathcal{I}(\hat{\mathbf{x}}) = \sum_{j=1}^{N} \frac{1}{\sigma_j^2} \frac{(\hat{\mathbf{x}} - \mathbf{a}_j)(\hat{\mathbf{x}} - \mathbf{a}_j)^T}{\|\hat{\mathbf{x}} - \mathbf{a}_j\|^2}$$

compute\_fim(estimated\_pose, beacons, range\_variances):

 $\bullet$  output: A  $2\times 2$  CRLB matrix, computed as:

$$\mathcal{C}=\mathcal{I}^{-1}$$

ullet exception: If  $\mathcal I$  is singular, the function returns 'None'.

## 9.4.5 Local Functions

None

## 10 MIS of Output Module

### 10.1 Module

output

#### 10.2 Uses

• Localization Module (Section 8)

## 10.3 Syntax

#### 10.3.1 Exported Constants

None

#### 10.3.2 Exported Access Programs

Name	In	Out	Exceptions
output_format	-	-	-
$output\_pose$	_	-	-

#### 10.4 Semantics

#### 10.4.1 State Variables

None

#### 10.4.2 Environment Variables

None

## 10.4.3 Assumptions

•

#### 10.4.4 Access Routine Semantics

output\_format():

• transition: [if appropriate —SS]

• output: [if appropriate —SS]

• exception: [if appropriate —SS]

output\_pose():

- $\bullet$  transition: [if appropriate —SS]
- $\bullet\,$  output: [if appropriate —SS]
- $\bullet \;$  exception: [if appropriate —SS]

## 10.4.5 Local Functions

None

## 11 MIS of Plotting Module

#### 11.1 Module

plot

## 11.2 Uses

### 11.3 Syntax

#### 11.3.1 Exported Constants

#### 11.3.2 Exported Access Programs

Name	In	Out	Exceptions
plot_localization_live	$R^{N\times 2}, R^2, \text{Image}$	Plot	-
update_trajectory	$R^2$	-	-

#### 11.4 Semantics

#### 11.4.1 State Variables

None

#### 11.4.2 Environment Variables

None

#### 11.4.3 Assumptions

None

#### 11.4.4 Access Routine Semantics

plot\_localization\_live(beacons, fm\_map\_2D, map):

• output: A dynamic plot showing real-time robot localization.

update\_trajectory(estimated\_pose):

• transition: Changes the robot's position on the map

#### 11.4.5 Local Functions

None

## References

Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. Fundamentals of Software Engineering. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.

Daniel M. Hoffman and Paul A. Strooper. Software Design, Automated Testing, and Maintenance: A Practical Approach. International Thomson Computer Press, New York, NY, USA, 1995. URL http://citeseer.ist.psu.edu/428727.html.

# 12 Appendix

 $[{\bf Extra~information~if~required~--SS}]$