T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4

- **Aim:- Configure IP ACLs to Mitigate Attacks**
- **Topology Diagram**



- **Assign IP Addresses**

T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4





Physical | Config | CLI

```
R1>en
R1#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R1(config)#host R1
R1(config)#interface Serial0/0/0
R1(config-if)#ip address 10.1.1.1 255.255.255.252
R1(config-if)#no shut
R1(config-if)#interface GigabitEthernet0/0
R1(config-if)#ip address 192.168.1.1 255.255.255.0
R1(config-if)#no shut
R1(config-if)#^Z
R1#
%SYS-5-CONFIG_I: Configured from console by console
exit
```

R2

Physical | Config | CLI

IOS Comm

```
R2>en
R2#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#host R2
R2(config)#interface Serial0/0/0
R2(config-if)#ip address 10.1.1.2 255.255.255.252
R2(config-if)#no shut
R2(config-if)#interface Serial0/0/1
R2(config-if)#ip address 10.2.2.2 255.255.255.252
R2(config-if)#no shut
R2(config-if)#int loopback1

R2(config-if)#
%LINK-5-CHANGED: Interface Loopback1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Loopback1, changed state to up
ip address 192.168.2.1 255.255.255.0
R2(config-if)#no shut
R2(config-if)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console
exit
```

T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4

✧ Displaying IP Address Details of Routers



T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4

```
R2>show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol

GigabitEthernet0/0     unassigned      YES unset  administratively down down

GigabitEthernet0/1     unassigned      YES unset  administratively down down

Serial0/0/0            10.1.1.2        YES manual up                    up

Serial0/0/1            10.2.2.2        YES manual up                    up

Serial0/1/0            unassigned      YES unset  administratively down down

Serial0/1/1            unassigned      YES unset  administratively down down

Loopback1              192.168.2.1     YES manual up                    up

Vlan1                  unassigned      YES unset  administratively down down
R2>
```

```
R3>show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol

GigabitEthernet0/0     192.168.3.1     YES manual up                    up

GigabitEthernet0/1     unassigned      YES unset  administratively down down

Serial0/0/0            10.2.2.1        YES manual up                    up

Serial0/0/1            unassigned      YES unset  administratively down down

Serial0/1/0            unassigned      YES unset  administratively down down

Serial0/1/1            unassigned      YES unset  administratively down down

Vlan1                  unassigned      YES unset  administratively down down
R3>
```

- **Configure RIP on routers**

```
R1>en
R1#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R1(config)#router rip
R1(config-router)#network 192.168.1.0
R1(config-router)#network 10.1.1.0
R1(config-router)#^Z
R1#
%SYS-5-CONFIG_I: Configured from console by console
exit
```

T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4

```
R2>en
R2#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#router rip
R2(config-router)#network 10.1.1.0
R2(config-router)#network 10.2.2.0
R2(config-router)#network 192.168.2.0
R2(config-router)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console

R2#exit
```

```
R3>en
R3#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R3(config)#router rip
R3(config-router)#network 10.2.2.0
R3(config-router)#network 192.168.3.0
R3(config-router)#^Z
R3#
%SYS-5-CONFIG_I: Configured from console by console
exit
```

- **Displaying routing table of routers**

```
R1>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C       10.1.1.0/30 is directly connected, Serial0/0/0
L       10.1.1.1/32 is directly connected, Serial0/0/0
R       10.2.2.0/30 [120/1] via 10.1.1.2, 00:00:02, Serial0/0/0
     192.168.1.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.1.0/24 is directly connected, GigabitEthernet0/0
L       192.168.1.1/32 is directly connected, GigabitEthernet0/0
R    192.168.2.0/24 [120/1] via 10.1.1.2, 00:00:02, Serial0/0/0
R    192.168.3.0/24 [120/2] via 10.1.1.2, 00:00:02, Serial0/0/0
R1>
```

T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4

```
R2>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 4 subnets, 2 masks
C       10.1.1.0/30 is directly connected, Serial0/0/0
L       10.1.1.2/32 is directly connected, Serial0/0/0
C       10.2.2.0/30 is directly connected, Serial0/0/1
L       10.2.2.2/32 is directly connected, Serial0/0/1
R    192.168.1.0/24 [120/1] via 10.1.1.1, 00:00:27, Serial0/0/0
     192.168.2.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.2.0/24 is directly connected, Loopback1
L       192.168.2.1/32 is directly connected, Loopback1
R    192.168.3.0/24 [120/1] via 10.2.2.1, 00:00:04, Serial0/0/1
R2>
```

```
R3>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
R       10.1.1.0/30 [120/1] via 10.2.2.2, 00:00:03, Serial0/0/0
C       10.2.2.0/30 is directly connected, Serial0/0/0
L       10.2.2.1/32 is directly connected, Serial0/0/0
R    192.168.1.0/24 [120/2] via 10.2.2.2, 00:00:03, Serial0/0/0
R    192.168.2.0/24 [120/1] via 10.2.2.2, 00:00:03, Serial0/0/0
     192.168.3.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.3.0/24 is directly connected, GigabitEthernet0/0
L       192.168.3.1/32 is directly connected, GigabitEthernet0/0
R3>
```

T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4

- **Configure SSH on R2**

```
R2>en
R2#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#ip domain-name securityincomputing.com
R2(config)#username admin secret pwd
R2(config)#line vty 0 4
R2(config-line)#login local
R2(config-line)#transport input ssh
R2(config-line)#crypto key zeroizersa
                  ^
% Invalid input detected at '^' marker.

R2(config-line)#crypto key zeroize rsa
% No Signature RSA Keys found in configuration.

R2(config)#crypto key generate rsa
The name for the keys will be: R2.securityincomputing.com
Choose the size of the key modulus in the range of 360 to 2048 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.

How many bits in the modulus [512]: 1024
% Generating 1024 bit RSA keys, keys will be non-exportable...[OK]

R2(config)#ipssh time-out 90
*Mar 2 0:49:12.552:  %SSH-5-ENABLED: SSH 1.99 has been enabled
             ^
% Invalid input detected at '^' marker.

R2(config)#ip ssh time-out 90
R2(config)#ipssh authentication-retries 2
             ^
% Invalid input detected at '^' marker.

R2(config)#ip ssh authentication-retries 2
R2(config)#ip ssh version 2
R2(config)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console
exit
```

- **Verify Basic Network Connectivity before ACL Configuration**



T.Y.B.Sc.IT
IT21036

Security In Computing

Date:- 31/01/2024
Practical no :- 4