Roll No: IT21036 **Subject - Security in Computing** **Date: 10-01-24**
Class – TYBSCIT **Sem - VI**

PRACTICAL NO 1

AIM: CONFIGURE ROUTERS

a. OSPF MD5 authentication
b. NTP
c. to log messages to the SYSLOG server
d. to support SSH connections.

➢ **Topology Diagram**



Roll No: IT21036 **Subject - Security in Computing** **Date: 10-01-24**
Class – TYBSCIT **Sem - VI**

➢ Assigning IP Addresses

1. NTPServer



2. SYSLOG Server



3. PC-0



4. Router 0



5. Router 1



6. Router 2



- **<u>Displaying IPAddress Details of Routers</u>**

1. Router 0

```
R0>show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol

GigabitEthernet0/0     192.168.1.1     YES manual up                    up

GigabitEthernet0/1     unassigned      YES unset  administratively down down

Serial0/0/0            10.1.1.1        YES manual up                    up

Serial0/0/1            unassigned      YES unset  administratively down down

Vlan1                  unassigned      YES unset  administratively down down
```

```
R1>show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol

GigabitEthernet0/0     unassigned      YES unset  administratively down down

GigabitEthernet0/1     unassigned      YES unset  administratively down down

Serial0/0/0            10.1.1.2        YES manual up                    up

Serial0/0/1            10.2.2.2        YES manual up                    up

Vlan1                  unassigned      YES unset  administratively down down
```

3. Router 2

```
R2>show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol

GigabitEthernet0/0     192.168.3.1     YES manual up                    up

GigabitEthernet0/1     unassigned      YES unset  administratively down down

Serial0/0/0            10.2.2.1        YES manual up                    up

Serial0/0/1            unassigned      YES unset  administratively down down

Vlan1                  unassigned      YES unset  administratively down down
```

- **<u>Configure OSPF on routes</u>**

1. Router 0




Router1
Physical
Config
CLI
IOS Command Line Interface
R1>en
R1#config t
Enter configuration commands, one per line. End with CNTL/Z.
R1(config)#router ospf 1
R1(config-router)#network 10.1.1.0 0.0.0.3 area 0
R1(config-router)#network 10.2.2.0 0.0.0.3 area 0
R1(config-router)#^Z
R1#
%SYS-5-CONFIG_I: Configured from console by console
R1#exit

3. Router 2


Router2
Physical
Config
CLI
IOS Command Line Interface
R2>en
R2#config t
Enter configuration commands, one per line. End with CNTL/Z.
R2(config)#router ospf 1
R2(config-router)#network 192.168.3.0 0.0.0.255 area 0
R2(config-router)#network 10.2.2.0 0.0.0.3 area 0
R2(config-router)#^Z
R2#
%SYS-5-CONFIG_I: Configured from console by console
R2#exit

➢ Displaying routing table of routers

1. Router 0



2. Router 1



3. Router 2


Router2
Physical
Config
CLI
IOS Command Line Interface
R2>show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
* - candidate default, U - per-user static route, o - ODR
P - periodic downloaded static route
Gateway of last resort is not set
10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
O 10.1.1.0/30 [110/128] via 10.2.2.2, 00:11:51, Serial0/0/0
C 10.2.2.0/30 is directly connected, Serial0/0/0
L 10.2.2.1/32 is directly connected, Serial0/0/0
O 192.168.1.0/24 [110/129] via 10.2.2.2, 00:11:51, Serial0/0/0
192.168.3.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.3.0/24 is directly connected, GigabitEthernet0/0
L 192.168.3.1/32 is directly connected, GigabitEthernet0/0

A. OSPF MD5 authentication

➢ **Configure OSPF MD5 authentication on Routers**

1. Router 0



2. Router 1



3. Router 2



- **Configure the MD5 key for all the routers**

1. Router 0



2. Router 1



3. Router 2



- **Displaying OSPF details of all the routers**

1. Router 0



2. Router 1




Router1
Physical
Config
CLI
IOS Command Line Interface
R1>show ip ospf interface Serial0/0/1
Serial0/0/1 is up, line protocol is up
Internet address is 10.2.2.2/30, Area 0
Process ID 1, Router ID 10.2.2.2, Network Type POINT-TO-POINT, Cost: 64
Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
No designated router on this network
No backup designated router on this network
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
Hello due in 00:00:05
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1 , Adjacent neighbor count is 1
Adjacent with neighbor 192.168.3.1
Suppress hello for 0 neighbor(s)
Message digest authentication enabled
Youngest key id is 1

3. Router 2


Router2
Physical
Config
CLI
IOS Command Line Interface
R2>show ip ospf interface Serial0/0/0
Serial0/0/0 is up, line protocol is up
Internet address is 10.2.2.1/30, Area 0
Process ID 1, Router ID 192.168.3.1, Network Type POINT-TO-POINT, Cost: 64
Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
No designated router on this network
No backup designated router on this network
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
Hello due in 00:00:05
Index 2/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1 , Adjacent neighbor count is 1
Adjacent with neighbor 10.2.2.2
Suppress hello for 0 neighbor(s)
Message digest authentication enabled
Youngest key id is 1

B. NTP

- **Check Clock Time in the routers**

1. Router 0

```
R0>show clock
*0:49:14.954 UTC Mon Mar 1 1993
R0>
```

2. Router 1

```
R1>show clock
*0:51:40.343 UTC Mon Mar 1 1993
R1>
```

3. Router 2

```
R2>show clock
*0:53:5.140 UTC Mon Mar 1 1993
R2>
```

- **Configure NTP Server**



➢ Configure NTP Client

1. Router 0



2. Router 1



3. Router 2



- **Configure NTP authentication and to timestamp log messages on the routers**

1. Router 0



2. Router 1



3. Router 2



➢ **Check updated UTC Clock Time in the routers**

1. Router 0

```
R0>show clock
*12:30:36.142 UTC Thu Jan 11 2024
R0>
```

2. Router 1

```
R1>show clock
*12:30:54.211 UTC Thu Jan 11 2024
R1>
```

3. Router 2

```
R2>show clock
*12:31:2.851 UTC Thu Jan 11 2024
R2>
```

C. SYSLOG

➢ **Configure Routers to Log Messages to the SYSLOG Server**

1. Router 0



2. Router 1



- **Verify logging configuration on Routers**

1. Router 0




Router1
Physical
Config
CLI
R1#show logging
Syslog logging: enabled (0 messages dropped, 0 messages rate-limited,
0 flushes, 0 overruns, xml disabled, filtering disabled)
No Active Message Discriminator.
No Inactive Message Discriminator.
Console logging: level debugging, 30 messages logged, xml disabled,
filtering disabled
Monitor logging: level debugging, 0 messages logged, xml disabled,
filtering disabled
Buffer logging: disabled, xml disabled,
filtering disabled
Logging Exception size (4096 bytes)
Count and timestamp logging messages: disabled
Persistent logging: disabled
No active filter modules.
ESM: 0 messages dropped
Trap logging: level informational, 30 message lines logged
Logging to 192.168.1.6 (udp port 514, audit disabled,
authentication disabled, encryption disabled, link up),
2 message lines logged,
0 message lines rate-limited,
0 message lines dropped-by-MD,
xml disabled, sequence number disabled
filtering disabled

3. Router 2


Router2
Physical
Config
CLI
R2#show logging
Syslog logging: enabled (0 messages dropped, 0 messages rate-limited,
0 flushes, 0 overruns, xml disabled, filtering disabled)
No Active Message Discriminator.
No Inactive Message Discriminator.
Console logging: level debugging, 17 messages logged, xml disabled,
filtering disabled
Monitor logging: level debugging, 0 messages logged, xml disabled,
filtering disabled
Buffer logging: disabled, xml disabled,
filtering disabled
Logging Exception size (4096 bytes)
Count and timestamp logging messages: disabled
Persistent logging: disabled
No active filter modules.
ESM: 0 messages dropped
Trap logging: level informational, 17 message lines logged
Logging to 192.168.1.6 (udp port 514, audit disabled,
authentication disabled, encryption disabled, link up),
2 message lines logged,
0 message lines rate-limited,
0 message lines dropped-by-MD,
xml disabled, sequence number disabled
filtering disabled

- **Examine logs of the SYSLOG Server**



D. SSH

- **Configure SSH on R2**

Router 2





- **Connect to R2 using telnet and SSH on PC**



Roll No: IT21036 **Subject - Security in Computing** **Date: 10-01-24**
Class – TYBSCIT **Sem - VI**