


SQL Injection Attack

Name: Alizeh Jafri


Task 1

Task 1.1:

I opened the website with the URL: <http://www.SEEDLabSQLInjection.com> and typed the Username: admin '# to be able to access the admin login page



I successfully logged in:




The screenshot shows a web browser window with the title 'SQLi Lab'. The address bar displays the URL 'www.seedlabsqlinjection.com/unsafe_home.php?username=...'. The page content features a green header bar, followed by a large heading 'User Details' and a table of user information.


Username	EId	Salary	Birthday	SSN	Nickname
Alice	10000	20000	9/20	10211002	
Boby	20000	30000	4/20	10213352	
Ryan	30000	50000	4/10	98993524	

Task 1.2

When I tried to write two statements it did not work.



The screen shot below shows the syntax error I received:




After some research regarding the MySQL mechanism, I concluded the reason related to the API function. Therefore, according to MySQL website, the API functions `mysql_query` and `mysql_real_query` does not set a flag connection which is essential for activating different multi queries in the server. In order to reduce the likeliness of accidental SQL injection attacks, an extra API call is used for various statements. A hacker can try to add the statements like `DROP DATABASE`. And if that attacker becomes successful in adding the SQL to the statement, but the `mysql_multi_queries` will not be used and the second malicious SQL statement will not be executed.

Task 2


Task 2.1

This is how the Alice's profile looks:




I edited the Alice's Salary from 20000 to 60000. For that I typed in the syntax:

Ali', Salary = '60000' WHERE eid = '20000' #




The updated Alice's profile is shown in the screen shot below:



Task 2.2


The screen shot below shows the query I used to Update Bobby's salary from Alice's:



I updated the Bobby's Salary from 20000 to 1. For that I typed in the syntax:

Bob', Salary = '1' WHERE eid = '20000'# as shown below:

The user details of Alice's and Bobby's updated profiles are shown in which Bobby's salary has been reduced to '1' which is shown in the screen shot below:




The screenshot shows a web browser window with the address bar displaying `www.seedlabsqlinjection.com/unsafe_home.php`. The page has a green header with the **SEEDLABS** logo, [Home](#), [Edit Profile](#), and a [Logout](#) button. The main content area is titled **User Details** and contains a table with the following data:


Username	EId	Salary	Birthday	SSN	Nickname	Email	Address	Ph. Number
Alice	10000	60000	9/20	10211002	Ali			
Boby	20000	1	4/20	10213352	Bob			
Ryan	30000	50000	4/10	98993524				
Samy	40000	90000	1/11	32193525				
Ted	50000	110000	11/3	32111111				
Admin	99999	400000	3/5	43254314				

Task 2.3

I wrote (Bob, Password = '2e51cf3f58377b8a687d49b960a58dfc677f0ad' WHERE eid ='20000'#)



Boby's password is now changed to the password 'attacker'



I successfully logged into Bobby's page:

Most Visited SEED Labs Sites for Labs

SEEDLABS Home Edit Profile


Bobby Profile

Key	Value
Employee ID	20000
Salary	1
Birth	4/20
SSN	10213352
NickName	Bob
Email	
Address	
Phone Number	

Copyright © SEED LABS


Task 3

I opened the terminal and typed the following codes as shown below:



```
Terminal File Edit View Search Terminal Help
[10/01/19]seed@VM:~$ su root
Password:
root@VM:/home/seed# cd /var/www/SQLInjection/
root@VM:/var/www/SQLInjection# gedit unsafe_home.php
```


unsafe_home.php file opened. And I also opened the safe_home.php. I copied the highlighted part from safe_home.php:



```
safe_home.php (/var/www/SQLInjection) - gedit
File Edit View Search Tools Documents Help
Open Save
*unsafe_home.php x safe_home.php x
}
// create a connection
$conn = getDB();
// Sql query to authenticate the user
$sql = $conn->prepare("SELECT id, name, eid, salary, birth, ssn,
phoneNumber, address, email,nickname,Password
FROM credential
WHERE name= ? and Password= ?");
$sql->bind_param("ss", $input_uname, $hashed_pwd);
$sql->execute();
$sql->bind_result($id, $name, $eid, $salary, $birth, $ssn, $phoneNumber,
$address, $email, $nickname, $pwd);
$sql->fetch();
$sql->close();

if($id!=""){
    // If id exists that means user exists and is successfully authenticated
    drawLayout($id,$name,$eid,$salary,$birth,$ssn,$pwd,$nickname,$email,
$address,$phoneNumber);
}else{
    // User authentication failed
    echo "</div>";
    echo "</nav>";
    echo "<div class='container text-center'>";
    echo "<div class='alert alert-danger'>";
    echo "The account information your provide does not exist.";
}
```

Then I replaced it with the highlighted part in unsafe_home.php file.



```
*unsafe_home.php (/var/www/SQLInjection) - gedit
File Edit View Search Tools Documents Help


Open Save

    die('There was an error running the query [' . $conn->error . ']\n');
    echo "</div>";
}
/* convert the select return result into array type */
$return_arr = array();
while($row = $result->fetch_assoc()){
    array_push($return_arr,$row);
}

/* convert the array type to json format and read out*/
$json_str = json_encode($return_arr);
$json_a = json_decode($json_str,true);
$id = $json_a[0]['id'];
$name = $json_a[0]['name'];
$eid = $json_a[0]['eid'];
$salary = $json_a[0]['salary'];
$birth = $json_a[0]['birth'];
$ssn = $json_a[0]['ssn'];
$phoneNumber = $json_a[0]['phoneNumber'];
$address = $json_a[0]['address'];
$email = $json_a[0]['email'];
$pwd = $json_a[0]['Password'];
$nickname = $json_a[0]['nickname'];
if($id!=""){
    // If id exists that means user exists and is successfully authenticated
    drawLayout($id,$name,$eid,$salary,$birth,$ssn,$pwd,$nickname,$email,
$address,$phoneNumber);
}else{
    // If id does not exist that means user does not exist
}
return $conn;
}

PHP Tab Width: 8 Ln 102, Col 42 INS
```

I even tried commenting some lines of codes with '//' back slashes. Both ways it works.




```
unsafe_home.php x safe_home.php x

    echo "</div>";
}
return $conn;
}


// create a connection
$conn = getDB();
// Sql query to authenticate the user
# $sql = "SELECT id, name, eid, salary, birth, ssn, phoneNumber, address,
email,nickname,Password
# FROM credential
#WHERE name= '$input_uname' and Password='$hashed_pwd'";
# if (!$result = $conn->query($sql)) {
# echo "</div>";
# echo "</nav>";
# echo "<div class='container text-center'>";
# die('There was an error running the query [' . $conn->error . ']\n');
# echo "</div>";
// }
// $conn = getDB();
// Sql query to authenticate the user
$sql = $conn->prepare("SELECT id, name, eid, salary, birth, ssn,
phoneNumber, address, email,nickname,Password
FROM credential
WHERE name= ? and Password= ?");
$sql->bind_param("ss", $input_uname, $hashed_pwd);
$sql->execute();

PHP Tab Width: 8 Ln 85, Col 76 INS
```

I entered admin'# and logged in:




I got the message shown in the screen shot below, which means that the injection will not work anymore.



Lastly, after the prepared statement mechanism was used, the SQL injection was fixed.

Also, When I entered 'admin' with the password 'seedadmin' as given in the lab task, I got:



After I clicked login the page which was viewed is shown below:

