With the support of the Erasmus+ Programme of the European Union

EMJMD GENIAL

GREEN NETWORKING & CLOUD COMPUTING

UNIVERSITÉ DE LORRAINE

LEEDS BECKETT UNIVERSITY

LULEÅ UNIVERSITY OF TECHNOLOGY

AI for Link Adaptation and Energy Prediction in Realistic 5G Networks

Alka Valiparambil Narendran

Supervisor : Prof. Evgeny Osipov

Collaboration : Effnet AB

Table of contents

01

Introduction

Introduction

5G is complex—dense networks, low latency, high energy demands.

Challenges

- Complex scenarios that are hard to model
- Gathering even simple data is difficult
- Legacy networks not designed for AI, need to rethink/rebuild



Problem Statement

Despite the potential of Artificial Intelligence, its application to critical 5G operational components—specifically, predictive link adaptation (MCS selection) under realistic conditions and granular energy consumption forecasting—remains underdeveloped. This research addresses this gap by developing and evaluating AI models for each of these distinct tasks, aiming to demonstrate their individual efficacy and pave the way for more intelligent network management.

Research Aim

To investigate and demonstrate the capabilities of Artificial Intelligence in:

- Optimizing link adaptation through predictive MCS selection in realistic 5G network simulations.
- Accurately forecasting energy consumption of 5G base stations using real-world data.
- Ultimately, to build a comprehensive perspective on AI-driven 5G network optimization, informing practical applications with Effnet AB.

Research Objectives

Data Extraction & Modelling

RO1: **Identify and extract relevant KPIs** from 5G-LENA simulations, including SNR, CQI, transmission power, and buffer size, to support AI-based MCS prediction.

RO2: Develop and evaluate an **AI model to predict MCS values** based on historical network states, targeting im proved robustness in the absence of frequent CSI updates.

RO3: Design a separate **AI model to estimate energy consumption** under varying transmission parameters using an external dataset.

Analysis & Validation

Practical Relevance

Research Objectives

Data Extraction & Modelling

Analysis & Validation

RO4: Analyze and **compare energy efficiency patterns** derived from the energy model, highlighting trade-offs with performance.

RO5: Integrate findings to formulate **practical recommendations** for optimizing 5G link adaptation strategies with sustainability considerations.

Practical Relevance

Research Objectives

Data Extraction & Modelling

Analysis & Validation

Practical Relevance

RO6: **Investigate the practical utility** of AI-driven optimization techniques for 5G systems, demonstrated within the 5G-LENA simulation framework, and identify path ways for their integration or enhancement in alignment with the objectives of industry partner Effnet.

SDG


9
INDUSTRY, INNOVATION
AND INFRASTRUCTURE


11
SUSTAINABLE CITIES
AND COMMUNITIES


13
CLIMATE
ACTION

02

Link Adaptation

Link Adaptation

Adjusts modulation and coding scheme (MCS) based on channel quality

Aims to maximize throughput while keeping error rate acceptable

Decision made at the gNB, based on UE feedback (SINR, CQI, HARQ)



Traditional Approaches

AMC (Adaptive Modulation and Coding)

Inner Loop Link Adaptation (ILLA)

Uses instantaneous SINR or CQI feedback from the receiver to select the best Modulation and Coding Scheme (MCS) based on a predefined lookup table

Outer Loop Link Adaptation (OLLA)

Adjusts an SINR offset dynamically using ACK/NACK feedback to ensure the target Block Error Rate (BLER) is met. Works on top of ILLA.

Hybrid Automatic Repeat Request (HARQ) with AMC

Retransmits failed packets with additional coding redundancy (incremental redundancy or chase combining) while also adapting MCS dynamically to improve reliability.

Link Adaptation– Traditional

Excessive Feedback Dependency

Reactive Adjustment

Lack of Predictive Insight

AI Optimisation for Link Adaptation

Direct vs Indirect MCS Prediction[1]

- Direct: Models predict MCS from features like SINR, CQI [1][2]
- Indirect: First predict channel metrics (e.g., SNR), then map to MCS

Temporal Models Perform Better[3]

- Recurrent models (e.g., LSTM, GRU) outperform CNNs and MLPs in dynamic channels
- These models capture short-term channel memory better, especially in mobile scenarios

[1] M. Elwekeil, S. Jiang, T. Wang and S. Zhang, "Deep Convolutional Neural Networks for Link Adaptations in MIMO-OFDM Wireless Systems," in IEEE Wireless Communications Letters, vol. 8, no. 3, pp. 665-668, June 2019, doi: 10.1109/LWC.2018.2881978.
[2] J.-E. Oh, A.-M. Jo, and E.-R. Jeong, 'MCS Selection Based on Convolutional Neural Network in Mobile Communication Environments', in *2023 Fourteenth International Conference on Ubiquitous and Future Networks (ICUFN)*, Jul. 2023, pp. 684–686. doi: 10.1109/ICUFN57995.2023.10201063.
[3]O. Stenhammar, G. Fodor, and C. Fischione, 'A Comparison of Neural Networks for Wireless Channel Prediction', *IEEE Wireless Communications*, vol. 31, no. 3, pp. 235–241, Jun. 2024, doi: 10.1109/MWC.006.2300140.

AI Optimisation for Link Adaptation

Simulation Data Dominates[1]

- Due to lack of real-world datasets, most research uses simulators (NYUSIM, MATLAB, custom tools)
- Realism varies widely: many simplify SINR traces or skip HARQ logic

Single-Direction Traffic

- Most studies target downlink, since MCS is gNB-controlled
- Uplink-focused works are rarer; datasets are harder to obtain

[1] M. Elwekeil, S. Jiang, T. Wang and S. Zhang, "Deep Convolutional Neural Networks for Link Adaptations in MIMO-OFDM Wireless Systems," in IEEE Wireless Communications Letters, vol. 8, no. 3, pp. 665-668, June 2019, doi: 10.1109/LWC.2018.2881978.
[2] J.-E. Oh, A.-M. Jo, and E.-R. Jeong, 'MCS Selection Based on Convolutional Neural Network in Mobile Communication Environments', in *2023 Fourteenth International Conference on Ubiquitous and Future Networks (ICUFN)*, Jul. 2023, pp. 684–686. doi: 10.1109/ICUFN57995.2023.10201063.
[3]O. Stenhammar, G. Fodor, and C. Fischione, 'A Comparison of Neural Networks for Wireless Channel Prediction', *IEEE Wireless Communications*, vol. 31, no. 3, pp. 235–241, Jun. 2024, doi: 10.1109/MWC.006.2300140.

Simulation

1 gNB, 4 Ues
3GPP UMa Channel Model (NLOS)
Frequency: 30.5 GHz
Bandwidth: 100 MHz
Random Walk mobility
Gaming traffic over UDP
Logged: SINR, CQI, MCS, HARQ
10 seeds × 3 runs → ~21,000 samples



Fig. 1. Usage scenarios of IMT for 2020 and beyond [3].

Data Preprocessing

Simulation Output

```
NrDlMacStats.txt (MCS assignments)
DlDataSinr.txt (downlink SINR events)
RxedGnbMacCtrlMsgsTrace.txt (CQI reports)
```

	time	mcs	sinr	RNTI	run	cqi_count
0	0.0765	26	33.4369	seed100_run1_rnti_2	seed100_run1	1.0
1	0.1585	26	32.6890	seed100_run1_rnti_2	seed100_run1	1.0
2	0.2145	26	33.4499	seed100_run1_rnti_2	seed100_run1	1.0
3	0.2745	26	33.1776	seed100_run1_rnti_2	seed100_run1	1.0
4	0.3265	26	34.2603	seed100_run1_rnti_2	seed100_run1	1.0

70% Training
30% Validation


SINR vs MCS
MCS
SINR (dB)
0
5
10
15
20
25
−30
−20
−10
0
10
20
30
40


Heat-map of MCS frequency vs. SINR
SINR (dB) bin center
MCS class
Count
39.2
33.6
28.1
22.5
16.9
11.4
5.8
0.2
-5.3
-10.9
-16.4
-22.0
-27.6
0
2
4
6
8
11
13
15
18
20
22
24
26
28
2000
1750
1500
1250
1000
750
500
250
0


Correlation Heatmap: MCS, SINR, CQI Count
mcs
sinr
cqi_count
1.00
0.84
-0.35
0.84
1.00
-0.64
-0.35
-0.64
1.00
1.0
0.8
0.6
0.4
0.2
0.0
−0.2
−0.4
−0.6

AI Modelling

Input

Sequences of SINR (and CQI, in some versions), with T = 10

Output

Next MCS

Models

CNN (baseline – sliding window of SINR)
CNN + CQI (adds feedback)
CNN + CQI + Masking (simulates missing feedback)
LSTM (captures longer temporal dependencies)

Training Details

Optimizer: Adagrad
Loss: Cross-Entropy
Epochs: 50.
Handled Class Imbalance: Weighted Random Sampler.

Hyperparameter Tuning: Basic sweep performed (12 configs for CNN, identified best params like 128 filters, 8D RNTI embedding, LR 0.005 leading to ~53.5% Acc).

Result

Model	Input Features	Architecture	Accuracy
CNN	SINR only	Conv1D + Dense	52.3%
CNN + CQI	SINR + CQI	Conv1D + Dense	53.7%
CNN + Masking	SINR + CQI + mask	Conv1D + Dropout	54.1%
LSTM	SINR + CQI	LSTM layers	55.1%



CNN



LSTM

03

Energy Prediction

Literature Review

- Energy Optimization are Often Reactive & Rule -Based
- AI Models Are Rare – And Often Use Synthetic or Simplified Data
- Underuse of Temporal and Contextual Features

Dataset

Source: dataset that was provided by the international telecommunication union (ITU) in 2023 as part of a global challenge[1]

Size: 92,629 entries from 1,019 base stations

Granularity: Hourly logs

Key Features

- Energy (Watt-hours)
- Load (traffic load)
- TXpower (transmission power)
- ESMODE (energy-saving mode)
- BSID
- Timestamp

	Time	BS	Energy	load	ESMODE	TXpower
0	20230101 010000	B_0	64.275037	0.487936	0.0	7.101719
1	20230101 020000	B_0	55.904335	0.344468	0.0	7.101719
2	20230101 030000	B_0	57.698057	0.193766	0.0	7.101719
3	20230101 040000	B_0	55.156951	0.222383	0.0	7.101719
4	20230101 050000	B_0	56.053812	0.175436	0.0	7.101719

[1]'5G-Energy consumption Dataset'. Accessed: May 20, 2025. [Online]. Available: https://www.kaggle.com/datasets/nadiatriki/5g-energy-consumption-dataset



Energy vs Load, colored by BS
100
80
60
40
20
0
Energy
0.0
0.2
0.4
0.6
0.8
1.0
load



Correction Matrix
Energy
load
TXpower
hour
weekday
is_weekend
1.00 0.64 0.45 0.20 0.01 0.01
0.64 1.00 0.20 0.32 0.04 0.02
0.45 0.20 1.00 0.00 -0.07 -0.03
0.20 0.32 0.00 1.00 0.02 0.02
0.01 0.04 -0.07 0.02 1.00 0.78
0.01 0.02 -0.03 0.02 0.78 1.00
1.0
0.8
0.6
0.4
0.2
0.0



Energy vs Time for BS: B_0
Energy Consumption
90
85
80
75
70
65
60
55
2023-01-01
2023-01-02
2023-01-03
2023-01-04
2023-01-05
2023-01-06
2023-01-07
2023-01-08
Time

AI Modelling

Input	Load, TXpower, ESMODE Time-based features (hour, weekday/weekend) Encoded Base Station IDs (one-hot or learned embeddings)
Target	Hourly energy consumption of base stations
Loss Function	Mean Absolute Percentage Error (MAPE) $\mathrm{MAPE} = \frac{\sum_{i=1}^{n} \lvert y_i - \widehat{y}_i \rvert}{\sum_{i=1}^{n} \lvert y_i \rvert},$

AI Modelling



(a) Deep learning model

(b) Training and inference phase

Fig. 2. Model Architecture: Our model is a two-layer Feed Forward Network. In the training phase, random masking is applied to randomly reassign BSIDs to 'Unknown BS'.

Models

Linear Regression
3-layer Neural Network
Masked Neural Network

Chen, Tingwei, et al. "Modelling the 5G Energy Consumption using Real-world Data: Energy Fingerprint is All You Need." *arXiv preprint arXiv:2406.16929* (2024).

Result


MAPE Comparison of Models
MAPE (%)
35.01
17.70
5.74
0
5
10
15
20
25
30
35
Linear Regression
NN
NN with Mask

04

Analysis

Analysis

- **Link Adaptation:** AI (LSTMs/tuned CNNs) show promise (~55% acc.) in learning temporal channel dynamics for MCS prediction, outperforming simpler methods.
- **Energy Prediction:** Advanced AI (Masked NN) achieved high accuracy (5.5% MAPE) in forecasting real-world BS energy use.
- Though not yet integrated, these findings lay a **foundation for dual-objective (Performance & Sustainability) optimization.**



Analysis

- Realistic and useful 5g Dataset is difficult to acquire
- **Link Adaptation** :
    - Temporal models are crucial
    - Data imbalance is a real-world challenge.
- Energy Modelling:

- AI models can learn from **structure in data**, but results depend heavily on data realism and balance.

05

FutureWork

Future Work

- **Explore temporal architectures** like GRU, MiniROCKET, and Hyperdimensional Computing (HDC) to improve MCS prediction under volatile channel conditions
- **Simulate denser, more diverse network scenarios** to address MCS class imbalance and improve generalizability
- Use richer energy datasets with detailed BS configurations (e.g., antenna count, RU type, deployment mode)
- **Integrate** link adaptation with energy modeling, enabling joint optimization of throughput and consumption

06

Conclusion

To Conclude

- Have successfully developed and evaluated AI models for both **MCS prediction** (simulation-based) and **energy estimation** (real-world data)
- Addressed key challenges in preprocessing, temporal modeling, and dataset realism
- All research objectives were successfully met
- This thesis demonstrates the potential of AI to support **smarter, greener 5G networks,** even when working with real-world complexity



References

1. Abubakar, A.I., Omeke, K.G., Ozturk, M., Hussain, S., and Imran, M.A. (2020). The role of artifi cial intelligence driven 5g networks in covid-19 out break: Opportunities, challenges, and future outlook. Frontiers in Communications and Networks, 1. doi: 10.3389/frcmn.2020.575065.
2. Balasubramanian, B. et al. (2021). Ric: A ran intel ligent controller platform for ai-enabled cellular net works. IEEE Internet Computing, 25(2), 7–17. doi: 10.1109/MIC.2021.3062487.
3. Chen, T., Wang, Y., Chen, H., Zhao, Z., Li, X., Piovesan, N., Zhu, G., and Shi, Q. (2024). Modelling the 5g energy consumption using real-world data: Energy fingerprint is all you need. arXiv preprint arXiv:2406.16929. Elgabroun, H.M.A.I. (2019).
4. Machine Learning Technique for Uplink Link Adaptation in 5G NR RAN at Millime ter Wave Frequencies. Master's thesis, Lund University. Http://lup.lub.lu.se/student-papers/record/9118249.
5. Gigayasa Wireless (2025). Link Adaptation — 5G Toolkit R24a Documentation. Accessed March 4, 2025. doi:
6. Herath, J.D., Seetharam, A., and Ramesh, A. (2019). A deep learning model for wireless channel qual ity prediction. In ICC 2019- IEEE Interna tional Conference on Communications, 1–6. IEEE, Shanghai, China. doi:10.1109/ICC.2019.8761934. Https://ieeexplore.ieee.org/document/8761934/.
7. Kojima, S., Maruta, K., and Ahn, C.J. (2019). Adaptive modulation and coding using neural net work based snr estimation. IEEE Access, 7, 183545–183553. doi:10.1109/ACCESS.2019.2946973. Https://ieeexplore.ieee.org/document/8865038/.
8. Lee, H., Jang, Y., Song, J., and Yeon, H. (2021). O ran ai/ml workflow implementation of personalized net work optimization via reinforcement learning. In 2021 IEEE Globecom Workshops (GC Wkshps), 1–6. doi: 10.1109/GCWkshps52748.2021.9681936.
9. Li, Y., Xu, Y., Li, G., Wang, X., Xu, Y., Liu, S., and Yue, L. (2024). Turning adversity into advantage: Robust mcs selection utilizing the uncertainty of channel prediction neural networks. IEEE Wireless Communications Letters, 13(10), 2632–2636. doi:10.1109/LWC.2024.3393939. Https://ieeexplore.ieee.org/abstract/document/10654736.
10. Nadia Triki (2025). 5g-energy consumption dataset. Https://www.kaggle.com/datasets/nadiatriki/5g energy-consumption-dataset (Accessed: May 20, 2025). Norolahi, J. and Azmi, P. (2023). A machine learning based algorithm for joint improvement of power control, link adaptation, and capacity in beyond 5g communica tion systems. Telecommunication Systems, 83(4), 323 337. doi:10.1007/s11235-023-01017-1.
11. Oh, J.E., Jo, A.M., and Jeong, E.R. (2023). Mcs selection based on convolutional neural network in mobile communication environments. In 2023 Fourteenth International Conference on Ubiquitous and Future Networks (ICUFN), 684 686. doi:10.1109/ICUFN57995.2023.10201063. Https://ieeexplore.ieee.org/abstract/document/10201063.

References

12. Parsa, A., Moghim, N., and Salavati, P. (2022). Joint power allocation and mcs selection for energy-efficient link adaptation: A deep reinforcement learning ap proach. Computer Networks, 218, 109386. 10.1016/j.comnet.2022.109386. doi:
13. Rezazadeh, F. et al. (2023). On the specialization of fdrl agents for scalable and distributed 6g ran slicing orches tration. IEEE Transactions on Vehicular Technology, 72(3), 3473–3487. doi:10.1109/TVT.2022.3218158.
14. Sahu, R. and Sahu, V. (2024). An energy-efficient algo rithm for resource allocation in h-cran (ee h-cram) for 5g networks. Wireless Personal Communications, 138(3), 1483–1499. doi:10.1007/s11277-024-11545-x.
15. Seeram, S.S.S.G.S. (2022). Link adaptation in 5G Net works: Reinforcement Learning framework based ap proach. Master's thesis, KTH Royal Institute of Tech nology. Stenhammar,
16. O., Fodor, G., and Fischione, C. (2024). A comparison of neural networks for wireless channel prediction. IEEE Wireless Communications, 31(3), 235 241. doi:10.1109/MWC.006.2300140.
17. Tran, N.B.L. et al. (2024). Ai-driven rapps for reducing radio access network interference in real world 5g deployment. In IEEE INFOCOM 2024- IEEE Conference on Computer Communications Workshops (INFOCOM WKSHPS), 1–2. 10.1109/INFOCOMWKSHPS61880.2024.10620743.
18. Tsipi, L., Karavolos, M., Papaioannou, G., Volakaki, M., and Vouyioukas, D. (2024). Machine networks. learning-based methods for mcs prediction in 5g Telecommunication Systems, 86(4), 705–728. doi:10.1007/s11235-024-01158-x. Https://link.springer.com/article/10.1007/s11235-024 01158-x.
19. Varshney, R., Gangal, C., Sharique, M., and Ansari, M.S. (2023). Deep learning based wireless channel prediction: 5g scenario. Procedia Computer Science, 218, 2626–2635. doi:10.1016/j.procs.2023.01.236. Https://www.sciencedirect.com/science/article/pii/S187705092300 2363.
20. Yun, W., Hong, S., and Jeong, E. (2024). Gru based mcs selection for uav communication in 5g en vironment. In 2024 Fifteenth International Confer ence on Ubiquitous and Future Networks (ICUFN), 472–475. doi:10.1109/ICUFN61752.2024.10625063. Https://ieeexplore.ieee.org/document/10625063.
21. Zhang, C.K., Hossain, E., and Kim, D.I. (2018). Deep convolutional neural networks for link adaptations in mimo-ofdm wireless systems. IEEE Transactions on Wireless Communications, 17(4), 2621–2633. doi:10.1109/TWC.2018.2804958. Https://ieeexplore.ieee.org/document/8540019.
22. Zhao, Z., Feng, C., Yang, H.H., and Luo, X. (2020). Federated-learning-enabled intelligent fog radio access networks: Fundamental theory, key techniques, and fu ture trends. IEEE Wireless Communications, 27(2), 22 28. doi:10.1109/MWC.001.1900370

Thanks ☺

Questions???

With the support of the Erasmus+ Programme of the European Union

EMJMD GENIAL

GREEN NETWORKING & CLOUD COMPUTING

UNIVERSITÉ DE LORRAINE

LEEDS BECKETT UNIVERSITY

LULEÅ UNIVERSITY OF TECHNOLOGY

Appendix A1

Table A.1. Comparison of Datasets in Recent MCS/Channel Prediction Studies

Study	**Data Method**	**Scenario**	**Realism**	**Tool / Company**
Varshney et al. (2023)	NYUSIM-based mmWave sim	28 GHz Urban Macro	High	NYUSIM / NYU
Zhang et al. (2018)	MIMO-OFDM, SNR sweep	Synthetic system-level	Medium-Low	–
Herath et al. (2019)	Real RSS from 5 networks	LTE, WiFi, Zigbee, etc.	Real-world	CRAWDAD / G5
Li et al. (2024)	RSSI via spectrum analyzer	2.4 GHz RSSI trace	Real-world	Spectrum Analyzer
Seeram (2022)	MATLAB 5G testbed	SU-MIMO, mobility, HARQ	Medium-High	Huawei
Oh et al. (2023)	Rayleigh/Rician in MATLAB	5G NR-like setup	Medium	MATLAB/TensorFlow
Elgabroun (2019)	mmWave sim (UL)	28 GHz, walking UE	High	Ericsson tool
Stenhammar et al. (2024)	3GPP TDL-A model	2 GHz NLOS, mobile UE	Medium-High	3GPP / –
Tsipi et al. (2024)	Ray-tracing + LTE overlay	Urban 2.1 GHz NSA	High	Altair FEKO
Yun et al. (2024)	5G NR sim, Rayleigh/Rician	UAV, 3.6 GHz, 100 MHz	Medium	MATLAB/TensorFlow

mcs	count
26	6965
28	4132
24	1677
0	1143
18	1030
22	968
13	880
20	674
6	658
15	610
8	577
11	529
4	439
2	436

Appendix B1