
Great Lakes



S = Superior M = Michigan H = Huron E = Erie O = Ontario

Lake	Volume $10^{12}\,\mathrm{m}^3$	Precip. $10^3\,\mathrm{m}^3/\mathrm{s}$	Watershed $10^3\,\mathrm{m}^3/\mathrm{s}$	Evap. $10^3\,\mathrm{m}^3/\mathrm{s}$	Lake inflow $10^3\,\mathrm{m}^3/\mathrm{s}$	Lake outflow $10^3\,\mathrm{m}^3/\mathrm{s}$	Other outflow $10^3\,\mathrm{m}^3/\mathrm{s}$
S	12.10	+2.00	+1.50	−1.40	—	−2.10 H	—
M	4.92	+1.50	+1.29	−1.10	+6.00 H +2.10 S	−7.60 H −6.00 M	−0.09 Chicago
H	3.54	+1.60	+1.40	−1.10	+7.60 M	−5.60 E	—
E	0.484	+0.70	+0.70	−0.70	+5.60 H	−6.30 O	—
O	1.64	+0.50	+1.00	−0.40	+6.30 E	—	−7.40 St. Lawrence

Volume balance

With t in seconds and each $v_i(t)$ in m^3

$$
\begin{aligned}
v_s'(t) &= (+2.00 + 1.50 - 1.40 - 2.10) \times 10^3 = 0 \\
v_m'(t) &= (+1.50 + 1.29 - 1.10 + 6.00 - 7.60 - 0.09) \times 10^3 = 0 \\
v_h'(t) &= (+1.60 + 1.40 - 1.10 + 2.10 + 7.60 - 6.00 - 5.60) \times 10^3 = 0 \\
v_e'(t) &= (+0.70 + 0.70 - 0.70 + 5.60 - 6.30) \times 10^3 = 0 \\
v_o'(t) &= (+0.50 + 1.00 - 0.40 + 6.30 - 7.40) \times 10^3 = 0
\end{aligned}
$$

Lake volumes are constant.

$$
\begin{aligned}
v_s &= 12.10 \times 10^{12}\,\mathrm{m}^3 \qquad v_m = 4.92 \times 10^{12}\,\mathrm{m}^3 \qquad v_h = 3.54 \times 10^{12}\,\mathrm{m}^3 \\
v_e &= 0.484 \times 10^{12}\,\mathrm{m}^3 \qquad v_o = 1.64 \times 10^{12}\,\mathrm{m}^3
\end{aligned}
$$

Pollutant balance in well-mixed lakes

- Lakes are well-mixed tanks with constant volume v in m^3.
- Pollutants do not evaporate. There is no external pollutant supply. Amounts change only through water transfers.
- Pollutant amount is $s(t)$ in kg and concentration is $s(t)/v$ in $\mathrm{kg/m}^3$. Initial concentration c_0 gives $s(0) = vc_0$.
- An inflow q in m^3/s carries its source lake's concentration c. Total water outflow q_{out} excludes evaporation and carries this lake's concentration $s(t)/v$.

Flow times concentration gives pollutant rate $(\cancel{\mathrm{m}^3}/\mathrm{s})(\mathrm{kg}/\cancel{\mathrm{m}^3}) = \mathrm{kg/s}$.

$$s'(t) = \underbrace{\sum_{\text{incoming flows}} qc}_{\text{pollutant inflow rate}} - \underbrace{q_{\mathrm{out}} s(t)/v}_{\text{pollutant outflow rate}}$$

Building the five-lake matrix

Use $\boldsymbol{s} = (s_s, s_m, s_h, s_e, s_o)$ with amounts in kg and time in seconds. Michigan receives pollutant from Huron and loses it to Huron and Chicago

$$s_m' = 10^{-9}\big(6.00 s_h/3.54 - (7.60 + 0.09) s_m/4.92\big)$$

Each row is a receiving lake's balance. Each column uses its source lake's volume.

$$\boxed{\boldsymbol{s}' = A\boldsymbol{s}} \qquad A = 10^{-9}\begin{pmatrix} -2.10/12.10 & 0 & 0 & 0 & 0 \\ 0 & -7.69/4.92 & 6.00/3.54 & 0 & 0 \\ 2.10/12.10 & 7.60/4.92 & -11.60/3.54 & 0 & 0 \\ 0 & 0 & 5.60/3.54 & -6.30/0.484 & 0 \\ 0 & 0 & 0 & 6.30/0.484 & -7.40/1.64 \end{pmatrix}$$

The constant matrix A has entries in s^{-1} since $(10^3\,\mathrm{m}^3/\mathrm{s})/(10^{12}\,\mathrm{m}^3) = 10^{-9}\,\mathrm{s}^{-1}$.

Estimation notes

- Historical starting values are principally 1953–2010 averages.
- Rounded teaching flows have been adjusted so every lake has zero net water flow. Transfers match at both ends.
- Michigan–Huron precipitation and evaporation were initially split by surface area, and runoff by land drainage area.
- Mackinac directional flows are assumptions. The final pair is 7600 toward Huron and 6000 toward Michigan, in m^3/s.
- Superior watershed inflow includes Long Lac and Ogoki. Huron includes Georgian Bay.
- The Huron–Erie route is one transfer with no Lake St. Clair tank. Erie–Ontario combines Niagara and Welland.
- Volumes are reference-level storage estimates.

Mackinac exchange estimate

The initial directional estimates used an assumed oscillating transport

$$Q(t) = 1100 + 20000 \sin(2\pi t/T) \qquad [Q] = \mathrm{m}^3/\mathrm{s}$$

Positive transport is toward Huron. Averaging over a complete cycle gives

$$\langle \max(Q(t), 0) \rangle \approx 6930 \ \mathrm{m}^3/\mathrm{s}$$
$$\langle \max(-Q(t), 0) \rangle \approx 5830 \ \mathrm{m}^3/\mathrm{s}$$

The final teaching values were adjusted to 7600 and 6000 m^3/s to balance the five-lake model. These are assumed directional averages, not measured long-term averages.

References

1. University of Michigan, Graham Sustainability Institute (2015).
   Great Lakes Water Budget, Figure 1.
   Historical water-budget components and connecting flows from NOAA-GLERL data.
2. U.S. Environmental Protection Agency.
   Physical Features of the Great Lakes.
   Surface and land drainage areas for the initial Michigan–Huron split.
3. NOAA Technical Memorandum GLERL-137, Table 3.
   Modified Great Lakes Hydrology Modeling System for Considering Simple Extreme Climates.
   Coordinated lake volumes, including Georgian Bay within Huron.

References for Mackinac exchange

4. Anderson and Schwab (2013).
Predicting the oscillating bi-directional exchange flow in the Straits of Mackinac.
Net transport near 1100 m^3/s and reversing exchange.
5. U.S. Environmental Protection Agency.
Biological, Chemical and Physical Relationships in the Straits of Mackinac.
Observed transport magnitudes motivating the assumed oscillation amplitude.
6. Anderson and Schwab (2017).
Meteorological influence on summertime baroclinic exchange in the Straits of Mackinac.
Simultaneous opposing flows during summer stratification.