


# ***CS200 - Computer Organization***

## **Dynamic Arrays & Structs**

Aravind Mohan

Allegheny College

September 14, 2021



# For starters!

- How is the **Dynamic** array differ from a Static array?
- What is Structs? and how can we use them?

# Variable Length Arrays

- Variable length arrays, use the space in the Stack and hence limited to store more data. It is often looked at an inefficient way of creating dynamic arrays.

# Dynamic Arrays

- Malloc based dynamic arrays, uses the space in Heap and hence can store data of larger size. It is the most efficient method to create a Dynamic array.
- Malloc is simply memory allocation procedure, that allocates blocks of memory based on programmers request.

# Dynamic Arrays

- A Pointer, can then be used to store, update, and read data elements from the memory. Malloc is part of the "stdlib" standard library.
- Look at "why.c" code in the src directory, to understand the difference.

# Variable Length Array - Code

```
#include <stdio.h>
#include <stdlib.h>
int main()
{
    int size;
    printf("Enter the size of the array:");
    scanf("%d", &size);
    /* This code below is for variable length array!*/

    int array[size];
    printf("#created array\n");

    for (int i=0; i < size; i++)
        array[i] = 10*i;
    for (int i=0; i < size; i++)
        printf("%d\t", array[i]);
    printf("\n");
}
```

# Variable Length Array - Code

```
Aravinds-MacBook-Pro:lecture12 amohan$ gcc why.c -o why.out
Aravinds-MacBook-Pro:lecture12 amohan$ ./why.out
Enter the size of the array:10000000
Segmentation fault: 11
Aravinds-MacBook-Pro:lecture12 amohan$
```

# Dynamic Array - Code

```
/* creating the memory block to store the dynamic array! */  
int *arr1 = (int *)malloc(size * sizeof(int));  
  
/* assigning values to each element in the array */  
for (int i = 0; i < size; i++)  
    *(arr1+i) = 10*i;  
  
/* printing values inside each element in the array */  
for (int i = 0; i < size; i++)  
    printf("%d\t", arr1[i]);  
  
printf("\n");  
free(arr1);
```



# Dynamic Array - Code

```
Aravinds-MacBook-Pro:lecture12 amohan$ gcc why.c -o why.out
Aravinds-MacBook-Pro:lecture12 amohan$ ./why.out
Enter the size of the array:10000000
```

```
9999520 9999530      9999540      9999550      9999560      9999579
9999580 9999590      9999600      9999610      9999620      9999639
9999640 9999650      9999660      9999670      9999680      9999699
9999700 9999710      9999720      9999730      9999740      9999759
9999760 9999770      9999780      9999790      9999800      9999819
9999820 9999830      9999840      9999850      9999860      9999879
9999880 9999890      9999900      9999910      9999920      9999939
9999940 9999950      9999960      9999970      9999980      9999999
Aravinds-MacBook-Pro:lecture12 amohan$
```

## 2 Dimensional Dynamic Array

- How can we create a 2 Dimmensional Dynamic Array using a Malloc?
- **Approach 1:** A single pointer is used to allocate the memory block to hold the entire 2D array.
- **Approach 2:** An array of pointers is created for the individual rows. The element in the array [pointer], is used to allocate a memory block to hold all the columns in the individual rows.

# Dynamic Array - Approach 1:

```
void approach1(){
    int rs = 4, cs = 4;
    int *arr = (int *)malloc(rs * cs * sizeof(int));
    int i, j, count = 0;

    for (i = 0; i < rs; i++) {
        for (j = 0; j < cs; j++) {
            *(arr + i*cs + j) = ++count;
            //printf("%d\t", arr2 + i*cs + j);
        }
        //printf("\n");
    }

    for (i = 0; i < rs; i++) {
        for (j = 0; j < cs; j++) {
            printf("%d\t", *(arr + i*cs + j));
        }
        printf("\n");
    }
    free(arr);
}
```

# Dynamic Array - Approach 2:

```
int r = 3, c = 4, i, j, count;
int *arr[r];
for (i=0; i<r; i++)
    arr[i] = (int *)malloc(c * sizeof(int));
// Note that arr[i][j] is same as *((arr+i)+j)
count = 0;
for (i = 0; i < r; i++)
    for (j = 0; j < c; j++)
        arr[i][j] = ++count; // Or *((arr+i)+j) = ++count

for (i = 0; i < r; i++)
    for (j = 0; j < c; j++)
        printf("%d ", arr[i][j]);

printf("\n");
```

- A datatype declaration that defines a grouped list of variables to be placed under one name in a block of memory.
- Think of it as a class without functions, just variables.
- **Struct** can hold any type of members including arrays.
- **Possible to:** create a pointer to Struct.
- Let us do some examples.

# Reading Assignment

**KR** - chapter 5 - [5.6 - 5.9]; chapter 06 - [6.1 - 6.4]

# Questions

- Feel free to ask your questions.
- I welcome you to stop by after class time to clarify any confusion related to class topics.
- Also please stop by during my office hours so we can spend some time together.