

Data Analytics


CS301

Dates and Times

Week 7: 24th Feb
Spring 2020
Oliver BONHAM-CARTER




42.7 percent of all statistics are
made up on the spot.



Seriously?!

Where in the Web?

Where in the Book?



- Note the chapter differences!
- Book:
 - Chap 13
- Web:
 - Chap 16
- Dates and Times with Lubridate

Dates and Times in R

- How do we deal when time or dates are a part of our analysis?
- How do we determine if our data spreads across a leap year?
- What if we measure our observations using a minute-by-minute time frame for some time frame? How can we focus on specific time details?





Libraries

```
# Remember. You do not need to  
reinstall these libraries each time  
you use them; only import them  
#install.packages("lubridate")  
library(lubridate)  
library(tidyverse)  
library(nycflights13)
```



What time is it?

```
# Show today's data
today()
# Show time and date for current time
now()
TodayDate <- today()
TimeNow <- now()
```

- What is the ***type of*** these variables?
- Now, try adding some seconds to the TimeNow variable.
Can you add some days or years to this variable?



Three Ways to Create Date and Time

- Depending on what you want to do with your code, you can work with dates:
- From a string.
- From individual date-time components.
- From an existing date/time object.





Convert Strings to Dates

```
# Use the built-in code provided by
lubridate to automatically format dates.

# Specify the order of the components:
year, month and day, then arrange "y",
"m", and "d" in the same order in command
name.

mdy("October 6th 2017")      # "2017-10-06"
dmy("06-Oct-2017")          # "2017-10-06"
ymd("2017-10-06")           # "2017-10-06"
ymd(20171006)                # "2017-10-06"
ydm(20171006)                # "2017-06-10"
```




Date and Time Strings


```
# Add the time in with the date and  
Coordinated Universal Time (UTC)
```

```
ymd_hms("2017-10-06 18:10:42")
```

```
mdy_hm("10/06/2017 08:10")
```

```
# Specify the timezone of the time
```

```
ymd(20171006, tz = "UTC")
```





Convert an object to a date or date-time with `as_datetime()` and `as_date()`

```
# Switch between a date-time and a date
```

```
now() # "2020-02-21 15:41:48 EST"
```

Note, myTime
contains both
time and date

```
myTime <- now() # "2020-02-21 15:42:41 EST"
```

```
as_date(myTime)
```

```
# gives just a date: "2020-02-21"
```

```
as_datetime(today())
```

```
# "2020-02-21 UTC"
```



Use the `lubridate()` to parse
each of the following dates:

```
# Consider these!  
d1 <- "January 1, 2010"  
d2 <- "2015-Mar-07"  
d3 <- "06-Jun-2017"  
d4 <- c("August 19 (2015)", "July 1  
(2015)")  
d5 <- "12/30/14" # Dec 30, 2014
```

Commands to try:
`dym()`, `mdy()` and `ymd()`



Parsing Specific Details

```
now() %>% ymd_hms()  
datetime <- ymd_hms("2018-10-16 12:01:13")  
year(datetime)  
month(datetime)  
mday(datetime) # (day of the month)  
yday(datetime) # (day of the year)  
wday(datetime) # (day of the week)  
hour(datetime)  
minute(datetime)  
second(datetime)
```



Parsing Specific Details

```
datetime <- ymd_hms("2018-10-16 12:01:13")  
# Get the month as a String  
month(datetime, label = TRUE) # short string  
month(datetime, label = TRUE, abbr = FALSE) # long  
  
# Get the day of the week as a string  
wday(datetime, label = TRUE, abbr = FALSE)
```



Parse Time and Date to Make Time Table

```
# load libraries if this has not been done
#library(tidyverse)
#library(nycflights13)
#View(flights)

timeTable <- flights %>% select(year, month,
day, hour, minute)
#what is this new table?
View(timeTable)
```

Pull out the time information from the flights data set.



Further Formatting

```
# Format a new column using mutate  
with the time data.
```

```
flights %>% select(year, month, day,  
hour, minute) %>% mutate(departure =  
  make_datetime(year, month, day,  
hour, minute))
```

Combine date and times information to make
a formatted “departure” column.

Note: *make_datetime()* is a built-in function.

Formatting: By Functions

```
flights %>%
  select(year, month, day, hour, minute) %>%
  mutate(departure = make_datetime(year, month,
    day, hour, minute))
```

**Can we automate
this formatting?**



```
> flights %>% select(year, month, day, hour, minute) %>%
  mutate(departure = make_datetime(year, month, day, hour,
    minute))
```

A tibble: 336,776 x 6

	year	month	day	hour	minute	departure
	<int>	<int>	<int>	<dbl>	<dbl>	<dtm>
1	2013	1	1	5	15	2013-01-01 05:15:00
2	2013	1	1	5	29	2013-01-01 05:29:00
3	2013	1	1	5	40	2013-01-01 05:40:00
4	2013	1	1	5	45	2013-01-01 05:45:00
5	2013	1	1	6	0	2013-01-01 06:00:00
6	2013	1	1	5	58	2013-01-01 05:58:00
7	2013	1	1	6	0	2013-01-01 06:00:00
8	2013	1	1	6	0	2013-01-01 06:00:00
9	2013	1	1	6	0	2013-01-01 06:00:00
10	2013	1	1	6	0	2013-01-01 06:00:00

... with 336,766 more rows



Format All Time Data In The Flights Table

The inputs from time details
are converted automatically

```
#Define a function with inputs: year, month,  
day and time
```

```
make_datetime_100 <- function(year, month,  
day, time) {  
  make_datetime(year, month, day, time %%  
100, time %% 100)  
}
```

Format All Time Data In The Flights Table

```
# Keep the dep_time and arr_time variables  
(rows) that exist (are not na)
```

```
flights_dt <- flights %>%  
  filter(!is.na(dep_time), !  
is.na(arr_time))  
  
%>%
```

```
# filter out the time components and pass  
the time data to a mutate function (next).
```

Code: part 1 of 3

Format All Time Data In The Flights Table

```
# format the individual times of the column:
mutate(
  dep_time = make_datetime_100(year, month,
    day, dep_time),
  arr_time = make_datetime_100(year, month,
    day, arr_time),
  sched_dep_time = make_datetime_100(year,
    month, day, sched_dep_time),
  sched_arr_time = make_datetime_100(year,
    month, day, sched_arr_time)) %>%
```

Code: part 2 of 3

Format All Time Data In The Flights Table



A photograph of an airport arrivals board. The board has a yellow header with the word "Arrivals" and a small airplane icon. Below the header, there are four columns of flight information. Each column lists flight numbers, origins, destinations, and arrival times. The text is small and somewhat blurry, but the layout is typical of an airport arrivals display.

```
# pull out the column headers (names) ending  
with "delay" or "time"
```

```
select(origin, dest, ends_with("delay"),  
ends_with("time"))
```

Code: part 3 of 3

```
make_datetime_100 <- function(year, month, day, time) {  
  make_datetime(year, month, day, time %% 100, time %%  
100) }  
  
flights_dt <- flights %>%  
  filter(!is.na(dep_time), !is.na(arr_time)) %>%  
  mutate(  
    dep_time = make_datetime_100(year, month, day, dep_time),  
    arr_time = make_datetime_100(year, month, day, arr_time),  
    sched_dep_time = make_datetime_100(year, month, day,  
sched_dep_time),  
    sched_arr_time = make_datetime_100(year, month, day,  
sched_arr_time)  
  ) %>%  
  select(origin, dest, ends_with("delay"), ends_with("time"))  
flights_dt %>% ggplot(aes(dep_time)) + geom_freqpoly(binwidth  
= 86400)
```

All code together with plotter



The Formatted Times in Table

```
View(flights_dt)
```

Now our time data looks like this and is formatted.

	origin	dest	dep_delay	arr_delay	dep_time	sched_dep_time
1	EWR	IAH	2	11	2013-01-01 05:17:00	2013-01-01 05:15:00
2	LGA	IAH	4	20	2013-01-01 05:33:00	2013-01-01 05:29:00
3	JFK	MIA	2	33	2013-01-01 05:42:00	2013-01-01 05:40:00
4	JFK	BQN	-1	-18	2013-01-01 05:44:00	2013-01-01 05:45:00
5	LGA	ATL	-6	-25	2013-01-01 05:54:00	2013-01-01 06:00:00
6	EWR	ORD	-4	12	2013-01-01 05:54:00	2013-01-01 05:58:00
7	EWR	FLL	-5	19	2013-01-01 05:55:00	2013-01-01 06:00:00
8	LGA	IAD	-3	-14	2013-01-01 05:57:00	2013-01-01 06:00:00
9	JFK	MCO	-3	-8	2013-01-01 05:57:00	2013-01-01 06:00:00



Quick Analysis:

What do the `dep_times` counts look like over the year, in days?

```
# We have formatted the time data and have made  
it convenient to insert into other functions.  
Let's plot it.
```

```
# We visualize the distribution of departure  
times across the year in day-size binwidths.
```


```
# note: 86400 seconds = 1 day
```

```
flights_dt %>% ggplot(aes(dep_time))  
+ geom_freqpoly(binwidth = 86400)
```

**Binwidths determine the
day-intervals during the year.**



Data By Year: Visualization of *dep_time*





Quick Analysis:


What do the dep_times counts look like on 1 and 2 of January?

```
# Now visualize this dep_time data by day.  
flights_dt %>% filter(dep_time < ymd(20130102))  
%>% ggplot(aes(dep_time)) +  
geom_freqpoly(binwidth = 600)  
# Note: 600 seconds = 10 minutes
```

**Binwidths determine the
minute-intervals during the day**



Data By Day: Visualization of *dep_time*






Quick Analysis!

When are most of the flights?

```
flights_dt %>%  
  mutate(wday = wday(dep_time, label = TRUE)) %>%  
  ggplot(aes(x = wday)) + geom_bar()
```


Aggregate by day of the week using wday()

More flights depart during the week days than on the weekend.





Average Departure Comparison






Quick Analysis!

What is the average departure delay
by minute, each hour?


```
flights_dt %>%  
  mutate(minute = minute(dep_time)) %>% group_by(minute) %>%  
  summarise(  
    avg_delay = mean(arr_delay, na.rm = TRUE),  
    n = n()) %>% ggplot(aes(minute, avg_delay)) + geom_line()
```

Flights leaving around
minutes 20-30
And 50-60, have
much lower delays
than the rest





Trend: Flights leaving in minutes 20-30 and 50-60 have lower delays than the rest of the hour.






Code to Add the Vertical Lines

```
# The average departure time delay by minute within  
the hour
```

```
flights_dt %>%  
  mutate(minute = minute(dep_time)) %>%  
  group_by(minute) %>%  
  summarise(  
    avg_delay = mean(arr_delay, na.rm = TRUE),  
    n = n()) %>%  
  ggplot(aes(minute, avg_delay)) + geom_line() +  
  geom_vline(xintercept = 20) +  
  geom_vline(xintercept = 30)
```



With the Vertical Lines






Quick Analysis!

Is there a (similar) pattern according to scheduled departure times?

```
sched_dep <- flights_dt %>% mutate(minute = minute(sched_dep_time)) %>%  
group_by(minute) %>%  
  summarise( avg_delay = mean(arr_delay, na.rm = TRUE), n = n())  
ggplot(sched_dep, aes(minute, avg_delay)) + geom_line()
```

No (real) pattern exists.

No pattern with the actual departure times?
Flights depart at times of convenience.
This is a bias that creeps into the
data since it is created by people.






Quick Analysis!

What do *human-selected* departure times look like, by the hour?

```
ggplot(sched_dep, aes(minute, n)) + geom_line()
```



Predictable!
it seems that
there are times
when flights
are more likely
to happen.