



Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering

# Introduction to Database Systems: CS312

## Advanced queries, joins and aggregates

Oliver BONHAM-CARTER

25 Sept 2020

# Joins: Bringing Data Together

## Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering



- The SQLite3 join-clause is used to combine records from two or more tables in a database.
- A **JOIN** is a means for combining fields from two tables by using values common to each.

# Joins: Visual Definitions

## Combining Tables

### Joins

Terms  
Cross Joins  
Inner Join  
Cartesian  
Products  
Left, Right




New  
Database

Sets

AS Clauses

Strings

Ordering



# SQL Code and Venn Diagrams

## Joins

### Terms

Cross Joins  
Inner Join  
Cartesian  
Products  
Left, Right

New  
Database


Sets

AS Clauses


Strings

Ordering


## SQL JOINS




```
SELECT <select_list>
FROM TableA A
LEFT JOIN TableB B
ON A.Key = B.Key
```




```
SELECT <select_list>
FROM TableA A
RIGHT JOIN TableB B
ON A.Key = B.Key
```




```
SELECT <select_list>
FROM TableA A
INNER JOIN TableB B
ON A.Key = B.Key
```




```
SELECT <select_list>
FROM TableA A
LEFT JOIN TableB B
ON A.Key = B.Key
WHERE B.Key IS NULL
```



```
SELECT <select_list>
FROM TableA A
RIGHT JOIN TableB B
ON A.Key = B.Key
WHERE A.Key IS NULL
```



```
SELECT <select_list>
FROM TableA A
FULL OUTER JOIN TableB B
ON A.Key = B.Key
```



```
SELECT <select_list>
FROM TableA A
FULL OUTER JOIN TableB B
ON A.Key = B.Key
WHERE A.Key IS NULL
OR B.Key IS NULL
```

# An explanation of terms

Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering

- SQL defines three major types of joins
  - The **CROSS JOIN**: Matches every row of the first table with every row of the second table. If the input tables have  $x$  and  $y$  columns, respectively, the resulting table will have  $x * y$  columns.
  - The **INNER JOIN**: Creates a new result table by combining column values of two tables (table1 and table2) based upon the join-predicate. The query compares each row of table1 with each row of table2 to find all pairs of rows which satisfy the join-predicate.

# Cross joins

Matches every row of the first table with every row of the second table.

- Cross join: *SELECT ... FROM table1 CROSS JOIN table2 ...*
- Automatically testing for equality between the values of every column that exists in both tables

## A practical example: Build a matrix of cards

```
CREATE TABLE ranks (  
    rank TEXT NOT NULL  
);  
  
CREATE TABLE suits (  
    suit TEXT NOT NULL  
);  
  
INSERT INTO ranks(rank)  
VALUES('2'),('3'),('4'),('5'),('6'),('7'),('8'),('9'),('10'),('J'),('Q'),('K'),('A');  
  
INSERT INTO suits(suit) VALUES('Clubs'),('Diamonds'),('Hearts'),('Spades');  
  
SELECT rank, suit  
FROM ranks  
    CROSS JOIN  
    suits  
ORDER BY suit;
```

# Inner joins

Joins two tables where values are equal and disregards the rest.

Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering

File: /sandbox/fruitJoin.txt

```
DROP TABLE TableA;  
CREATE TABLE TableA (  
  fruit VARCHAR,  
  colour VARCHAR);
```

```
DROP TABLE TableB;  
CREATE TABLE TableB (  
  fruit VARCHAR,  
  colour VARCHAR);
```

```
INSERT INTO TableA VALUES ("Lemons_A", "Yellow");  
INSERT INTO TableA VALUES ("Apples_A", "Red");  
INSERT INTO TableA VALUES ("Grapes_A", "Purple");
```

```
INSERT INTO TableB VALUES ("Lemons_B", "Yellow");  
INSERT INTO TableB VALUES ("Apples_B", "Red");  
INSERT INTO TableB VALUES ("Oranges_B", "Orange");
```

```
.tables
```

```
SELECT * from TableA;  
SELECT* from TableB;
```

```
SELECT TableA.fruit, TableA.colour, TableB.colour, TableB.fruit  
FROM TableA  
INNER JOIN  
TableB ON TableB.colour == TableA.colour;
```

# Inner joins

Joins two tables where values are equal and disregards the rest.

Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering

File: /sandbox/fruitJoin.txt

```
SELECT
    TableA.fruit, TableA.colour,
    TableB.colour, TableB.fruit
FROM
    TableA
INNER JOIN
    TableB ON TableB.colour == TableA.colour;
```

## Output

```
Lemons_A|Yellow|Yellow|Lemons_B
Apples_A|Red|Red|Apples_B
```



# Cross Join (Cartesian Product Demo)

Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering

- Inner join: *SELECT ... FROM table1 [INNER] JOIN table2 ON conditional\_expression ...*
- Combines column values of two tables (table1 and table2) based upon the join-predicate

## Create TableA and TableB

```
drop table tableA;  
create table tableA (  
    num VARCHAR);
```

```
drop table tableB;  
create table tableB (  
    num VARCHAR);
```

# Cross Joins (Cartesian Product Demo)

Joins

Terms

Cross Joins

Inner Join

Cartesian  
Products

Left, Right

New

Database

Sets

AS Clauses

Strings

Ordering

## Populate TableA and TableB

```
INSERT INTO tableA VALUES (1);  
INSERT INTO tableA VALUES (2);  
INSERT INTO tableA VALUES (3);  
INSERT INTO tableA VALUES (4);
```

```
INSERT INTO tableB VALUES (1);  
INSERT INTO tableB VALUES (2);  
INSERT INTO tableB VALUES (3);  
INSERT INTO tableB VALUES (4);  
INSERT INTO tableB VALUES (5);  
INSERT INTO tableB VALUES (6);  
INSERT INTO tableB VALUES (7);  
INSERT INTO tableB VALUES (8);  
INSERT INTO tableB VALUES (9);
```

# Joins

## CROSS JOIN: Cartesian Products

Joins

Terms

Cross Joins

Inner Join

Cartesian  
Products

Left, Right

New


Database

Sets

AS Clauses

Strings

Ordering



```
SELECT * FROM tableA CROSS JOIN tableB
```

```
SELECT * from TableA CROSS JOIN TableB;
SELECT * from tableA, TableB;
```

# Inner Joins

Joins

Terms

Cross Joins

Inner Join

Cartesian

Products

Left, Right

New


Database

Sets

AS Clauses

Strings

Ordering



Left: Blue and Green in Venn Diagram, Above

```
/* inner (left) join */  
SELECT TableA.num FROM TableB LEFT JOIN TableA ON TableA.num == TableB.num;  
SELECT count(TableA.num) FROM TableB LEFT JOIN TableA ON TableA.num == TableB.num;
```

Right: Yellow and Green in Venn Diagram, Above

```
/* inner (right) join */  
SELECT TableB.num FROM TableA LEFT JOIN TableB ON TableA.num == TableB.num;  
SELECT count(TableB.num) FROM TableA LEFT JOIN TableB ON TableA.num == TableB.num;
```

- How many spaces did you count from each query?
- What do the spaces tell you?

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering



(A New Database!)



Schema: Red boxes are the tables of today's database study


Schema: Red boxes are the tables of today's database study

## New Database

## AS Clauses

## Strings

## Ordering



**Figure 2.8** Schema diagram for the university database.

# New Database

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- Find the database maker file, *campusDB\_build.txt*, in your sandbox directory

```
cat campusDB_build.txt | sqlite3 myCampusDB.sqlite3
```

# Set Operations

## OR & AND

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- **OR:** Find all deptNames in the **UNION** of Instructor and Course

- `select deptName from Instructor UNION select deptName from course;`
- `select distinct(deptName) from Instructor;`

- **AND:** Find all deptNames in the **INTERSECT** of Instructor and Course

- `select deptName from Instructor INTERSECT select deptName from Course;`
- `select distinct(Instructor.deptName) from Instructor, Course where Instructor.deptName == Course.deptName;`



# Set Operations

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- `select distinct(deptName) from Instructor;`
- `select distinct(deptName) from Course;`

- The EXCEPT operator compares the result sets of two queries and returns distinct rows from the left query that are not in the output by the right query.
- Find all deptNames different to both the *Instructor* and *Course*
- Check these two queries below. Why is the output different?

- `select deptName from Instructor EXCEPT select deptName from Course;`
- `select deptName from Course EXCEPT select deptName from Instructor;`

# AS clauses

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- The **AS** clause is used to rename relations; useful for reducing necessary code in queries
- Ex: *For all instructors in the university who have taught some course, find their names and the course ID of all their taught courses*
  - Select I.name, T.courseID  
FROM Instructor AS I , Teaches AS T  
WHERE I.ID= T.ID;
- On the second line:
  - the Instructor table is renamed to I
  - the Teaches table is renamed to T.

- Another reason to rename a relation is a case where we wish to compare tuples in the same relation.
- We then need to take the Cartesian product of a relation with itself and, without renaming, it becomes impossible to distinguish one tuple from the other.
- Suppose that we want to write the query, *find the names of all instructors whose salary is greater than at least one instructor in the Math department.*
  - ```
SELECT DISTINCT T.name
FROM Instructor as T ,
Instructor AS S
WHERE T.salary > S.salary and S.deptName == "Math"
```

- Find all names of common teachers in Instructor and Teaches tables

Use AS to implement variables attributes to hold places

- ```
select distinct(Instructor.name) as newName from  
Instructor, teaches where Instructor.ID =  
teaches.ID and newName == "Thompson";
```

# AS clauses

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- Find the names of all Instructors whose salary is greater than at least one Instructor in the Math department.
- `select distinct(T.name) from Instructor as T,  
Instructor as S where T.salary > S.salary and  
S.deptName == "Math";`
- `select distinct T.name, T.salary from Instructor as  
T, Instructor as S where T.salary > S.salary and  
S.deptName == "Math";`
- Reference: `select * from Instructor;`

# Regular Expression-ish

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- Textual *wildcards* to recover information from partial knowledge.
- Finding substrings using the % and \_ operators.

- `select name from Instructor where name like "%ille%";`
  - Selects *Miller* from a substring
- `select name from Instructor where name like "%son";`
  - Selects all names followed by "son" substring
- Compare to: *Select \* from Instructor;*
- `select name from Instructor where name like "__ll__";`
- `select name from Instructor where name like "__ll___";`
  - Selects "Miller" or "William" from the number of spaces after the "ll";.

# Regular Expression-ish

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

- Find special pattern characters (i.e., "%" and "\_") in strings
- SQL even allows the specification of an escape character.

- **like 'ab\%cd%' escape '\'** matches all strings beginning with "ab%cd".
- **like 'ab\\cd%' escape '\'** matches all strings beginning with "ab\cd".

# Ordering Results

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

Having

- SQL allows for sorting the output.
- Output is sorted alphabetically

- `select name from Instructor order by name;`
- `select name,salary from Instructor order by salary;`
  - Provides numerical values in an interval



# “Intermediate” Results Using **HAVING**

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

Having

- The **HAVING** clause enables you to specify conditions that filter which group results appear in the final results.
- The **HAVING** clause must follow the GROUP BY clause in a query and must also precede the ORDER BY clause if used.

## Pseudo-code

```
SELECT column1, column2  
FROM table1, table2  
WHERE [ conditions ]  
GROUP BY column1, column2  
HAVING [ conditions ]  
ORDER BY column1, column2
```

# Group By

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

Having

- Give the number of names, and names of all members of departments who make less than 100000.

- ```
select count(name), deptName from Instructor GROUP BY  
deptName HAVING salary < 100000;
```

- Give the deptNames and the average salaries for departments that begin with the letter 'C'.

- ```
select deptName, avg(salary) from Instructor group by  
deptName HAVING deptName LIKE "C%";
```

# Group By

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

Having

- Give the department names and salaries from the Instructor group for whose members make between 97K and 100K.

- `select deptName, salary from Instructor group by deptName  
HAVING salary < 100000 and salary > 97000;`

- Compare to: Give me deptName and salary information where the salary is between 97K and 100K.

- `select deptName, salary from Instructor where salary <  
100000 and salary > 97000 group by deptName;`

# Use avg to Query

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

Having

- `select deptName, avg(salary) from Instructor group by deptName;`
  - Report average salaries for departments
- `select deptName, avgSalary FROM (select deptName, avg(salary) as avgSalary from Instructor group by deptName) where avgSalary > 97000;`
  - Report average salaries larger than \$97k. This query is similar to one using the **HAVING** clause. Here we use the **FROM** clause.

# Ordering Result Using BETWEEN

Joins

New  
Database

Sets

AS Clauses

Strings

Ordering

Having

- SQL allows for sorting the output by criteria
- Output is sorted for values in an interval

- `select name, salary from Instructor where salary <= 100000 and salary >= 90000;`
- `select name, salary from Instructor where salary between 70000 and 100000;`
  - Query values in their intervals.