



Introduction to Database Systems: CS312

A Larger Database system

Oliver Bonham-Carter

1 March 2022

ER Model Basics

Tables


Tables

Design

Persistent
Databases

Populate

Conditional
Queries



<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000

attributes
(or columns)

tuples
(or rows)

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000

- Four **attributes**: *ID*, *name*, *dept_name* and *salary*
- The **relation instance** refers to a finite set of tuples in the relational database system and represents a relation instance (i.e., a group of observations). Relation instances do not have duplicate tuples.
- The **instance** of the instructor table shown above has 12 tuples, corresponding to 12 instructors (12 *observations*)

Overview of The Entity-Relationship Model Design

Consider these!



- What is the *data* to store in the database?
- What are the *relationships* between the *entities* of information?
- What is the conceptual *design* of a system to link all this information together: the entity-Relationship (ER) model

E-R Models ... Entities? Relationships?

Section 1.6.3, The Entity-Relationship Model

Tables

Design

Entities

Schema

Null Values

Persistent
Databases

Populate

Conditional
Queries

Entities

- The entity-relationship (E-R) data model uses a collection of basic objects, called **entities**, and relationships exist to connect these objects.
- Entities are defined by attributes (i.e, *column headers* in tables)
- *ID*, *name*, and *salary* are points of information to describe an *instructor* entity

Relationships

- A *relationship* is an association among several *entities*
- For example, a member relationship associates an instructor with her department.
- The set of all *entities* of the same type and the set of all *relationships* of the same type are termed an *entity set* and *relationship set*, respectively.

E-R Models ... Entities? Relationships?

Section 1.6.3, The Entity-Relationship Model

Tables

Design

Entities

Schema

Null Values

Persistent

Databases

Populate

Conditional

Queries




Figure 1.3 A sample E-R diagram.

- *Entity sets* are represented by a rectangular box with the *entity set* name in the header and the attributes listed below it.
- *Relationship sets* are represented by a diamond connecting a pair of related *entity sets*. The name of the *relationship* is placed inside the diamond.

ER Model Basics

Schemas and Relationships

Tables

Design

Entities


Schema

Null Values

Persistent
Databases

Populate

Conditional
Queries



- Relationship Set: A collection of similar relationships for entities
- Relationship sets can also have *descriptive attributes* (i.e., the “since” attribute of *WorksIn*)

Displaying schemas

We create some tables to find schema

Tables

Design

Entities

Schema

Null Values

Persistent
Databases

Populate

Conditional
Queries

- A **schema** resembles a subroutine and describes the table and the data that it contains.

```
CREATE TABLE employees
( name VARCHAR,
  ssn VARCHAR,
  lot VARCHAR);
```

```
CREATE TABLE dept
( discipline VARCHAR,
  building VARCHAR,
  status VARCHAR);
```

```
CREATE TABLE workin
( since VARCHAR);
```

.schema

Null Values

What needs to be included in a table's values?

Tables

Design

Entities

Schema

Null Values

Persistent
Databases

Populate

Conditional
Queries

Definition: Null Values

- SQLite NULL is the term used to represent a missing value. A NULL value in a table is a value in a field that appears to be blank.
- A field with a NULL value is a field with no value. It is very important to understand that a NULL value is different than a zero value or a field that contains spaces (i.e, 0 or " ").

Null and Non Nulls

- When you CREATE a table, you can specify whether or not NULL or NOT NULL values can be accepted (i.e., inserted into table).
- Once a NOT NULL constraint is attached to a column, then an insertion or an update involving a NULL (i.e., a nothing value) will be rejected (i.e., a constraint violation).
- NOT NULL signifies that the column should always accept an explicit value of the given data type.

Null Values

Tables

Design

Entities

Schema

Null Values

Persistent

Databases

Populate

Conditional
Queries

Pseudocode Form

```
CREATE TABLE table_name (  
    ...  
    column_name type_name NOT NULL,  
    ... );
```

SQL Code

```
CREATE TABLE secretNames(  
    name VARCHAR,  
    codeName VARCHAR NOT NULL,  
    role VARCHAR );
```

Example

```
INSERT INTO secretNames  
VALUES("SherlockHolmes",221,"Consulting Detective");
```

```
INSERT INTO secretNames  
VALUES("JamesWatson",201,"Wing Guy");
```

Will this command work?

```
INSERT INTO secretNames  
VALUES("BillyBob",NULL,"Wing guy");
```

Will this command work?

- What happened? Why?

We've got it!

Tables

Design

Entities

Schema

Null Values

Persistent
Databases

Populate

Conditional
Queries



- Let's build a relational database in SQLite3!!

Let's Make a Persistent Database!

Tables

Design

Persistent
Databases

Populate

Conditional
Queries

The data

```
1|Ezra|Weston Loomis|Pound|30/10/1885|1/11/1972|USA
2|Arthur|Conan|Doyle|05/22/1859|07/7/1930|UK
3|Ernest|Miller|Hemingway|07/21/1899|07/02/1961|USA
4|John|Edward|Williams|08/22/1922|03/3/1994|USA
```

Attributes

- ID
- first name
- middle name
- last name
- birth date
- death date
- country of origin

Create the file!

Tables

Design

Persistent
Databases

Populate

Conditional
Queries

The terminal command to open a new database

```
sqlite3 writers.sqlite3
```

```
obonhamcarter$ sqlite3 writers.sqlite3
SQLite version 3.19.3 2017-06-27 16:48:08
Enter ".help" for usage hints.
sqlite>
```

Create Table command

```
CREATE TABLE Writers (  
    id INTEGER NOT NULL PRIMARY KEY,  
    first_name VARCHAR NOT NULL,  
    middle_name VARCHAR,  
    last_name VARCHAR NOT NULL,  
    birth_date VARCHAR NOT NULL,  
    death_date VARCHAR,  
    country_of_origin VARCHAR NOT NULL );
```

- Note: NOT NULL ensures that this field is not left blank when populating

Add Data for writers Table

Tables

Design

Persistent
Databases

Populate

Conditional
Queries

Insert Commands

```
INSERT INTO Writers VALUES(1, 'Ezra', 'Weston Loomis', 'Pound', '30/10/1885',  
'1/11/1972', 'USA');  
INSERT INTO Writers VALUES(2, 'Arthur', 'Conan', 'Doyle', '05/22/1859',  
'07/7/1930', 'UK');  
INSERT INTO Writers VALUES(3, 'Ernest', 'Miller', 'Hemingway', '07/21/1899',  
'07/02/1961', 'USA');  
INSERT INTO Writers VALUES(4, 'John', 'Edward', 'Williams', '08/22/1922',  
'03/3/1994', 'USA');
```

Tables and Schema

- What is the schema (i.e., the arrangement of data) of your database?
 - Type in **“.schema”** and see!
- What are the tables of your database?
 - Type in **“.tables”** and see!

Conditional Queries

Adding conditional clauses to queries

Tables

Design

Persistent
Databases

Populate

Conditional
Queries

Queries to play with using conditional clauses

```
select * from Writers where country_of_origin == "UK";
```

```
select * from Writers where country_of_origin == "USA";
```

```
select * from Writers where birth_date == "08/22/1922";
```

```
select * from Writers where first_name == "Arthur";
```

What else can you query using this code?

Save your DB and exit with following command:

.exit

Consider this...

Please see the *sandbox* file for code.

Tables

Design

Persistent
Databases

Populate

Conditional
Queries



THINK

- Can you populate your base by adding more data?
- Can you also check that the data was correctly stored in the table?
- Can you run queries to access particular attributes?