

```

Database changed
mysql> CREATE TABLE employees (
  ->     id INT,
  ->     name VARCHAR(100),
  ->     email VARCHAR(100)
  -> );
Query OK, 0 rows affected (0.07 sec)

mysql> INSERT INTO employees (id, name, email)
  -> VALUES (1, 'Harry Potter', 'pharry@warnerbros.com');
Query OK, 1 row affected (0.04 sec)

mysql>
mysql> INSERT INTO employees (id, name, email)
  -> VALUES (2, 'Clark Kent', 'kclark@dccomics.com');
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> INSERT INTO employees (id, name, email)
  -> VALUES (3, 'Tony Stark', 'stony@marvel.com');
Query OK, 1 row affected (0.05 sec)

mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE build_email_list(INOUT email_list VARCHAR(4000))
  -> BEGIN
  ->     DECLARE v_finished INT DEFAULT 0;
  ->     DECLARE v_email VARCHAR(100) DEFAULT '';
  ->
  ->     DECLARE email_cursor CURSOR FOR
  ->         SELECT email FROM employees;
  ->
  ->     DECLARE CONTINUE HANDLER FOR NOT FOUND
  ->         SET v_finished = 1;
  ->
  ->     OPEN email_cursor;
  ->
  ->     get_email: LOOP
  ->         FETCH email_cursor INTO v_email;
  ->
  ->         IF v_finished = 1 THEN
  ->             LEAVE get_email;
  ->         END IF;
  ->
  ->         SET email_list = CONCAT(v_email, ';', email_list);
  ->
  ->     END LOOP get_email;
  ->     CLOSE email_cursor;
  -> END $$
Query OK, 0 rows affected (0.04 sec)

```

```

mysql>
mysql> DELIMITER ;
mysql> SET @email_list = '';
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> CALL build_email_list(@email_list);
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> SELECT @email_list;
+-----+
| @email_list                                     |
+-----+
| stony@marvel.com;kclark@dccomics.com;pharry@warnerbros.com; |
+-----+
1 row in set (0.00 sec)

```