

```

Database changed
mysql> CREATE TABLE CUSTOMER (
  ->     CNAME VARCHAR(30),
  ->     CREDITLIMIT INT
  -> );
Query OK, 0 rows affected (0.07 sec)

mysql> INSERT INTO CUSTOMER VALUES
  -> ('DANISH', 30000),
  -> ('NAGARAJ', 60000),
  -> ('RAM', 15000),
  -> ('SARAN', 5000);
Query OK, 4 rows affected (0.05 sec)
Records: 4  Duplicates: 0  Warnings: 0

mysql> DELIMITER //
mysql>
mysql> CREATE FUNCTION CustomerLevel(CREDITLIMIT INT)
  -> RETURNS VARCHAR(20)
  -> DETERMINISTIC
  -> BEGIN
  ->
  ->     DECLARE level VARCHAR(20);
  ->
  ->     IF CREDITLIMIT > 50000 THEN
  ->         SET level = 'PLATINUM';
  ->
  ->     ELSEIF CREDITLIMIT >= 10000 AND CREDITLIMIT <= 50000 THEN
  ->         SET level = 'GOLD';
  ->
  ->     ELSE
  ->         SET level = 'SILVER';
  ->
  ->     END IF;
  ->
  ->     RETURN level;
  ->
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql> SELECT CNAME, CustomerLevel(CREDITLIMIT)
  -> FROM CUSTOMER
  -> ORDER BY CNAME;
+-----+-----+
| CNAME | CustomerLevel(CREDITLIMIT) |
+-----+-----+
| DANISH | GOLD                        |
| NAGARAJ | PLATINUM                    |
| RAM    | GOLD                        |
| SARAN  | SILVER                      |
+-----+-----+
4 rows in set (0.03 sec)

```

```

mysql> SET @@GLOBAL.max_sp_recursion_depth = 255;
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> SET @@session.max_sp_recursion_depth = 255;
Query OK, 0 rows affected (0.00 sec)

mysql> DELIMITER //
mysql> CREATE PROCEDURE factorial(IN n INT, OUT result INT)
-> BEGIN
->
->     IF n = 0 OR n = 1 THEN
->         SET result = 1;
->
->     ELSE
->         CALL factorial(n - 1, result);
->         SET result = n * result;
->
->     END IF;
->
-> END //
Query OK, 0 rows affected (0.05 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL factorial(5, @result);
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> SELECT @result;
+-----+
| @result |
+-----+
|      120 |
+-----+
1 row in set (0.00 sec)

```